

- > Energy Saving 20 Watt Integrated LED
- > Save up to \$220 over the life of the fixture
- > Cool White 4000K CCT
- > With PIR Sensor
- > Tool Free Adjustability
- > Lasts 45 years* or 50,000 Hours Continuous Use
- > 5 Year Limited Warranty

2-head Security Light with PIR Sensor (White)

1800 lm | 120VAC | Model 51402242 | Part SC-20-840-SV-OS-W




SPECIFICATIONS

Model	51402242	
Part	SC-20-840-SV-OS-W	
Description	2-head Security Light with PIR Sensor (White)	
Input Voltage (VAC)	120	
Wattage	20	
Dimmability	NA	
Average Rated Life ¹	50,000 hours	
Typical Lumens ²	1800	
CCT ³	4000K	
Location Rating	UL Wet	lighting fa
CRI⁴	80	
Beam Angle	67°	Light Output (Lumens)
Operating Temperature	Min -13°F (-25° C), Max 113°F (45° C)	Watts Lumens per Watt (Efficacy
Power Factor	>0.9	Color Accuracy
R9	-5	Color Rendering Index (CRI)
DUV	0.00075	Light Color Correlated Color Temperature (CCT)
CBCP	1500	Correlated Color Temperature (CCT)
Operating Frequency (Hz)	60	Warm White Bright White

1 Hours lifetime with 70% lumen maintenance 2 Thermally stable typical lumens (±10%) 3 Thermally stable CCT (±10%)

4 Color rendering index/Ra





TO ORDER: www.ETiSSL.com Call: 1.855.ETi.SSLI 1.855.384.7754



2-head Security Light with PIR Sensor (White)

1800 lm | 120VAC | Model 51402242 | Part SC-20-840-SV-OS-W

SHIPPING INFORMATION

Model	51402242
Part	SC-20-840-SV-OS-W
UPC	849489009995
Product Dimensions (L x W x H in.)	6.89 x 4.53 x 5.51
Product Dimensions (L x W x H cm.)	17.5 x 11.5 x 14.0
Product Weight (lbs.)	2.03
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	6
Master Carton Bar Code	50849489009969
Master Carton Dimensions (L x W x H in.)	21.81 x 18.35 x 7.01
Master Carton Dimensions (L x W x H cm.)	55.4 x 46.6 x 17.8
Master Carton Weight (Ibs)	17.37
Pallet Quantity	360

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see www.ETiSSL.com/fcc15b

ETi Solid State Lighting, Inc. 720 Corporate Woods Parkway Vernon Hills, IL 60061 Phone: 855.384.7754 Fax: 847.383.6256

TO ORDER: www.ETiSSL.com Call: 1.855.ETi.SSLI 1.855.384.7754