

# DF1/DF2 Series Faucet Mount Water Filter User's Manual

## Product Benefits

- Removes chlorine, chloramine, germs, cysts, lead, mercury, lindane, atrazine, VOCs & many other contaminants.
- Improves the taste of tap water.
- Fast flow rate of up to 1.5 GPM with long-lasting filter life up to 500 Gallon.

## Precautions

1. Install with normal or lower water pressure (below 70psi).
2. Install using standard tap water sources.
3. Maximum temperature: 100 °F; Minimum temperature: 40 °F

## Installation

Installation varies depending on the bath or kitchen faucet you are installing the filter on.



1. Included with the package are a metal adapter with 2 male ends, a universal adapter and sealing washers.
2. Remove the aerator from the faucet if it has one. For faucets with external threads, place the sealing washer into the metal connector of the faucet filter and connect to the faucet. If your faucet has fewer threads, add the sealing washer from the metal adapter into the connector as well for a better seal. For faucets with internal threads, use the metal adapter to connect the faucet filter to the faucet. For faucets without aerators, attach the universal adapter to the outside of the faucet.
3. Turn on the faucet. Turn the diverter handle in line with the connector for regular tap water.
4. Turn the diverter handle perpendicular to the connector for filtered water. To flush out the loose carbon, keep the faucet on for a couple of minutes until water runs clear.

## Usage Recommendations

1. Let the water run for 10 seconds before use every day.
2. If the product has not been used for more than two days, let the water run for one minute before use.
3. Do not use the product when the filter is unscrewed
4. The service life of the product may vary according to water quality, pressure, and usage frequency. For details, please refer to "Filter Replacement".
5. For areas with higher water pressure, turn down the tap water valve before use.

6. Do not use the product near heat sources.
7. Do not clog the water outlet or connect other adapters.
8. Do not disconnect the filter while it is in use.
9. Do not use detergents, ethanol or other cleansers to clean the product.

### **Filter Replacement**

*Replace filter every 6-8 months or 500 gallons depending on water quality and usage in order to guarantee the best water quality.*

1. Unscrew the housing cap.
2. Replace the filter cartridge.
3. Reinstall and test the water to complete the replacement.

Check the sealing ring carefully for any problems to avoid water leakage.

### **Limited Warranty**

iSpring provides a **30-day Money Back Guarantee, 1 year Manufacturer Warranty** and **LifetimeTech Support** to all products. However, we do not have the order information from the vendors other than 123Filter.com. The easiest way to activate the warranty is to forward your order confirmation email to [support@ispringfilter.com](mailto:support@ispringfilter.com) or register it on 123filter.com, along with your comment; or if you prefer, please fill out and mail the form below. Please remember, we love to help our customers. If you have any questions or concerns about our products, please don't hesitate to call or email us. We will do everything we can to make your purchase a 5-star experience.

If you are happy with our product and service, please show your support by writing a product review on the channel you purchased it from, even if it's just a single line. It takes you just a minute, but means a lot to us. Thank you!



<b>iSpring Warranty Registration Form</b>	
<b>Your Name:</b>	
<b>Your Address:</b>	
<b>Your E-Mail:</b>	
<b>Your Phone:</b>	
<b>Order#:</b>	
<b>Order From:</b>	
<b>Model#:</b>	
<b>Order Date:</b>	
<b>Reviewer ID:</b>	
<b>Notes:</b>	

**Phone:** 1-678-261-7611  
**Fax:** 1- 678-530-1070  
**Hours:** M-F 9 AM–5 PM EST  
**Technical Support Hours:**  
 M-F 9 AM–5 PM EST  
**Email:** support@ispringfilter.com  
**Mailing Address:**  
 iSpring Water Systems  
 3020 Trotters Pkwy  
 Alpharetta, GA 30004 USA