



**A Outside Corner (Female)** - has two 1/2" welded tabs. Use with a male outside corner. Each leg is 10"L x 5"H.  
RHH-OCF WT 9.0

**B Outside Corner (male)** - has one 1/2" welded tab. Use with a female outside corner to connect docks end to end. Joint requires 3/4" bolt set or connector pin (L). Each leg is 10"L x 5"H.  
RHH-OCM WT 8.5

**C Outside Corner End** - use this corner at ends of fingers and docks. Ideal for swim floats and ski jump corners. Each leg is 10"L x 5"H.  
RHH-OCE WT 7.0

**D Inside Corner** - this heavy-duty inside corner should be used with one of the outside corners. Each leg has elongated holes for easy fit-up and is 8-1/4"L x 6"H  
RHH-IC WT 6.5

**E Inside Corner/Pipe Holder 3"** - these heavy-duty inside corners should be used with one of the outside corners and has an internal pipe holder to be used with 2" pipe. Welded gusset gives strength to the dock's frame. Measures 8-1/4"L x 5"H. Requires carriage bolt set for attaching  
RHH-O1C3 WT 11.5

**F Angle** - use this heavy-duty angle for all cross supports. Each leg measures 2-1/2"L x 5"H.  
RHH-A WT 1.75

**G Female T Connector** - has two welded 1/2" tabs. Bolts to side of dock to attach fingers and ramps. 5"L x 5"H.  
RHH-SF WT 3.5

**H Male T Connector** - has one welded 1/2" tab. Use with female T connector to attach fingers and ramps. 5"L x 5"H. 3/4" bolt set required for joint.  
RHH-SM WT 3.25

**I Washer Plate** - use two washer plates with each angle. Measures 1-1/2"L x 5"H.  
RHHW WT 0.5

**J Chain Retainer** - bolts to side of dock. Use weights and chains to hold dock in place. Accommodates 1/4", 3/8", & 1/2" chain. Measures 5"L x 5"H.  
RHCH WT 3.75

**K Pipe Holder/Outside 3"** - bolts to outside of dock. Carriage bolt set required for attaching. Use 2" pipe to hold dock in place.  
RHP-3 WT 8.25

**L Connector Pin Set** - for quick disconnect. Used to connect male and female connectors. Galvanized 3/4" connector pin and hitch clip pin.  
RHBPIN

**Cellofoams' Dock Hardware** is designed for use with 1-1/2" thick lumber (minimum width 6"). All hardware is mounted with 1/2" carriage bolts. All male and female dock to dock connections are made with either 3/4" bolts with lock nuts or 3/4" connecting pins (L).

For orders and customer service requests, contact us at  
**800-531-4734**

floats@cellofoamna.com  
[www.cellofoam.com](http://www.cellofoam.com)