

# CEMENT TILE SEALING GUIDE

## CAUTION:

Please follow sealer manufacturer's instructions exactly for the best results.

## PREPARATION:

Be sure that the surface is clear of any contaminants prior to sealing. Test on scrap tile or in a hidden section to see the results of this sealer prior to sealing the whole installation. Allow 24 hours to dry to determine desired results, and then test for possible stains using likely staining contaminants. Use caution when using this product. For safety purposes, it is recommended that you wear chemical resistant gloves and protective eyewear.

## APPLICATION:

When sealing cement tiles, you will want to use the sealer prior to grouting. You can use a cotton towel, sponge, brush, paint pad, or sprayer to install the sealer. Apply even coats in moderation, and if sealer does not absorb into the tile, be sure to wipe excess sealer off the surface with a cotton towel or absorbent paper. We recommend doing 2-3 coats of sealer. Allow 30 minutes between coats. Two hours after your final coat, test the sealer by pouring water droplets onto the tile surface. If water absorbs into the surface, you should apply another coat. When you have reached the desired amount of coats for your installation, allow it to dry for a full 24 hours prior to grouting. Please be advised that it is recommended that you reseal cement tiles once a year to prolong their life.



**RECOMMENDED SEALER: AQUA MIX GOLD BY CUSTOM® BUILDING PRODUCTS**  
**IF YOU HAVE ANY QUESTIONS ABOUT SEALING**  
**REACH OUT TO THE SEALER MANUFACTURER.**

