

SPECIFICATIONS

Model Number	920013	920014	920022	920021
Description	Compact 22	Compact 24	Compact 24 Track	Compact 24
Engine	Ariens AX	Briggs & Stratton Polar Force	Ariens AX	
Gross Torque* – lbf-ft (N•m)	9.5 (12.9)			
*Engine output stated in gross torque per SAE J1940 as rated by engine manufacturer.				
Displacement – in. (cc)	12.7 (208)			
High Idle – RPM (min)	3600 ± 50	3600 ± 100	3600 ± 50	
Electric Start	120V			
Fuel Tank Capacity – qt (Liters)	2.9 (2.7)	3.2 (3.0)	2.9 (2.7)	
Headlight	Yes			
Chute				
Chute Rotation Angle	205°			
Rotation Control	2.5X Quick Turn			
Deflector Control	Manual	Remote		
Auger				
Snow Clearing Width – in. (cm)	22.0 (55.9)	24.0 (61.0)		
Gear Case	Cast Iron			
Auger Diameter – in. (cm)	11.0 (27.9)			
Impeller				
Impeller Diameter – in. (cm)	12.0 (30.5)			
Impeller Speed (RPM)	1190			
Impeller Tip Speed – ft/sec (m/s)	62.3 (19.0)			
Drive				
Blower Drive	HA Belt			
Drive System	Disc-O-Matic®			
Speeds	6 Forward and 2 Reverse			
Axle Control	Pin-Lock		Solid Axle	Pin-Lock
Pneumatic Tires – in. (cm)	13 x 4.10 – 6		–	15 x 5.00 – 6
Rubber Track	–		5.5 (13.97) Wide Directional Track	–
Size and Weight				
Length – in. (cm)	51.9 (131.8)			50.8 (129.0)
Height – in. (cm)	44.3 (112.5)		42.6 (108.2)	45.4 (115.3)
Width – in. (cm)	24.4 (62.0)	26.4 (67.0)		
Weight – lbs (Kg)	179.0 (81.2)	180.0 (81.6)	218.0 (98.9)	180.0 (81.6)