

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name : Wilsonart 740A Adhesive  
Product form : Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Adhesive for laminate

#### 1.3. Details of the supplier of the safety data sheet

Wilsonart LLC  
P.O. Box 6110  
Temple, TX 76503-6110  
Information phone: 800-433-3222 (USA)  
In Case of Emergency Contact CHEMTREC (International): 703-527-3887

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC: (800) 424-9300

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

|                       |      |
|-----------------------|------|
| Flam. Aerosol 1       | H222 |
| Pressurized Container | H229 |
| Compressed Gas        | H280 |
| Asp. Tox. 1           | H304 |
| Skin Irrit. 2         | H315 |
| Skin Sens. 1B         | H317 |
| Eye Irrit. 2A         | H319 |
| Repr. 2               | H361 |
| STOT SE 3             | H336 |
| STOT RE 2             | H373 |

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

**Danger**

Hazard statements (GHS-US) :

H222 - Extremely flammable aerosol  
H229 - Pressurized container: may burst if heated  
H280 - Compressed Gas  
H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness  
H361 - Suspected of damaging fertility or the unborn child  
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use  
P202 - Do not handle until all safety precautions have been read and understood  
P210 - Keep away from heat, open flames, sparks. - No smoking  
P211 - Do not spray on an open flame or other ignition source  
P251 - Pressurized container: Do not pierce or burn, even after use  
P260 - Do not breathe vapors, mist, fume, gas, spray  
P261 - Avoid breathing mist, spray, gas, vapors  
P264 - Wash hands, forearms and face thoroughly after handling  
P271 - Use only outdoors or in a well-ventilated area  
P272 - Contaminated work clothing must not be allowed out of the workplace  
P280 - Wear eye protection, face protection, protective gloves, face shield  
P301+P310 - IF SWALLOWED: Immediately call a poison center  
P302+P352 - If on skin: Wash with plenty of soap and water  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

# Wilsonart 740A Adhesive

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P308+P313 - If exposed or concerned: Get medical advice/attention  
P314 - Get medical advice/attention if you feel unwell  
P321 - Specific treatment (see first aid instructions on this label)  
P331 - Do NOT induce vomiting  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention  
P337+P313 - If eye irritation persists: Get medical advice/attention  
P362+P364 - Take off contaminated clothing and wash it before reuse  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed  
P405 - Store locked up  
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

No data available

## SECTION 3: Composition/Information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

| Name  | Product identifier  | %          |
|---|---------------------|------------|
| Propane   | (CAS No) 74-98-6    | 15 - 40*   |
| Dimethyl ether  | (CAS No) 115-10-6   | 15 - 40*   |
| Acetone   | (CAS No) 67-64-1    | 10 - 30*   |
| Pentane   | (CAS No) 109-66-0   | 3 - 7*     |
| Toluene   | (CAS No) 108-88-3   | 3 - 7*     |
| Distillates, petroleum, light distillate hydrotreating process, low-boiling | (CAS No) 68410-97-9 | 1 - 5*     |
| Isopentane  | (CAS No) 78-78-4    | 1 - 5*     |
| Cyclohexane   | (CAS No) 110-82-7   | 0.5 - 1.5* |
| Naphtha, petroleum, hydrotreated light                                      | (CAS No) 64742-49-0 | 0.1 - 1*   |
| Hexane  | (CAS No) 110-54-3   | 0.1 - 1*   |
| Proprietary ester resin   | Proprietary         | 0.1 - 1*   |

\*In accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR §1910.1200), the specific chemical identity or exact weight % has been withheld as a trade secret

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

- First-aid measures general : If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.
- First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention. If breathing is difficult, supply oxygen. If breathing has stopped, give artificial respiration.
- First-aid measures after skin contact : IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. If irritation develops or persists, get medical attention immediately.
- First-aid measures after eye contact : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. Continue rinsing if pain, blinking, or irritation develops or persists, get medical attention. Continue rinsing.
- First-aid measures after ingestion : IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : May be fatal if swallowed and enters airways. Causes serious eye irritation. Suspected of damaging fertility. Suspected of damaging the unborn child. Causes skin irritation. May cause damage to organs through prolonged or repeated exposure. May cause an allergic skin reaction. May cause drowsiness or dizziness. May displace oxygen and cause rapid suffocation.
- Symptoms/injuries after inhalation : May cause drowsiness or dizziness. May displace oxygen and cause rapid suffocation.
- Symptoms/injuries after skin contact : Causes skin irritation. May cause an allergic skin reaction.
- Symptoms/injuries after eye contact : Causes serious eye irritation.
- Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways.
- Chronic symptoms : Suspected of damaging fertility. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

# Wilsonart 740A Adhesive

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water fog.

Unsuitable extinguishing media : Direct water spray.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable aerosol.

Explosion hazard : Static discharge may serve as an ignition source for this product. Pressurized container: may burst if heated.

Reactivity : No dangerous reactions known under normal conditions of use.

#### 5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment. Prevent human exposure to fire, fumes, smoke and products of combustion.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Other information : Vapors may travel long distances along ground before igniting/flashing back to vapor source. This material is flammable and may be ignited by heat, sparks, or static electricity.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate area. Keep upwind. Ventilate area. Spill should be handled by trained clean-up crews properly equipped with respiratory equipment and full chemical protective gear (see Section 8). Avoid vapor formation. In case of spills, beware of slippery floors and surfaces. Eliminate all sources of ignition. Vapor may cause flash fires. Vapors are heavier than air and can travel long distances to ignition sources.

##### 6.1.1. For non-emergency personnel

Protective equipment : Wear Protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Remove all sources of ignition. Avoid breathing of vapors. Wear appropriate respirator and other protective clothing. Ventilate. Shut off source of leak only if safe to do so. Soak up with absorbent material, and place in non-leaking containers for proper disposal.

#### 6.4. Reference to other sections

See Sections 8 and 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, sparks and open flames. Use adequate ventilation and avoid repeated or prolonged skin contact. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Ground/bond container and receiving equipment. Prohibit smoking in storage area. Avoid contact with skin and eyes.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep container tightly closed. Isolate from oxidizers, heat, sparks, electrical equipment and open flame. Closed containers may explode if exposed to extreme heat. Store in a cool dry place. Prohibit smoking in storage area. Do not store with acids or oxidizers. Electrical service in storage area must be rated for flammable liquids.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

| Distillates, petroleum, light distillate hydrotreating process, low-boiling (68410-97-9) |                      |
|--|----------------------|
| Remark (ACGIH)   | OELs not established |
| Remark (OSHA)  | OELs not established |

# Wilsonart 740A Adhesive

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|  |   |
|--|---|
| <b>Isopentane (78-78-4)</b>                                |   |
| ACGIH TWA (ppm)  | 600 ppm (listed under Pentane, all isomers)   |
| Remark (OSHA)  | OELs not established  |
| <b>Pentane (109-66-0)</b>                                  |   |
| ACGIH TWA (ppm)  | 600 ppm (listed under Pentane, all isomers)   |
| OSHA PEL (TWA) (mg/m <sup>3</sup> )                        | 2950 mg/m <sup>3</sup>  |
| OSHA PEL (TWA) (ppm)                                       | 1000 ppm  |
| <b>Naphtha, petroleum, hydrotreated light (64742-49-0)</b> |   |
| Remark (ACGIH)   | OELs not established  |
| Remark (OSHA)  | OELs not established  |
| <b>Hexane (110-54-3)</b>                                   |   |
| ACGIH TWA (ppm)  | 50 ppm  |
| OSHA PEL (TWA) (mg/m <sup>3</sup> )                        | 1800 mg/m <sup>3</sup>  |
| OSHA PEL (TWA) (ppm)                                       | 500 ppm   |
| <b>Toluene (108-88-3)</b>                                  |   |
| ACGIH TWA (ppm)  | 20 ppm  |
| Remark (ACGIH)   | Visual impair; female repro;  |
| <b>Acetone (67-64-1)</b>                                   |   |
| ACGIH TWA (ppm)  | 500 ppm   |
| ACGIH STEL (ppm)   | 750 ppm   |
| OSHA PEL (TWA) (mg/m <sup>3</sup> )                        | 2400 mg/m <sup>3</sup>  |
| OSHA PEL (TWA) (ppm)                                       | 1000 ppm  |
| OSHA PEL (STEL) (mg/m <sup>3</sup> )                       | 2400 mg/m <sup>3</sup> (The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors) |
| OSHA PEL (STEL) (ppm)                                      | 1000 ppm  |
| <b>Propane (74-98-6)</b>                                   |   |
| ACGIH TWA (ppm)  | 1000 ppm (listed under Aliphatic hydrocarbon gases: Alkane C1-4)  |
| OSHA PEL (TWA) (mg/m <sup>3</sup> )                        | 1800 mg/m <sup>3</sup>  |
| OSHA PEL (TWA) (ppm)                                       | 1000 ppm  |
| DNEL   | >=  |
| <b>Dimethyl ether (115-10-6)</b>                           |   |
| Remark (ACGIH)   | OELs not established  |
| Remark (OSHA)  | OELs not established  |

### 8.2. Exposure controls

Appropriate engineering controls

: Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

: Safety glasses. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.



Hand protection

: Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl.

Eye protection

: Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.

Skin and body protection

: Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.

# Wilsonart 740A Adhesive

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory protection : Wear a NIOSH-approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions. In case of inadequate ventilation or risk of inhalation of vapors, use suitable respiratory equipment with gas filter (type A2). Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Appearance : Liquid adhesive in pressurized canister.  
Color : No data available  
Odor : Solvent.  
Odor Threshold : No data available  
pH : No data available  
Relative evaporation rate (butyl acetate=1) : No data available  
Melting point : No data available  
Freezing point : No data available  
Boiling point : No data available  
Flash point : -104 °C Open Cup (-156 °F)  
Auto-ignition temperature : 245 °C (Cyclohexane 473 °F)  
Decomposition temperature : No data available  
Flammability (solid, gas) : No data available  
Vapor pressure : No data available  
Relative vapor density at 20 °C : No data available  
Relative density : No data available  
Solubility : Water: Not soluble  
Log Pow : No data available  
Log Kow : No data available  
Viscosity, kinematic : No data available  
Viscosity, dynamic : No data available  
Explosive properties : No data available  
Oxidizing properties : No data available  
Explosion limits : 2.3 - 9.5 vol % (Propane)

#### 9.2. Other information

No additional information available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

#### 10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

#### 10.3. Possibility of hazardous reactions

None known.

#### 10.4. Conditions to avoid

Heat, flame. Ignition sources.

#### 10.5. Incompatible materials

Copper and copper alloys, strong acids, alkalies and oxidizers.

#### 10.6. Hazardous decomposition products

Carbon oxides (CO, CO<sub>2</sub>). Various hydrocarbons.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified

#### Isopentane (78-78-4)

LC50 inhalation rat (mg/l) : 280000 mg/m<sup>3</sup> 4 h

# Wilsonart 740A Adhesive

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| <b>Pentane (109-66-0)</b>  |                          |
|----------------------------|--------------------------|
| LD50 oral rat              | > 2000 mg/kg             |
| LD50 dermal rabbit         | 3000 mg/kg               |
| LC50 inhalation rat (mg/l) | 364 g/m <sup>3</sup> 4 h |

| <b>Naphtha, petroleum, hydrotreated light (64742-49-0)</b> |              |
|--|--------------|
| LD50 oral rat  | > 5000 mg/kg |
| LD50 dermal rabbit   | > 3160 mg/kg |
| LC50 inhalation rat (ppm)                                  | 73680 ppm/4h |

| <b>Hexane (110-54-3)</b>  |              |
|---------------------------|--------------|
| LD50 dermal rabbit        | 3000 mg/kg   |
| LC50 inhalation rat (ppm) | 48000 ppm/4h |

| <b>Toluene (108-88-3)</b>  |              |
|----------------------------|--------------|
| LD50 oral rat              | 2600 mg/kg   |
| LD50 dermal rabbit         | 12000 mg/kg  |
| LC50 inhalation rat (mg/l) | 12.5 mg/l/4h |

| <b>Acetone (67-64-1)</b>   |                         |
|----------------------------|-------------------------|
| LC50 inhalation rat (mg/l) | 50100 mg/m <sup>3</sup> |

| <b>Propane (74-98-6)</b>   |                 |
|----------------------------|-----------------|
| LC50 inhalation rat (mg/l) | 658 mg/l/4h     |
| ATE CLP (vapors)           | 658.000 mg/l/4h |
| ATE CLP (dust, mist)       | 658.000 mg/l/4h |

| <b>Dimethyl ether (115-10-6)</b> |                                |
|----------------------------------|--------------------------------|
| LC50 inhalation rat (mg/l)       | 308.5 mg/l/4h (Source: IUCLID) |

Skin corrosion/irritation : Causes skin irritation.  
Serious eye damage/irritation : Causes serious eye irritation.  
Respiratory or skin sensitization : May cause an allergic skin reaction.  
Germ cell mutagenicity : Not classified.  
Carcinogenicity : Not classified.

| <b>Benzene (71-43-2)</b>                 |                             |
|--|-----------------------------|
| IARC group                               | 1 - Carcinogenic to humans  |
| National Toxicology Program (NTP) Status | 2 - Known Human Carcinogens |

| <b>Ethylbenzene (100-41-4)</b> |                                      |
|--------------------------------|--------------------------------------|
| IARC group                     | 2B - Possibly carcinogenic to humans |

Reproductive toxicity : Suspected of damaging fertility or the unborn child.  
Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness.  
Specific target organ toxicity (repeated exposure) : May cause damage to organs through prolonged or repeated exposure.  
Aspiration hazard : May be fatal if swallowed and enters airways.  
Symptoms/injuries after inhalation : May cause drowsiness or dizziness. May displace oxygen and cause rapid suffocation.  
Symptoms/injuries after skin contact : Causes skin irritation. May cause an allergic skin reaction.  
Symptoms/injuries after eye contact : Causes serious eye irritation.  
Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways.  
Chronic symptoms : Suspected of damaging fertility. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.

## SECTION 12: Ecological information

### 12.1. Toxicity

No additional information available

### 12.2. Persistence and degradability

| <b>Wilsonart 740A Adhesive</b> |                                   |
|--------------------------------|-----------------------------------|
| Persistence and degradability  | The product is not biodegradable. |

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

# Wilsonart 740A Adhesive

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

- Waste treatment methods : Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without an NPDES permit.
- Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

## SECTION 14: Transport information

In accordance with DOT

- Transport document description : UN1950 Aerosols, flammable, 2.1, Limited Quantity
- UN-No.(DOT) : 1950
- DOT NA no. : UN1950
- Proper Shipping Name (DOT) : Aerosols, flammable
- Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
- Hazard labels (DOT) : 2.1 - Flammable gas



- DOT Quantity Limitations Passenger aircraft/rail : 75 kg  
(49 CFR 173.27)
- DOT Quantity Limitations Cargo aircraft only (49 : 150 kg  
CFR 175.75)
- DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel
- DOT Vessel Stowage Other : 25 - Shade from radiant heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

### Additional information

- Other information : Limited Quantity Exception applies under 49CFR.173.150 for containers <1L

### Transport by sea

No additional information available

### Air transport

No additional information available

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### Wilsonart 740A Adhesive

All components of this product are listed on the TSCA Inventory or are exempt

|                                     |   |
|-------------------------------------|---|
| SARA Section 311/312 Hazard Classes | Delayed (chronic) health hazard<br>Immediate (acute) health hazard<br>Fire hazard |
|-------------------------------------|---|

#### Cyclohexane (110-82-7)

|                       |                               |
|-----------------------|-------------------------------|
| Section 302 (EHS) TPQ |                               |
| Section 304 EHS RQ    |                               |
| CERCLA RQ             | 1000 lb                       |
| Section 313           | Listed on US SARA Section 313 |

#### Toluene (108-88-3)

|                       |                               |
|-----------------------|-------------------------------|
| Section 302 (EHS) TPQ |                               |
| Section 304 EHS RQ    |                               |
| CERCLA RQ             | 1000 lb                       |
| Section 313           | Listed on US SARA Section 313 |

#### Acetone (67-64-1)

|                       |  |
|-----------------------|--|
| Section 302 (EHS) TPQ |  |
|-----------------------|--|

# Wilsonart 740A Adhesive

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|                          |                                   |
|--------------------------|-----------------------------------|
| Section 304 EHS RQ       |                                   |
| CERCLA RQ                | 5000 lb                           |
| Section 313              | Not Listed on US SARA Section 313 |
| <b>Hexane (110-64-3)</b> |                                   |
| Section 302 (EHS) TPQ    |                                   |
| Section 304 EHS RQ       |                                   |
| CERCLA RQ                | 5000 lb                           |
| Section 313              | Listed on US SARA Section 313     |

### 15.2. International regulations

No additional information available.

### 15.3. US State regulations

WARNING! This product contains chemicals known to the state of California to cause cancer, birth defects, or other reproductive harm.

|   |   |   |   |                                   |
|---|---|---|---|-----------------------------------|
| <b>Benzene (71-43-2)</b>                              |   |   |   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| Yes   | Yes   | No  | Yes   | 6.4 µg/day                        |
| <b>Ethylbenzene (100-41-4)</b>                        |   |   |   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| Yes   | No  | No  | No  | 54 µg/day                         |
| <b>Toluene (108-88-3)</b>                             |   |   |   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| No  | Yes   | No  | No  | 7000 µg/day                       |

|   |  |  |  |  |
|---|--|--|--|--|
| <b>Cyclohexane (110-82-7)</b>   |  |  |  |  |
| U.S. - Massachusetts - Right To Know List                             |  |  |  |  |
| U.S. - New Jersey - Right to Know Hazardous Substance List            |  |  |  |  |
| U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List |  |  |  |  |

|  |  |  |  |  |
|--|--|--|--|--|
| <b>Isopentane (78-78-4)</b>                                |  |  |  |  |
| U.S. - Massachusetts - Right To Know List                  |  |  |  |  |
| U.S. - New Jersey - Right to Know Hazardous Substance List |  |  |  |  |
| U.S. - Pennsylvania - RTK (Right to Know) List             |  |  |  |  |

|  |  |  |  |  |
|--|--|--|--|--|
| <b>Pentane (109-66-0)</b>                                  |  |  |  |  |
| U.S. - Massachusetts - Right To Know List                  |  |  |  |  |
| U.S. - New Jersey - Right to Know Hazardous Substance List |  |  |  |  |
| U.S. - Pennsylvania - RTK (Right to Know) List             |  |  |  |  |

|  |  |  |  |  |
|--|--|--|--|--|
| <b>Hexane (110-54-3)</b>                                   |  |  |  |  |
| U.S. - Massachusetts - Right To Know List                  |  |  |  |  |
| U.S. - New Jersey - Right to Know Hazardous Substance List |  |  |  |  |
| U.S. - Pennsylvania - RTK (Right to Know) List             |  |  |  |  |

|  |  |  |  |  |
|--|--|--|--|--|
| <b>Benzene (71-43-2)</b>   |  |  |  |  |
| U.S. - Massachusetts - Right To Know List                                |  |  |  |  |
| U.S. - New Jersey - Right to Know Hazardous Substance List               |  |  |  |  |
| U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances |  |  |  |  |
| U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List    |  |  |  |  |

|   |  |  |  |  |
|---|--|--|--|--|
| <b>Ethylbenzene (100-41-4)</b>  |  |  |  |  |
| U.S. - New Jersey - Right to Know Hazardous Substance List            |  |  |  |  |
| U.S. - Massachusetts - Right To Know List                             |  |  |  |  |
| U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List |  |  |  |  |



# Wilsonart 740A Adhesive

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Toluene (108-88-3)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List  
U.S. - Pennsylvania - RTK (Right to Know) List

### Acetone (67-64-1)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

### Propane (74-98-6)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

### Dimethyl ether (115-10-6)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List


### Talc (14807-96-6)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16: Other information

Indication of changes : New SDS Created.  
Revision date : 08/05/2016  
Other information : Author: MDT.

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.  
NFPA fire hazard : 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in air and will burn readily.  
NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



### HMIS III Rating

Health : 2\*  
Flammability : 4  
Physical : 0  
Personal protection :

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product