



WILLIAM H. HARVEY COMPANY  
4334 South 67<sup>th</sup> Street  
Omaha, NE 68117  
TECHNICAL SUBMITTAL  
PH: 1-800-321-9532  
FAX: 1-800-321-9535

## HARVEY'S WHITE PTFE THREAD SEAL TAPE

**TECHNICAL SPECIFICATION:** Harvey's White Polytetrafluoroethylene (PTFE) Thread Seal Tape is made of virgin white PTFE. Economy grade, low density tape. Provides a clean, positive seal on threaded connections. PTFE Thread Seal Tape is an all purpose thread sealing tape and can be used with plastic, brass, copper, aluminum, galvanized steel or black iron piping. Nonflammable.



### **COMMON APPLICATIONS**

Harvey's PTFE Thread Seal Tape can be used on plastic, brass, copper, aluminum, galvanized steel or black iron piping.

NOT FOR USE WITH LINES CARRYING OXYGEN.

Consult Harvey Technical Department for applications not specifically referenced above.

### **INGREDIENT**

Virgin PTFE

When used for the intended end use application, this product is considered an "article" as defined in OSHA 29 CFR 1910.1200(c).

### **APPROVALS AND LISTINGS**

Meets Military Specification T-27730A.

### **PHYSICAL/CHEMICAL PROPERTIES**

Appearance	White Tape
Density	0.4 ± 0.1 g/cm <sup>3</sup>
Temperature Range	-400° F to 500° F
Thickness	0.003" to 0.0045"
Elongation	50%
Shelf Life	Indefinite

### **DIRECTIONS FOR USE**

For threads up to 1-1/2" diameter, use 1/2" width of thread seal tape. For larger diameter threads, use 3/4" width of thread seal tape. Clean the male and female threads of any oil or dirt. Apply the thread seal tape a minimum of three wraps, using care to wrap in the direction of the thread rotation. Be sure to keep tension on the tape while wrapping. Do not overlap the tape on the ends of the fitting.

### **PRECAUTIONS**

Read all cautions and directions carefully before using this product. Store spool in clean place and keep cover on the spool when not in use.

PRODUCT NUMBER	SIZE	PACK	CARTON WEIGHT
017850	1/2" x 260" (blue spool)	[add]	[add]
017852	1/2" x 260" 5-pack (blue spool)	[add]	[add]
017400-24	1" x 520" (blue spool)	24	2 lbs.