



TRANSPARENT LOG HOME GLOSS FINISH

NO. 15



PRODUCT INFORMATION

BEHR PREMIUM® Transparent Log Home Gloss Finish is a durable and flexible formula that moves with the natural expansion and contraction of natural wood surfaces and will also protect from the sun's harmful UV rays. It's available in both clear and cedar finishes, and is also great for fences and siding.

RECOMMENDED USES:

Ideal for use on exterior surfaces such as:

- Wood

Do not use on horizontal surfaces subject to foot traffic.

PRODUCT SPECIFICATIONS:

Tint Bases/Max Tint Load:

- No. 15 128 oz
- No. 16 128 oz

Gloss: 80-100 @ 60°

Resin Type: Alkyd/Acrylic Dispersion

Weight per Gallon: 8.5 lbs

% Solids by Volume: 29.7%

% Solids by Weight: 31.0%

VOC: <275 g/L

Flash Point: N/A

Viscosity: 20-35 sec #2 Zahn Cup

Recommended Film Thickness:

- Wet: 8.2 Dry: 2.4 mils @ 200 Sq. Ft./Gal.
- Wet: 4.1 Dry: 1.2 mils @ 400 Sq. Ft./Gal.

Coverage: 200-400 Sq. Ft./Gal., depending on application method and substrate porosity. Does not include the loss of material from spraying.

APPLICATION:

Brush: Nylon/polyester

Roller: 3/8"-1/2" nap

Airless Spray: At packaged consistency

Tip: .015- .019"

Filter: 60 mesh

Dry Time: @ 77° & 50% RH

To Touch: 8-12 hours

To Recoat: 24 hours

- Follow spraying immediately with back brushing or back rolling for a uniform appearance.
- Maintain a wet edge when applying.

SURFACE PREPARATION:

The following steps and products are recommended

for best results: If you use a product such as BEHR PREMIUM® Wood Stain & Finish Stripper No. 64 to remove loose wood fibers, latex, oil-based and 100% acrylic coating on new or weathered wood, then you must use BEHR PREMIUM® All-In-One Wood Cleaner No. 63 to brighten & neutralize wood. If you do not use BEHR PREMIUM Wood Stain & Finish Stripper No. 64, use a product such as BEHR PREMIUM All-In-One Wood Cleaner No. 63 to clean and brighten the wood surface and to remove light to medium stains caused by mold, mildew, algae & fungus. On new wood, use a product such as BEHR PREMIUM All-In-One Wood Cleaner No. 63 to remove mill glaze and open the pores of the wood. Rinse thoroughly and allow to dry before coating. Lightly sand any remaining wood fibers/fuzz.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

CLEAN UP:

Clean all tools and equipment with clean water. For proper disposal of empty containers and unused product, contact your household refuse collection service.

COMPLIES WITH THE BELOW AS OF 1/1/2016			
SCAQMD	YES	LADCO	YES
CARB	YES	AIM	YES
OTC	YES	LEED v.3 (2009) [†]	YES

[†]Please visit www.usgbc.org/LEED for additional details.

CAUTIONS/LIMITATIONS:

- Protect from freezing
- Do not use if rain is expected within 24 hours
- DO NOT THIN PRODUCT
- Avoid applying stain in direct sunlight or hot surfaces
- Test product for color on a small hidden area before proceeding
- Over application of stain will lead to surface failure including peeling & cracking
- Shelf life under normal conditions is two years (unopened containers)
- Temperature Range: 40-90°F (4.5-32°C)

GENERAL INFORMATION:



Warning! Causes eye and skin irritation. Harmful if swallowed. Wear protective clothing, gloves, eye, and face protection. Do not eat, drink, or smoke when using this product. Take off contaminated clothing and wash it before reuse. Wash hands thoroughly after handling. Collect spillage and avoid release to the environment. Dispose of unused, contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.

First aid: If in eyes: Rinse cautiously with water for several minutes and remove contacts if present and easy to do. Continue rinsing and get medical attention if eye irritation persists. **If on skin:** Wash with plenty of soap and water. **If swallowed:** Rinse mouth and get medical attention if you feel unwell.

