



Dependable. Reliable. Professional.

WATER HEATER INSTALLATION TAPE

UL LISTED TAPE



Backing: Printed Biaxially-Oriented Polypropylene Film
Adhesive: Acrylic
Liner: N/A
Specifications: UL 181B-FX Listed
Colors: Metallic
Available Size: 1.89 in x 30 yd (48 mm x 27.4 m)

Applications

- Conforms and bonds securely to water heater insulation jacketing to seal seams and repair rips and tears
- Tough, contractor-grade closure system intended for use on UL Listed flexible, non-metallic ducts

Features

Benefits

Acrylic Adhesive	<ul style="list-style-type: none"> • Aggressive, high tack bond to insulation jacket • Low-odor adhesive • Mold and moisture-resistant
Biaxially-Oriented Polypropylene Film	<ul style="list-style-type: none"> • Tough and durable • Hand tearable for simple, quick installation • Conformable for hard-to-seal areas • 181B-FX printed for easy inspector identification
Low VOC Content	<ul style="list-style-type: none"> • Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	3.1 mils	79 µm	ASTM D-1000
Adhesion to Steel	45 oz/in	4.92 N/cm	PSTC-101
Tensile Strength	34 lb/in	59.54 N/cm	ASTM D-1000
Installation Temperature	-10 to 180 °F	-17 to 82 °C	
Operating Temperature	-40 to 212 °F	-40 to 100 °C	
VOC Content	< 1 g/L		
Recommended Storage Conditions: 60 - 80 °F at 40-60% RH Standard Shelf Life (at 25 °C): 24 months from date of manufacture			

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.



25 Forge Parkway Franklin, MA 02038
 1-800-343-7875 Fax 1-800-328-4822
 www.nashuatape.com