



**CHALKED
CLEAR PROTECTIVE TOPCOAT**

DESCRIPTION AND USES

Rust-Oleum® Chalked Clear Protective Topcoat enhances any Chalked Ultra Matte paint finish and adds protection to the surface. The clear topcoat can be applied to maintain and enhance any Chalked project. **For interior use only.**

PRODUCTS

SKU	Description
287722	Clear Matte

PAINTING CONDITIONS

Use in a well ventilated area such as an open garage. Apply when temperature is between 50 and 90°F (10-32°C) and humidity is below 85% to ensure proper drying.

PRODUCT APPLICATION

SURFACE PREPARATION

Surfaces must be clean, dry and sound. Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with soap and water and let dry. Remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy surfaces. Remove any wax by lightly wiping the surface with mineral spirits.

WARNING: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT APPLICATION (cont.)

APPLICATION

Apply only when air and surface temperatures are between 50-90°F (10-32°C) and humidity is below 85% to ensure proper drying. Stir thoroughly. Do not shake the can. Thinning is not required. Avoid painting in direct sunlight or on hot surfaces.

Use a high quality synthetic brush. Roller application is not recommended. Avoid excessive brushing as this will reduce film thickness and protection. Wait for the base coat to dry for at least 8 hours before applying the Clear Protective Topcoat. Use light even brush strokes to ensure even flow and the smoothest finish. Apply 1-2 even coats. Wait 2 hours between each coat.

DRY & RECOAT

Dry and recoat times are based on 70°F (21°C) and 50% relative humidity. Allow more time at cooler temperatures. Dries to the touch in 30 minutes, to handle in 1 hour and is fully dry in 4 hours. It can be recoated after 2 hours.

CLEAN-UP

Clean brush and other and application tools with soap and water.

**TECHNICAL DATA****CHALKED CLEAR PROTECTIVE TOPCOAT****PHYSICAL PROPERTIES**

		CHALKED CLEAR PROTECTIVE TOPCOAT
Resin Type		Acrylic Urethane
Pigment Type		NA
Solvents		Water and Glycol Ethers
Weight	Per Gallon	8.5 lbs.
	Per Liter	1.02 kg
Solids	By Weight	30.5%
	By Volume	28.8%
Volatile Organic Compounds		<250 g/l (2.08 lbs./gal.)
Recommended Dry Film Thickness (DFT) Per Coat		1.0-2.0 mils (25-50 μ)
Wet Film to Achieve DFT		4.0-6.0 mils (100-150 μ)
Practical Coverage at Recommended DFT		110-150 sq.ft./qt. (2.7-3.7 m ² /l)
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	30 minutes
	Handle	1-2 hours
	Recoat	2 hours
Shelf Life		3 years
Flash Point		>200°F (93°C)
Safety Information		For additional information, see MSDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061
An RPM Company

Phone: 877-385-8155
www.rustoleum.com

Form: GDH-774
Rev.: 024135