



Dependable. Reliable. Professional.

324A HVAC PREMIUM FOIL

UL LISTED TAPE



- Backing:** Printed Aluminum Foil
- Adhesive:** Acrylic
- Liner:** Unbleached Natural Kraft Paper
- Specifications:** UL 181A-P Listed
UL 181B-FX Listed
- Colors:** Aluminum
- Available Size:** 2.5 in x 60 yd (63.5 mm x 54.9 m)

Applications

- Premium closure system for permanently sealing fiberglass duct board and flexible duct systems
- Suitable for use on rigid sheet metal ducts
- Durable seal for dryer ventilation

Features

Benefits

UL 181B-FX & 181A-P Listed	<ul style="list-style-type: none"> • Meets code requirements in sealing rigid and flexible air ducts and connections • Can contribute toward satisfying EA Credit 1 (Optimize Energy Performance) under LEED®
Acrylic Adhesive	<ul style="list-style-type: none"> • Superior bond in cold (down to -25 °F) or hot humid conditions (up to 325 °F) • High tack and adhesion • Resistant to moisture and mold
Aluminum Foil Backing	<ul style="list-style-type: none"> • Thick and durable • Conforms securely around duct and corners • 181A/B printed for easy inspector identification
Low VOC Content	<ul style="list-style-type: none"> • Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	4.8 mils	122 µm	ASTM D-1000
Adhesion to Steel	68 oz/in	7.44 N/cm	PSTC-101
Tensile Strength	28 lb/in	40.28 N/cm	ASTM D-1000
Installation Temperature	-10 to 200 °F	4 to 93 °C	
Operating Temperature	-25 to 325 °F	-32 to 163 °C	
VOC Content	< 1 g/L		
Recommended Storage Conditions: 60 - 80 °F at 40-60% RH			
Standard Shelf Life (at 25 °C): 36 months from date of manufacture			

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.