

### SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** Christy's® ROOT-BAN™ Drain Pipe Adhesive      **SYNONYMS:**

**PRODUCT USE:** Synthetic Rubber Based Adhesive

**SUPPLIER and MANUFACTURER:** T Christy Enterprises, Inc.  
655 East Ball Road, Anaheim, CA 92805-5910  
Tel. 1-714-507-3300 (North America)  
Tel. 1-714-507-3300 (International)

**EMERGENCY:** Transportation/Medical issues: Tel. 800.535.5053 INFOTRAC

### SECTION 2 - HAZARDS IDENTIFICATION

**GHS CLASSIFICATION:**

|   |  |  |
|---|--|--|
| <p><b>Health</b></p> <p>Skin Corrosion/Irritation: Category 2<br/>Eye: Category 2A<br/>Aspiration Hazard: Category 1<br/>Specific Target Organ Toxicity (Single Exposure): Category 3</p> | <p><b>Environmental</b></p> <p>Acute Toxicity: None Known<br/>Chronic Toxicity: None Known</p> | <p><b>Physical</b></p> <p>Flammable Liquid: Category 2</p> |
|---|--|--|

**Signal Word:** DANGER      **GHS LABEL:**       **WHMIS CLASSIFICATION:** CONTROLLED PRODUCT CLASS B, DIVISION 2      CLASS D, DIVISION 2B

|   |   |
|---|---|
| <p><b>Hazard Statements</b></p> <p>H225 Highly flammable liquid and vapor<br/>H304 May be fatal if swallowed and enters airways<br/>H315 Causes skin irritation<br/>H319 Causes serious eye irritation<br/>H335 May cause respiratory irritation<br/>H336 May cause drowsiness or dizziness</p> | <p><b>Precautionary Statements (See Section 15 for all advisory and required precautions)</b></p> <p>P210 Keep away from heat, hot surfaces, open flames and other ignition sources. No smoking<br/>P261 Avoid breathing dust/ fume/gas/mist/vapours/spray<br/>P264 Wash hands thoroughly after handling.<br/>P271 Use only outdoors or in a well-ventilated area.<br/>P280 Wear protective gloves/ protective/ clothing/ eye protection/ face protection<br/>P301+P310 IF SWALLOWED immediately call a POISON CONTROL CENTER or doctor/physician<br/>P304 + P340 IF INHALED: remove person to fresh air and keep comfortable for breathing.<br/>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.<br/>Remove contact lenses, if present and easy to do. Continue rinsing.<br/>P312 Call a POISON CENTER/ doctor if you feel unwell.<br/>P331 Do not induce vomiting<br/>P332+P337+P313 If skin or eye irritation occurs: Get medical advice/ attention<br/>P362+P364 Take off contaminated clothes and wash it before reuse.<br/>P405 Store locked up<br/>P403+P233+P235 Store in a well-ventilated place. Keep container tightly closed. Keep cool<br/>P501 Dispose of contents/container in accordance with local regulations.</p> |
|---|---|

### SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

|                   | CAS#        | EINECS #  | REACH                   | CONCENTRATION |
|-------------------|-------------|-----------|-------------------------|---------------|
|                   |             |           | Pre-registration Number | % by Weight   |
| Rosin Based Resin | 8050-26-8   |           |                         | 13-30         |
| Acetone           | 67-64-1     | 200-662-2 | 05-2116297713-35-0000   | 10-40         |
| Heptane*          | 426260-76-6 |           |                         | 20-60         |
| Globalprene SBS   | 9003-55-8   |           |                         | 5-30          |

All of the constituents of this adhesive product are listed on the TSCA inventory of chemical substances maintained by the US EPA, or are exempt from that listing.  
\*This chemical is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 (40CFR372).

### SECTION 4 - FIRST AID MEASURES

**Contact with eyes:** Flush eyes immediately with plenty of water for 15 minutes and seek medical advice immediately.  
**Skin contact:** Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water. If irritation develops, seek medical advice.  
**Inhalation:** Remove to fresh air. If breathing is stopped, give artificial respiration. If breathing is difficult, give oxygen. Seek medical advice.  
**Ingestion:** Rinse mouth with water. Give 1 or 2 glasses of water or milk to dilute. Do not induce vomiting. Seek medical advice immediately.

### SECTION 5 - FIREFIGHTING MEASURES

|  |  |              |      |            |
|--|--|--------------|------|------------|
| <b>Suitable Extinguishing Media:</b>   | Dry chemical powder, carbon dioxide gas, foam, Halon, water fog.                 | HMS          | NFPA | 0-Minimal  |
| <b>Unsuitable Extinguishing Media:</b> | Water spray or stream.   | Health       | 2    | 1-Slight   |
| <b>Exposure Hazards:</b>               | Carbon monoxide, carbon dioxide, hydrogen chloride and smoke                     | Flammability | 3    | 2-Moderate |
| <b>Combustion Products:</b>            | Carbon monoxide, carbon dioxide, hydrogen chloride and smoke                     | Reactivity   | 1    | 3-Serious  |
| <b>Protection for Firefighters:</b>    | Self-contained breathing apparatus or full-face positive pressure airline masks. |              |      | 4-Severe   |

### SECTION 6 - ACCIDENTAL RELEASE MEASURES

**Personal precautions:** Keep away from heat, sparks and open flame.  
Provide sufficient ventilation, use explosion-proof exhaust ventilation equipment or wear suitable respiratory protective equipment.  
Prevent contact with skin or eyes (see section 8).

**Environmental Precautions:** Prevent product or liquids contaminated with product from entering sewers, drains, soil or open water course.

**Methods for Cleaning up:** Clean up with sand or other inert absorbent material. Transfer to a closable metal container

**Materials not to be used for clean up:** Aluminum or plastic containers

### SECTION 7 - HANDLING AND STORAGE

**Handling:** Avoid breathing of vapor, avoid contact with eyes, skin and clothing.  
Keep away from ignition sources, use only electrically grounded handling equipment and ensure adequate ventilation/fume exhaust hoods.  
Do not eat; drink or smoke while handling.

**Storage:** Store in ventilated room or shade below 27°C (80°F) and away from direct sunlight.  
Keep away from ignition sources and incompatible materials: caustics, ammonia, inorganic acids, chlorinated compounds, strong oxidizers and isocyanates.  
Follow all precautionary information on container label, product bulletins and solvent cementing literature.

### SECTION 8 - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

| EXPOSURE LIMITS: | Component | ACGIH TLV | ACGIH STEL | OSHA PEL | OSHA STEL: |
|------------------|-----------|-----------|------------|----------|------------|
|                  | Acetone   | 500 ppm   | 750 ppm    | 750 ppm  | 1000 ppm   |
|                  | Heptane   | 200 ppm   |            | 300 ppm  | 500 ppm    |

**Engineering Controls:** If ventilated cabinet, enclosure or fume hood is necessary, average airflow should be at least 100 FPM (50.8 cm/sec).

**Monitoring:** Maintain breathing zone airborne concentrations below exposure limits.

**Personal Protective Equipment (PPE):**

**Eye Protection:** Avoid contact with eyes, wear splash proof chemical goggles, face shield, safety glasses (spectacles) with brow guards and side shields, etc. as may be appropriate for the exposure.

**Skin Protection:** Prevent contact with the skin as much as possible. Polyethylene or PVA coated rubber gloves should be used for frequent immersion.  
Use of latex/nitrile surgical gloves or solvent-resistant barrier cream should provide adequate protection when normal adhesive application practices and procedures are used for making structural bonds.

**Respiratory Protection:** Prevent inhalation of the solvents. Use in a well-ventilated room. Open doors and/or windows to ensure airflow and air changes. Use local exhaust ventilation to remove airborne contaminants from employee breathing zone and to keep contaminants below levels listed above.  
With normal use, the Exposure Limit Value will not usually be reached. When limits approached, use respiratory protection equipment.

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

|   |  |                               |                                     |
|---|--|-------------------------------|-------------------------------------|
| <b>Appearance:</b>                            | Green, medium syrupy liquid  | <b>Odor Threshold:</b>        | N/D                                 |
| <b>Odor:</b>                                  | Ethereal   |                               |                                     |
| <b>P.H.</b>                                   | Not Applicable   |                               |                                     |
| <b>Melting/Freezing Point:</b>                | -95°C (-139°F) Based on first freezing component: Acetone                                    | <b>Boiling Range:</b>         | 57°C (133°F) to 98°C (208°F)        |
| <b>Boiling Point:</b>                         | 57°C (133°F) Based on first boiling component: Acetone                                       | <b>Evaporation Rate:</b>      | > 1.0 (BUAC = 1)                    |
| <b>Flash Point:</b>                           | -4°C (24.8°F) T.C.C. based on heptane  | <b>Flammability:</b>          | Category I                          |
| <b>Specific Gravity</b>                       | @23°C ± 2° (73°F ± 3.6°) Typical 0.833 ± 0.01  | <b>Flammability Limits:</b>   | <b>LEL:</b> 2%<br><b>UEL:</b> 11.8% |
| <b>Solubility:</b>                            | Solvent portion completely soluble in water. Resin portion separates out.                    | <b>Vapor Pressure:</b>        | 181 mm Hg @ 20°C (68°F): Acetone    |
| <b>Partition Coefficient n-octanol/water:</b> | Not Available  | <b>Vapor Density:</b>         | <2 (Air = 1)                        |
| <b>Auto-ignition Temperature:</b>             | 203°C (399°F): T.C.C. Based on heptane   | <b>Other Data: Viscosity:</b> | Medium bodied                       |
| <b>Decomposition Temperature:</b>             | Not Applicable   |                               |                                     |
| <b>VOC Content :</b>                          | When applied as directed, per SCAQMD Rule 1168, Test Method 316A, VOC content is: ≤ 250 g/l. |                               |                                     |

**SECTION 10 - STABILITY AND REACTIVITY**

|  |   |
|--|---|
| <b>Stability:</b>                        | Stable  |
| <b>Hazardous decomposition products:</b> | None in normal use. When forced to burn, this product gives off carbon monoxide (CO), carbon dioxide (CO <sub>2</sub> ), hydrogen chloride (HCl) and smoke. |
| <b>Conditions to avoid:</b>              | Keep away from heat, sparks, open flame and other ignition sources.   |
| <b>Incompatible Materials:</b>           | Caustics, ammonia, inorganic acids, chlorinated compounds, strong oxidizers and isocyanates.  |

**SECTION 11 - TOXICOLOGICAL INFORMATION**

|                                     |   |   |  |
|-------------------------------------|---|---|--|
| <b>Likely Routes of Exposure:</b>   | Inhalation, Eye and Skin Contact  |   |  |
| <b>Acute symptoms and effects:</b>  |   |   |  |
| <b>Inhalation:</b>                  | Severe overexposure may result in nausea, dizziness, headache. Can cause drowsiness, irritation of eyes and nasal passages.                       |   |  |
| <b>Eye Contact:</b>                 | Vapors slightly uncomfortable. Overexposure may result in severe eye injury with corneal or conjunctival inflammation on contact with the liquid. |   |  |
| <b>Skin Contact:</b>                | Liquid contact may remove natural skin oils resulting in skin irritation. Dermatitis may occur with prolonged contact.                            |   |  |
| <b>Ingestion:</b>                   | May cause nausea, vomiting, diarrhea and mental sluggishness.   |   |  |
| <b>Chronic (long-term) effects:</b> | None known to humans  |   |  |
| <b>Toxicity:</b>                    | LD <sub>50</sub>  | LC <sub>50</sub>                        |  |
| Acetone                             | Oral: 9.75 g/kg (rat), Dermal 20 g/kg (rabbit)  | Inhalation LCLO 4 hrs. 16,000 PPM (rat) |  |
| Heptane                             | Oral: 5170 mg/kg (rat)  | Inhalation LCLO: 4 hrs. 7.63 mg/l (rat) |  |

| Reproductive Effects | Teratogenicity | Mutagenicity | Embryotoxicity | Sensitization to Product | Synergistic Products |
|----------------------|----------------|--------------|----------------|--------------------------|----------------------|
| Not Applicable       | Not Applicable | Poss.        | Not Applicable | Not Applicable           | Not Available        |

**SECTION 12 - ECOLOGICAL INFORMATION**

|                         |   |
|-------------------------|---|
| <b>Ecotoxicity:</b>     | No known significant effects or critical hazards  |
| <b>Mobility:</b>        | In normal use, emission of volatile organic compounds (VOC's) to the air takes place. Typically at a rate of ≤ 250 Grams/Liter. |
|                         | Minimal other adverse effects include possible ground water contamination from release to soil, sewers, drains or water course. |
| <b>Degradability:</b>   | Biodegradable   |
| <b>BioAccumulation:</b> | Minimal to none.  |

**SECTION 13 - WASTE DISPOSAL CONSIDERATIONS**

Follow local and national regulations. Consult disposal expert. Can be disposed of by controlled incineration. May be allowed to dry and disposed of as trash. Excessive quantities should not be permitted to enter drains, sewers or water courses. Empty containers should be air dried before disposing.

**SECTION 14 - TRANSPORT INFORMATION****DOT, IATA, ADR, IMO/IMDG SHIPPING INFORMATION**

|                               |                  |   |
|-------------------------------|------------------|---|
| <b>Proper Shipping Name:</b>  | Adhesives        | DOT/IMDG EXCEPTION: Case quantities of cement in containers of less than one liter may be shipped as LIMITED QUANTITY when properly labeled and marked. |
| <b>Hazard Class:</b>          | 3                |   |
| <b>Secondary Risk</b>         | None             | ICAO/IATA May be shipped by air as CONSUMER COMMODITY, ID 8000 when properly packaged, labeled and marked.  |
| <b>Identification Number:</b> | UN 1133          |   |
| <b>Packing Group:</b>         | II               | <b>TDG INFORMATION</b>  |
| <b>Label Required:</b>        | Flammable Liquid | TDG CLASS: FLAMMABLE LIQUID 3   |
|                               |                  | SHIPPING NAME: ADHESIVES (ACETONE)  |
| <b>Marine Pollutant:</b>      | NO               | UN NUMBER: 1133, PG II  |

**SECTION 15 - REGULATORY INFORMATION**

|   |  |  |
|---|--|--|
| <b>Precautionary Label Information:</b> | Highly Flammable, Irritant<br>F, Xi  | Ingredient Listings: USA TSCA, Europe EINECS, Canada DSL, Australia AICS, Korea ECL/TCCL, Japan MITI (ENCS)  |
| <b>Risk Phrases:</b>                    | R-11 Highly Flammable<br>R-20 Harmful by inhalation<br>R-21 Harmful in contact with skin.<br>R-22 Harmful if swallowed.  | R-36/37/38 Irritating to eyes, respiratory system and skin.<br>R-41 Risk of serious damage to the eyes.<br>R-43 May cause sensitization by skin contact.   |
| <b>Safety Phrases:</b>                  | S-2 Keep out of reach of children.<br>S-7 Keep container tightly closed when not in use.<br>S-9 Keep container in a well-ventilated place.<br>S-15/16 Keep away from heat and sources of ignition. No smoking.<br>S-23 Do not breathe vapor. | S-24/25 Avoid contact with skin and eyes.<br>S-29 Do not empty into drains.<br>S-37 Wear suitable gloves.<br>S-45 If seeking medical advice show physician label or SDS.<br>S-51 Use only in well ventilated areas.<br>S-46 If swallowed, seek medical advice immediately and show this container or label |

**SECTION 16 - OTHER INFORMATION**

|   |  |  |
|---|--|--|
| <b>Specification Information:</b>         |  |  |
| <b>Department issuing data sheet:</b>     | Environmental Health & Safety  | All ingredients are compliant with the requirements of the European Directive on RoHS (Restriction of Hazardous Substances). |
| <b>e-mail address:</b>                    | <EHSinfo@tchristy.com>   |  |
| <b>Training necessary:</b>                | Yes, training in practices and procedures contained in product literature.   |  |
| <b>Reissue date / reason for reissue:</b> | NOV 2018/ Updated Information  |  |
| <b>Intended Use of Product:</b>           | Contact adhesive for polyethylene, HDPE and Styrene drain pipe and fittings. |  |

This product is intended for use by skilled individuals at their own risk. The information contained herein is based on data considered accurate based on current state of knowledge and experience. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof.