

HyperBC-4C-X05 - 8410007X1BC
HyperBC-4F-X05 - 8420007X1BC



For your safety these Hyperikon® tubes are UL-listed [E472253] to avoid electrical shock and fire hazard. All Hyperikon 4FT tubes are DLC-approved and thus eligible for state and Nationwide rebate programs.

4FT CRI84+ DOUBLE ENDED HYPERIKON® LED TUBE

SPECIFICATIONS

Model Name	Hyperikon Code	Wattage	Lumens	Efficacy	Kelvin
HyperBC-4C-305	841000731BC	18W	2300 Lm	128 Lm/W	3000K
HyperBC-4C-405	841000741BC	18W	2320 Lm	129 Lm/W	4000K
HyperBC-4C-505	841000751BC	18W	2340 Lm	130 Lm/W	5000K
HyperBC-4C-605	841000761BC	18W	2360 Lm	131 Lm/W	6000K
HyperBC-4F-305	842000731BC	18W	2200 Lm	122 Lm/W	3000K
HyperBC-4F-405	842000741BC	18W	2220 Lm	123 Lm/W	4000K
HyperBC-4F-505	842000751BC	18W	2240 Lm	124 Lm/W	5000K
HyperBC-4F-605	842000761BC	18W	2260 Lm	125 Lm/W	6000K

MODEL DESIGN

4 ft (1219 mm)

8410007X1BC
Clear 120°



8420007X1BC
Frosted 140°



Voltage
120-277V



Base
G13



Beam Angle
120°-140°



CRI
84+



Dimmer Not
Recommended



Temperature
-22 °F to 130 °F

- Suitable for damp locations outside as well as inside.
- 45,000+ hours of lifespan, more than 41.1 years based on 3Hrs/day average
- Please note that the 6000K variations are not DLC certified

WARNINGS AND CAUTIONS

- Turn power off before inspection, installation or removal. Risk of electric shock - do not use where directly exposed to water or weather.
- This device is not intended for use with emergency exit fixtures or emergency exit lights.

HYPERIKON®

(888) 846-4973
info@hyperikon.com
707 Broadway Suite 800
San Diego, CA 92101
www.hyperikon.com

