

KILZ 3 PREMIUM - INTERIOR/EXTERIOR WATER-BASE PRIMER



- Primer/sealer/stain blocker
- For use on interior and exterior surfaces
- Superior quality high hiding formula
- Blocks out most stains including pencil, ink, felt marker, nicotine, grease, rust, water and more
- Thick and creamy high hide formula
- Excellent adhesion
- Mildew resistant coating, very mild odor
- Very low V.O.C. (volatile organic compounds)
- Easy clean-up with soap and water
- Fast drying; Recoat in 1 hour



Soap & Water
Clean-Up



300 - 400 sq. ft. / gal.¹



30 Min - Dry Time to Touch¹
1 Hr - Dry Time to Recoat¹



Protect from
Freezing

WHERE TO USE

KILZ® 3 PREMIUM primer is a superior quality, fast drying, low odor, very low VOC, water-based primer-sealer-stain blocker. It has excellent adhesion and provides a mildew resistant coating making it ideal for use in moisture-prone areas. KILZ 3 PREMIUM primer blocks most stains caused by water, tannin, ink, pencil, felt marker and grease. Use on interior and exterior surfaces including woodwork, drywall, plaster, paneling, masonry, brick, painted metal and properly prepared glossy surfaces[†]. Not recommended for floors.

SURFACE PREPARATION (The following steps are recommended for product performance)

- All surfaces must be clean, free of dust, chalk, oil, grease, wax, polish, mold and mildew, loose peeling paint, rust and all other foreign substances.
- If washing is necessary, use a non-soapy detergent or a TSP substitute, rinse well and allow to dry.
- Peeling or Checked Paint: Scrape off loose paint and sand to a smooth surface*. Sanding or removal of paint containing lead is hazardous.
- [†]Glossy Surfaces: For maximum adhesion, scuff sand the surface thoroughly before priming*.
- Mold or Mildew Covered Surfaces: Wash the area with a mildew remover, rinse with water and allow to dry before priming.
- Masonry, Brick, Stucco and Plaster: KILZ 3 PREMIUM primer may be used on clean, dry, aged masonry surfaces. New masonry must be allowed to cure (dry) at least 30 days before applying KILZ 3 PREMIUM primer.
- Fire Restoration: It is critical to clean damaged surfaces thoroughly before priming. Primer recommendations: KILZ RESTORATION™ for water-based, KILZ® ORIGINAL, KILZ ORIGINAL INTERIOR/EXTERIOR or KILZ ORIGINAL LOW ODOR primers for oil-based.

APPLICATION

- Eye protection is recommended. For spray applications, a small amount of water (no more than 1/2 pint per gallon) may be added. Do not thin for stain blocking applications.
- Only apply if surface, air and product temperatures are between 50°-90°F (10°-32°C). Stir thoroughly before and occasionally during use. Apply using a brush, roller or sprayer.
- Brush – High quality Nylon/Polyester
- Roller – High quality 3/8-1/2” nap on smooth surfaces or 1/2-3/4” nap on semi-rough or porous surfaces.
- Airless spray – .017 - .021 tip / 60 mesh filter
- Prime the entire surface to ensure a uniform appearance of the topcoat.
- Stain blocking: After priming, test for stain bleed-through by applying the topcoat to a small section. If the stain bleeds through the topcoat, apply a second coat of primer and test again before topcoating the entire area. If bleeding continues, a longer dry time is needed before topcoating.

- Tinting: KILZ 3 PREMIUM primer may be tinted with up to 2 ounces of universal colorant per gallon. Tinting to a lighter shade than the topcoat is recommended.
- Coverage: 300 - 400 sq. ft. (27.87 - 37 m²) per gallon depending on application method and surface porosity.
- Dry Time @ 77°F (25°C) / 50% RH: Touch 30 minutes, Recoat 1 hour.

CLEAN-UP & DISPOSAL

- Clean equipment and paint splatters with warm, soapy water.
- Do not dispose of this product down a drain. Please consider donating any unused product. For recycling or disposal information contact your local household refuse collection service.
- If spilled, contain material and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused product in accordance with all current federal, state and local regulations. For recycling or disposal information contact your local household refuse collection service.

***WARNING** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.



WARNING Cancer and Reproductive Harm
www.P65Warnings.ca.gov

USE ONLY WITH ADEQUATE VENTILATION

CAUTION IRRITANT Avoid contact with eyes. May cause eye, nose and throat irritation. Avoid breathing of dust, vapors or spray mist. Open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/ mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH / MSHA TC -23C or equivalent) during and after application. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling and before smoking or eating. **FIRST AID:** If swallowed, do not induce vomiting. Get medical attention immediately. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. In case of eye contact, flush eyes immediately with plenty of water for at least 15 minutes and get medical attention.

KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY

LIFETIME LIMITED WARRANTY: Masterchem Industries LLC warrants to you, the original residential consumer purchaser, the performance of this product as described on this label for so long as you reside in your home. If this product is found to be defective upon inspection by its representative, Masterchem Industries LLC will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. This warranty is not transferable. **This warranty excludes (1) labor and costs of labor for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. To the extent permitted by applicable law, any implied warranties including the implied warranties of merchantability and of fitness for a particular purpose, are limited to the duration of this express warranty. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state. **Note to residents of the State of New Jersey:** The provisions of this warranty, including its limitations, are intended to apply to the fullest extent permitted by the laws of the State of New Jersey. For warranty service, call: 1-866-774-6371, or email: techservice@masterchem.com. Masterchem Industries LLC reserves the right to inspect any and all application of the product prior to processing your claim made under this warranty.

¹Depending on the surface texture, porosity and application method

¹At 77°F (25°C), 50% RH. Longer dry time may be required in cooler temperatures and in higher humidity



©2019 Masterchem Industries LLC
1-866-774-6371 • www.kilz.com
1300 • REV. 06/19
VOC <5 g/L, excluding colorant(s)