Dalton Enterprises, Inc.

Phone: (203) 272-3221

Phone: 04/05/2018



# SAFETY DATA SHEET



#### Section I - PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** Dalton Enterprises SS-1h Tack Coat **Manufacturer Name:** Dalton Enterprises, Inc.

**Item #:** 1220: 5 Gallon Pail

UPC#: 0 90932 01220 2 1220P: Pallet (36 Pails) UPC#: 0 90932 34060 2

Address: 131 Willow Street Cheshire, CT 06410

**Telephone Number:** (203) 272-3221

**24 Hour Emergency Number:** (203) 272-3221

U.S. And Canada: (203) 272-3221

Trade Names and Synonyms: Anionic Emulsion

**Recommended Use and Restrictions:** Tack Coat / Primer for asphalt pavement

**Product Description:** Dalton Enterprises SS-1h tack coat is for asphalt surfaces. Proper application of ready-to-use emulsified product as applied presents no degree of hazard to the user. Outdoor use only.

### Section II - HAZARDS IDENTIFICATION

#### Classification

Carcinogenicity	1A
Caremogeneity	17.1

#### **Label Elements**

GHS Pictogram: Signal Word: Danger

**Hazard Statements:** May cause cancer **Precautionary Statements – Prevention** Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Dalton Enterprises, Inc.

Phone: (203) 272-3221

Phone: 04/05/2018

#### **Precautionary Statements - Storage**

Store locked up

## **Precautionary Statements - Disposal**

Dispose of contents/container in accordance with local regulations.

#### Hazards not otherwise classified (HNOC)

Not applicable

## **Unknown Toxicity**

0% of the mixture consists of ingredient(s) of unknown toxicity

### Other information

No information available

#### **Interactions with Other Chemicals**

No information available.

#### Section III - COMPOSITION

CAS#	CAS# Component	
8052-42-4	Petroleum Asphalt	57 - 65

#### Section IV - FIRST-AID MEASURES

### **Emergency and First Aid Procedures**

**General Advice:** Present this safety data sheet to the physician in attendance.

**Eye Contact:** Flush thoroughly with water for fifteen minutes. If irritation persists, see a physician. **Skin Contact:** Clean exposed area thoroughly with soap and water. If irritation persists, see a physician.

**Ingestion:** If swallowed do NOT induce vomiting. Seek medical attention if symptoms develop.

**Inhalation:** Move to fresh air if symptoms develop. If irritation persists, see a physician.

**Most Important Symptoms:** Possibility of minor eye and skin irritation.

Indication of Immediate Medical Attention and Special Treatment Needed: Treat Symptomatically

### Section V - FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: CO2, dry chemical, foam, sand.

**Unsuitable Extinguishing Media:** Water. Do not use water jet as an extinguisher, as this will spread the fire. **Specific Hazards arising from the Chemical:** Combustion may yield hazardous fumes, smoke, carbon monoxide and carbon dioxide.

**Special Protective Equipment and Precautions for Firefighters:** Wear full protective clothing, including self-contained breathing apparatus (Positive Pressure/Pressure Demand), helmet, and face mask.

#### Section VI - ACCIDENTAL RELEASE MEASURES

Dalton Enterprises, Inc.

Phone: (203) 272-3221

Phone: 04/05/2018

**Personal Precautions, Protective Equipment and Emergency Procedures:** Avoid skin and eye contact, use proper protective equipment recommended in section 8.

Methods and Materials for Containment and Cleanup: Contain spill and dike with inert material (sand, sawdust, dirt, etc.). Place in closed container for proper disposal. Avoid runoff to waterways and sewers. Dispose of in accordance with local regulations.

#### Section VII - HANDLING AND STORAGE

**Precautions for Safe Handling:** Store in a dry area, avoid eye contact and wash thoroughly after handling **Conditions for Safe Storage, Including Incompatibilities:** Keep container closed and upright to prevent leakage. Store in a cool, dry, ventilated area. Avoid freezing. Keep container upright to prevent leakage.

#### Section VIII - EXPOSURE CONTROLS / PERSONAL PROTECTION

### **Personal Exposure Guidelines**

Component ACGIH TWA (mg/m³)		OSHA PEL (TWA) (mg/m3)		
Petroleum Asphalt	$0.5 \text{ mg/m}^3$	-		

Engineering Controls: Ensure adequate ventilation

### **Individual Protection Measures**

Eyes/Face: Safety goggles

Skin: Gloves

Respiratory: None required if good ventilation is maintained. This product is an emulsified, encapsulated

mixture which greatly reduces the likelihood of exposure to hazardous particles.

Hygienic controls: Wash thoroughly with soap and water before eating or drinking. Wash

contaminated clothing.

#### Section IX - PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Dark brown to black liquid **Upper Explosive Limit:** N/A **Physical State:** liquid **Lower Explosive Limit:** N/A

Odor: Asphaltic odor

Odor Threshold: N/A

Vapor Pressure: 24mm Hg @ 77°F

Vapor Density: Heavier than air

Straiff Counting 0.08 at 0.2 @ 600

pH: 7.0 - 11.3 Specific Gravity:  $0.98 - 1.02 @ 60^{\circ}F$  Melting Point: N/A Solubility In Water: Easily dispersible

Flash Point: >350°F (>177 °C)

Auto Ignition Temperature: N/A

Evaporation Rate: N/A

Decomposition Temperature: N/A

Flammability: N/A Max Voc: 0g/L

#### Section X - STABILITY AND REACTIVITY

**Reactivity:** None known under normal conditions

Dalton Enterprises, Inc.

Product: SS-1h Tack Coat
SDS Date: 04/05/2018

Stability: Stable

**Hazardous Reactions:** None known under normal conditions **Conditions to avoid:** Keep from freezing and extreme heat

**Incompatibility:** Strong oxidizers

Hazardous Decomposition Products: Combustion may yield fumes, smoke, carbon monoxide and carbon

dioxide.

#### Section XI - TOXICOLOGICAL INFORMATION

### **Health Effects**

Eye Contact: Minor irritation may result Skin Contact: Minor irritation may result Ingestion: Minor irritation may result Inhalation: Minor irritation may result

**Toxicological Effects** 

<u>Component</u>	CAS#	Acute oral toxicity LD50	Acute dermal toxicity LD50
Petroleum Asphalt	8052-42-4	5,001 mg/kg (rat)	2,001 mg/kg (rat)

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization: Product not known to cause sensitization

Mutagenic Effects: None known Carcinogenicity: May cause cancer

<b>Component</b>	CAS#	<u>IARC</u>	<u>NTP</u>	<u>OSHA</u>
Petroleum Asphalt	8052-42-4	2B	Suspected	-

Reproductive Toxicity: No toxicity known STOT – Single Exposure: None Known STOT – Repeated Exposure: None Known Chronic Toxicity: No Known Effect Target Organ Effects: Eyes, Skin.

**Aspiration Hazard:** Based on available data, the classification criteria are not met.

### **Numerical Measures of Toxicity**

No data available

#### Section XII - ECOLOGICAL INFORMATION

Ecological Fate:No data availablePersistence/Degradability:No data availableBioaccumulation Potential:No data availableMobility in Soil:No data available

Dalton Enterprises, Inc.

Product: SS-1h Tack Coat
SDS Date: 04/05/2018

Other Adverse Effects: No data available

Analysis for ecological effects has not been conducted.

## Section XIII - DISPOSAL CONSIDERATIONS

**Waste Disposal Method:** Dispose of in accordance with Local, State, and Federal regulations. Do not reuse contaminated packaging.

#### Section XIV - TRANSPORT INFORMATION

**DOT** – U.S. Department of Transportation **Proper Shipping Name:** Not regulated

**TDG -** Canada - Transport of Dangerous Goods **Proper Shipping Name:** Not Restricted

IATA – International Air Transport Association Proper Shipping Name: Not regulated

IMDG – International Maritime Dangerous GoodsProper Shipping Name: Not regulated

#### Section XV - REGULATORY INFORMATION

### **International Inventories**

**TSCA:** Complies

**DSL/NDSL:** Complies

### **US Federal Regulations**

**SARA 313:** This product contains no chemicals subject to Annual Release Reporting Requirements under SARA Title III, Section 313 (40 CFR 372)

**SARA Hazard Category (311/312):** Non Hazardous

**CWA (Clean Water Act):** This product contains no chemicals regulated by the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

**CERCLA:** This product contains no substances regulated by the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

### **US State Regulations**

Component Name	CAS	State Right to Know		
		MA	NJ	PA

Dalton Enterprises, Inc.

Product: SS-1h Tack Coat
SDS Date: 04/05/2018

Petroleum Asphalt	8052-42-4	yes	yes	yes
-------------------	-----------	-----	-----	-----

## California Proposition 65

WARNING: This product can expose you to chemicals including Asphalt, which is known to the State of California to cause cancer. For more information, go to <a href="https://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>.

## **International Regulations**

WHMIS: Non Hazardous

#### Section XVI - OTHER INFORMATION

#### **Other Precautions:**

Do not take internally.

Keep away from children.

For external use only.

Store in a cool, dry place.

Keep away from sources of ignition.

Do not apply during or before rain to avoid runoff.

Do not apply if pavement is below 55 degrees F.

**NFPA Rating:** Health 1; Fire 1: Reactivity 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

**Revision Date:** 04/05/2018 **Supersedes:** 04/08/2015

#### **Disclaimer/Statement of Liability:**

THE INFORMATION AND RECOMMENDATIONS PROVIDED HEREIN ARE BELIEVED TO BE ACCURATE AND ARE BASED UPON EXPERIENCE, TESTS, LITERATURE REFERENCES, AND/OR CALCULATIONS. THE MANUFACTURER MAKES NO GUARANTEE, EXPRESSED OR IMPLIED, AS TO THE AFFECT OF USE, OR THE SAFETY AND TOXICITY OF THE PRODUCT. THE INFORMATION CONTAINED IN THIS SHEET CANNOT BE TAKEN AS THE SUM TOTAL OF ALL PROTECTIVE MEASURES TO BE TAKEN.