

Battic Door Energy Conservation Products

P.O. Box 15
Mansfield, MA 02048-0015

508.320.9082 voice
508.339.4571 fax
www.batticdoor.com
mark@batticdoor.com

Specifications for radiant barrier foam pad used with Battic Door's Whole House Fan Seal Radiant Barrier with Velcro Attachment kits:

PRODUCT DIMENSIONS & DESCRIPTIONS: Double sided scrimmed aluminum foil laminated to polyethylene foam (1/4" nominal thickness)

WIDTH: 4', 5', 6' **LENGTH:** 125', 100', 84'

CORE MATERIAL: Polyethylene

FACINGS AVAILABLE: Foil/Foil

EDGINGS AVAILABLE: Trimmed, Staple Flange, EZ-Seal

FLAME AND SMOKE: ASTM E-84

FLAME SPREAD: Less than 25, **SMOKE DEVELOPED:** Less than 50

FULL SCALE FIRE TEST: NFPA 286 - Foil/Foil Passed

R-VALUE: Up to R-11*

PERM RATING: E-96 - .008

*R-values vary depending on facing and assembly.

PRODUCT DIMENSIONS & DESCRIPTIONS: Double sided scrimless aluminum foil laminated to polyethylene foam (1/4" nominal thickness)

WIDTH: 4', 6' **LENGTH:** 125', 84'

CORE MATERIAL: Polyethylene

FACINGS AVAILABLE: Foil/Foil, Foil/White Foil

EDGINGS AVAILABLE: Trimmed, Staple Flange, EZ Seal

FLAME AND SMOKE: ASTM E-84

FLAME SPREAD: Less than 25, **SMOKE DEVELOPED:** Less than 50

FULL SCALE FIRE TEST: NFPA 286 - Foil/White Foil Passed

R-VALUE: Up to R-11*

PERM RATING: E-96 - .008

Thank you and Regards,

Mark D. Tyrol, P.E.

President

Battic Door Energy

