According to HCS-2012 APPENDIX D TO §1910.1200

Version: 1.0/ENRevision date: 02-Sep-2016Product name: SJDB R6P(AA) CARBON ZINC BATTERIESPrinting date: 02-Sep-2016

Tribudo hame. Sobb Not (NN) SANDON ZINO BATTENIES

1. Identification

(a) Product identifier

Product name: SJDB R6P(AA) CARBON ZINC BATTERIES

(b) Other means of identification

Product description: Model: R6P(AA)

Nominal Voltage: 1.5V

Weight: 14.0g

Dimension: 49.6mm×14.0mm (T×D)

(c) Recommended use of the chemical and restrictions on use

Recommended use: Carbon zinc Battery.

Restriction on use: No information available.

(d) Details of the supplier of the product

Company name(China) Guangdong Liwang New Energy Co.,Ltd

Address: Shima District, Tangxia Town, Dongguan City, Guangdong Province, China

E-mail: qa1@liwangbattery.com Telephone: +86-769-86201111-8062

(e) Emergency phone number

+86-769-86201111-8062

2. Hazard(s) identification

(a) Classification of the chemical

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.

Acute toxicity - Oral	Category 4
Acute toxicity - Dermal	Category 4
Skin corrosion/irritation	Category 1 Sub-category A
Serious eye damage/eye irritation	Category 1
Carcinogenicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 1

(b) GHS Label elements, including precautionary statements

Emergency Overview

Signal word Danger

Hazard Statements

Harmful if swallowed

Harmful in contact with skin

Causes severe skin burns and eye damage

Causes serious eye damage

Suspected of causing cancer

Causes damage to organs through prolonged or repeated exposure

According to HCS-2012 APPENDIX D TO §1910.1200

Version: 1.0/ENRevision date: 02-Sep-2016Product name: SJDB R6P(AA) CARBON ZINC BATTERIESPrinting date: 02-Sep-2016



This product is an article which contains a chemical substance. Safety information is given for exposure to the article as sold. Intended use of the product should not result in exposure to the chemical substance This is a battery. In case of rupture: the above hazards exist.

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

In case of inadequate ventilation wear respiratory protection

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves

Do not breathe dust/fume/gas/mist/vapors/spray

Precautionary Statements – Response

Specific measures (see .? on this label)

IF exposed or concerned: Get medical advice/attention

Specific treatment (see supplemental first aid instructions on this label)

Eves

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Immediately call a POISON CENTER or doctor/physician

Skin

IF ON SKIN: Wash with plenty of soap and water Take off contaminated clothing and wash before reuse If skin irritation or rash occurs: Get medical advice/attention

Inhalation

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician

Ingestion: IF SWALLOWED: Call a POISON CENTER or doctor/physician.

if you feel unwell, Rinse mouth. Don't induce vomiting

Precautionary Statements – Storage: Store locked up

Precautionary Statements - Disposal: Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC): Not applicable

(c) Other information

Very toxic to aquatic life with long lasting effects;

Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.

(d) Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

According to HCS-2012 APPENDIX D TO §1910.1200

Version: 1.0/EN Revision date: 02-Sep-2016 Product name: SJDB R6P(AA) CARBON ZINC BATTERIES Printing date: 02-Sep-2016

3. Composition/information on ingredients

(a) Mixtures information					
Chemical name	CAS No.	Concentration%			
Manganese Dioxide	1313-13-9	37.0			
Zinc	7440-66-6	33.0			
Carbon Black	1333-86-4	10.0			
Water	7732-18-5	14.2			
Ammonium chloride	12125-02-9	0.6			
Paper	RR-01108-5	0.5			
Iron	7439-89-6	2.0			
Polypropylene	9003-07-0	1.5			
Zinc chloride	7646-85-7	1.2			

4. First-aid measures

(a) Description of first aid measures

General Advice First aid is upon rupture of sealed battery. Show this safety data sheet to the doctor in

attendance. Immediate medical attention is required.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye

wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to

do. Continue rinsing. Seek immediate medical attention/advice.

Skin contact: Wash off immediately with soap and plenty of water for at least 15 minutes. May cause an allergic

skin reaction. In the case of skin irritation or allergic reactions see a physician.

Inhalation: Remove to fresh air. Get medical attention immediately if symptoms occur. May cause allergic

respiratory reaction. If breathing has stopped, give artificial respiration. Get medical attention

immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.

Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. May produce an allergic reaction. If an allergic reaction occurs, stop use and seek medical help right away. Call a physician or poison control

center immediately.

Self-protection of

Ingestion:

Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Wear the first aider:

personal protective clothing (see section 8). Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.

(b) Most important symptoms/effects, acute and delayed

Most important symptoms and

Burning sensation. Itching. Rashes. Hives. May cause allergy or asthma symptoms or breathing

difficulties if inhaled. Coughing and/ or wheezing

effects

(c) Indication of any immediate medical attention and special treatment needed

Notes to Physician May cause sensitization of susceptible persons. Treat symptomatically.

According to HCS-2012 APPENDIX D TO §1910.1200

Version: 1.0/ENRevision date: 02-Sep-2016Product name: SJDB R6P(AA) CARBON ZINC BATTERIESPrinting date: 02-Sep-2016

5. Fire-fighting measures

(a) Extinguishing media

Suitable extinguishing media: Use foam, dry powder or dry sand, CO₂ as appropriate.

Unsuitable extinguishing media: No information available.

(b) Special hazards arising from the chemical

Under fire conditions, batteries may burst and release hazardous decomposition products when exposed to a fire situation. This could result in the release of flammable or corrosive materials. Hazardous combustion products: CO, CO₂, Metal oxides, Irritating fumes

(c) Special protective equipment and precautions for fire-fighters

Firefighters must wear fire resistant protective equipment and appropriate breathing apparatus. The staff must equip with filtermask (full mask) or isolated breathing apparatus. The staff must wear the clothes which can defense the fire and the toxic gas. Put out the fire in the upwind direction. Remove the container to the open space as soon as possible. Spray water on the containers in the fireplace to keep them cool until finish extinguishment.

6. Accidental release measures

(a) Personal precautions, protective equipment and emergency procedures

Personal Precautions Attention! Corrosive material. Avoid contact with skin, eyes or clothing.

Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of

spill/leak.

Other Information Refer to protective measures listed in Sections 7 and 8.

(b) Environmental Precautions

Environmental Precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage

or spillage if safe to do so. Should not be released into the environment. Do not

allow to enter into soil/subsoil. Prevent product from entering drains.

(c) Methods and materials for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

7. Handling and storage

(a) Precautions for safe handling

In case of rupture: Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

(b) Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.

Keep out of the reach of children.

Incompatible Products Strong acids. Strong oxidizing agents. Strong bases.

According to HCS-2012 APPENDIX D TO §1910.1200

Version: 1.0/ENRevision date: 02-Sep-2016Product name: SJDB R6P(AA) CARBON ZINC BATTERIESPrinting date: 02-Sep-2016

8. Exposure controls/personal protection

(a) Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Manganese dioxide 1313-13-9	TWA: 0.02 mg/m3 Mn TWA: 0.1 mg/m3 Mn	(vacated) Ceiling: 5 mg/m3 Ceiling: 5 mg/m3 Mn	IDLH: 500 mg/m3 Mn TWA: 1 mg/m3 Mn STEL: 3 mg/m3 Mn
Carbon black 1333-86-4	TWA: 3 mg/m3 inhalable fraction	TWA: 3.5 mg/m3 (vacated) TWA: 3.5 mg/m3	IDLH: 1750 mg/m3 TWA: 3.5 mg/m3 TWA: 0.1 mg/m3 Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
Zinc 7440-66-6	STEL: 10mg/m³ respirable fraction TWA: 2mg/m³ respirable fraction	TWA: 5mg/m³ fume TWA: 15mg/m³ toal dust TWA: 5mg/m³ respirable fraction	IDLH: 50 mg/m³ Ceilng: 15mg/m³ dust TWA: 5mg/m³ dust and fume STEL: 10mg/m³ fume

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value

OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life

or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d

962 (11th Cir., 1992) See section 15 for national exposure control parameters

(b) Appropriate engineering controls

Engineering Measures Showers

Eyewash stations Ventilation systems

(c) Individual protection measures, such as personal protective equipment

Eye/Face Protection Face protection shield.

Skin and Body Protection Wear protective gloves and protective clothing. Long sleeved clothing. Chemical

resistant apron. Impervious gloves.

Respiratory Protection No protective equipment is needed under normal use conditions. If exposure limits

are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Do not eat,

drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Wash hands before breaks and immediately after handling the

product.

9. Physical and chemical properties

(a) Appearancesolid(b) OdorOdorless(c) Odor thresholdNot available.

According to HCS-2012 APPENDIX D TO §1910.1200

Version: 1.0/ENRevision date: 02-Sep-2016Product name: SJDB R6P(AA) CARBON ZINC BATTERIESPrinting date: 02-Sep-2016

(d) pH Not available. (e) Melting point/freezing point Not available. (f) Initial boiling point and boiling range Not available. Not applicable. (g) Flash point (h) Evaporation rate Not applicable. (i) Flammability Non flammable. (j) Upper/lower flammability or explosive limits Not available. (k) Vapor pressure Not applicable. (I) Vapor density Not available. (m) Relative density Not available. (n) Solubility(ies) Insoluble in water. Not available. (o) Partition coefficient: n-octanol/water (p) Auto-ignition temperature Not available. Not available. (q) Decomposition temperature Not available. (r) Viscosity

10. Stability and reactivity

(a) Reactivity

No data available.

(b) Chemical stability

Stable under recommended storage conditions.

(c) Possibility of hazardous reactions

None under normal processing.

(d) Conditions to avoid

None known based on information supplied.

(e) Incompatible materials

Strong acids. Strong oxidizing agents. Strong bases.

(f) Hazardous decomposition products

Carbon oxides.

11. Toxicological information

(a) Information on the likely routes of exposure

Product Information Product does not present an acute toxicity hazard based on known or

supplied information.

In case of rupture:

Inhalation: Specific test data for the substance or mixture is not available. May cause

irritation of respiratory tract. May cause sensitization of susceptible

persons. (based on components)

Ingestion: Specific test data for the substance or mixture is not available. Ingestion

According to HCS-2012 APPENDIX D TO §1910.1200

Version: 1.0/ENRevision date: 02-Sep-2016Product name: SJDB R6P(AA) CARBON ZINC BATTERIESPrinting date: 02-Sep-2016

may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May be harmful if

under "Inhalation".

Skin contact: Specific test data for the substance or mixture is not available. Expected to

be an irritant based on components. Irritating to skin. Prolonged contact may cause redness and irritation. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). Specific test data for the substance or mixture is not available. Expected to

swallowed. (based on components). May cause additional affects as listed

be an irritant based on components. Severely irritating to eyes. Causes serious eye damage. May cause burns. May cause irreversible damage to

eyes.

Component Information

Eye contact:

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Manganese dioxide	= 9000 mg/kg (Rat)		
1313-13-9			
Iron	= 984 mg/kg (Rat)		
7439-89-6	- 964 Hig/kg (Kat)		

(b) Information on toxicological characteristics

Symptoms Erythema (skin redness). May cause redness and tearing of the eyes. May

cause blindness. Burning. Itching. Rashes. Hives. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain, or

flushing. Coughing and/ or wheezing.

(C) Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization May cause sensitization of susceptible persons. May cause sensitization by

skin contact. May cause sensitization by inhalation.

Mutagenic Effects No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as

a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Carbon black	A3			
1333-86-4				

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

Reproductive Toxicity

STOT - single exposure

No information available

No information available

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure. Based

on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT

RE).

Chronic Toxicity No known effect based on information supplied. Prolonged exposure may

According to HCS-2012 APPENDIX D TO §1910.1200

Version: 1.0/EN Revision date: 02-Sep-2016 Product name: SJDB R6P(AA) CARBON ZINC BATTERIES Printing date: 02-Sep-2016

> cause chronic effects. Repeated contact may cause allergic reactions in very susceptible persons. Contains a known or suspected mutagen. Possible risk of irreversible effects. Contains a known or suspected carcinogen. Contains a known or suspected reproductive toxin. Avoid repeated exposure. May cause adverse effects on the bone marrow and blood-forming system.

> Respiratory system. Eyes. Skin. May affect the genetic material in germ cells (sperm and eggs). Gastrointestinal tract (GI). Reproductive System. Blood.

Central Nervous System (CNS). Kidney. Lungs. Nasal cavities.

No information available.

Aspiration Hazard

Target Organ Effects

12. Ecological information

(a) Ecotoxicity

Very toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity t	o	Daphnia	Magna
			Microorganisms		(Water Flea)	
Iron		96h LC50: = 13.6 mg/L				
7439-89-6		(Morone saxatilis)				
Zinc 7440-66-6	96h EC50: 0.11 - 0.271 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 0.09 - 0.125 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 2.16 - 3.05 mg/L (Pimephales promelas) 96h LC50: 0.211 - 0.269 mg/L (Pimephales promelas) 96h LC50: = 2.66 mg/L (Pimephales promelas) 96h LC50: = 30 mg/L (Cyprinus carpio) 96h LC50: = 0.45 mg/L (Cyprinus carpio) 96h LC50: = 7.8 mg/L (Cyprinus carpio) 96h LC50: = 3.5 mg/L (Lepomis macrochirus) 96h LC50: = 0.24 mg/L (Cyprinus carpio) 96h LC50: = 0.24 mg/L (Cyprinus macrochirus) 96h LC50: = 0.59 mg/L (Cyprinus mykiss) 96h LC50: = 0.59 mg/L (Cyprinus mykiss) 96h LC50: = 0.41 mg/L (Cyprinus mykiss) 96h LC50: = 0.41 mg/L (Cyprinus mykiss) 96h LC50: = 0.41 mg/L (Cyprinus mykiss)			48h EC50: 0.139 mg/L	- 0.908

(b) Persistence and Degradability

No information available.

(c) Bioaccumulative potential

No information available.

(d) Other adverse effects

According to HCS-2012 APPENDIX D TO §1910.1200

Version: 1.0/ENRevision date: 02-Sep-2016Product name: SJDB R6P(AA) CARBON ZINC BATTERIESPrinting date: 02-Sep-2016

No information available.

13. Disposal considerations

(a) Waste treatment methods

Disposal methods This material, as supplied, is not a hazardous waste according to Federal regulations (40

CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state,

regional, or local regulations for additional requirements.

Contaminated Packaging Dispose of contents/containers in accordance with local regulations

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste	
Zinc	Ignitable powder Toxic	
7440-66-6	igrillable powder Toxic	

14. Transport information

DOT NOT REGULATED

Proper Shipping Name NON REGULATED

Hazard Class N/A

TDG Not regulated

MEX Not regulated

ICAO Not regulated

IATA Not regulated

Proper Shipping Name NON REGULATED

Hazard Class N/A

IMDG/IMO Not regulated

Hazard Class N/A

Marine Pollutant Product is a marine pollutant according to the criteria set by IMDG/IMO

RIDNot regulatedADRNot regulatedADNNot regulated

15. Regulatory information

(a) Safety, health and environmental regulations specific for the product in question

CAS No.	USA	EU	Japan	Korea	China	Canada
CAS NO.	TSCA	EINECS	ENCS	ECL	IECSC	DSL
1313-13-9	Listed	Listed	Listed	Listed	Listed	Listed
7440-66-6	Listed	Not listed	Listed	Listed	Listed	Listed
1333-86-4	Listed	Listed	Listed	Listed	Listed	Listed
7732-18-5	Listed	Not listed	Listed	Listed	Listed	Listed

According to HCS-2012 APPENDIX D TO §1910.1200

Version: 1.0/EN Revision date: 02-Sep-2016 Printing date: 02-Sep-2016

Product name: SJDB R6P(AA) CARBON ZINC BATTERIES

12125-02-9	Listed	Listed	Listed	Listed	Listed	Not listed
RR-01108-5	Listed	Listed	Listed	Listed	Listed	Listed
7439-89-6	Listed	Not listed	Listed	Listed	Listed	Listed
9003-07-0	Listed	Listed	Not listed	Listed	Listed	Not listed
7646-85-7	Listed	Not listed	Listed	Listed	Listed	Not listed

16. Other information, including date of preparation or last revision

(a) Preparation and revision information

Date of previous revision: Not applicable. Date of this revision: 02-Sep-2016

Revision summary: The first New SDS

(b) Abbreviations and acronyms

TSCA: Toxic Substances Control Act, The American chemical inventory.

DSL **Domestic Substances List**

EINECS: European Inventory of Existing Commercial chemical Substances

ENCS Japanese Existing and New Chemical Substances

ECL: Existing Chemicals List, the Korean chemical inventory. IECSC: Inventory of existing chemical substances in China.

(c) Disclaimer

Because all of our batteries are defined as "articles", they are exempted from the requirements of the Hazard Communication Standard. The information in this SDS is provided all the relevant data fully and truly. However, the information is provided without any warranty on their absolute extensiveness and accuracy. This SDS was prepared to provide safety preventive measures for the users who have got professional training. The personal user who obtained this SDS should make independent judgment for the applicability of this SDS under special conditions. In these special cases, we do not assume responsibility for the damage.

 End	of the	SDS	
 End	of the	SDS	