

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Product Name: Masonry, Stucco & Brick Paint Satin White

MSDS Manufacturer 2

Number:

Number:

Manufacturer Name: BEHR Process Corporation
Address: 3400 W. Segerstrom Avenue
Santa Ana, CA 92704

 General Phone Number:
 (714) 545-7101

 General Fax Number:
 (714) 241-1002

 Customer Service Phone
 (800) 854-0133 ext. 2

CHEMTREC: For emergencies in the US, call CHEMTREC: 800-424-9300

Canutec: In Canada, call CANUTEC: (613) 996-6666 (call collect)
MSDS Creation Date: January 30, 2007

MSDS Revision Date: January 30, 2007

MSDS Revision Date: January 31, 2010

MSDS Format: According to ANSI Z400.1-2004



HMIS	
Health Hazard	1
Fire Hazard	1
Reactivity	0
Personal	
Protection	

* Chronic Health Effects

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent
Titanium dioxide	13463-67-7	10 - 30 by weight
Vinyl-acrylic based polymer	Proprietary	10 - 30 by weight
Nepheline Syenite	37244-96-5	5 - 10 by weight
2,2,4-Trimethyl-1,3-Pentanediol Monoisobutyrate	25265-77-4	1 - 5 by weight
Ethylene glycol	107-21-1	1 - 5 by weight
Non hazardous ingredient(s)	Not applicable	30 - 60 by weight

SECTION 3 - HAZARDS IDENTIFICATION

Emergency Overview: Irritant.

Potential Health Effects:

Eye: May cause irritation.
Skin: May cause irritation.

Inhalation: Prolonged or excessive inhalation may cause respiratory tract irritation.

Ingestion: May be harmful if swallowed. May cause vomiting.

Chronic Health Effects: Prolonged or repeated contact may cause skin irritation.

Signs/Symptoms: Overexposure may cause headaches and dizziness.

Target Organs: Eyes. Skin. Respiratory system. Digestive system.

Aggravation of Pre-Existing None generally recognized.

Conditions:

Inhalation:

SECTION 4 - FIRST AID MEASURES

Eye Contact: Immediately flush eyes with plenty of water for 15 to 20 minutes. Get medical

attention, if irritation or symptoms of overexposure persists.

Skin Contact: Immediately wash skin with soap and plenty of water.

Get medical attention if irritation develops or persists.

If inhaled, remove to fresh air. If not breathing, give artificial respiration or give

oxygen by trained personnel. Seek immediate medical attention.

Ingestion: If swallowed, do NOT induce vomiting. Call a physician or poison control center

immediately. Never give anything by mouth to an unconscious person.

Other First Aid: Due to possible aspiration into the lungs, DO NOT induce vomiting if ingested.

Provide a glass of water to dilute the material in the stomach. If vomiting occurs naturally, have the person lean forward to reduce the risk of aspiration.

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point: No Data
Lower Flammable/Explosive Limit: Not applicable.
Upper Flammable/Explosive Limit: Not applicable.

Extinguishing Media: Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog or spray

when fighting fires involving this material.

Protective Equipment: As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH

(approved or equivalent) and full protective gear

NFPA Ratings:

1 NFPA Health: NFPA Flammability: 1 NFPA Reactivity: 0

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personnel Precautions: Use proper personal protective equipment as listed in section 8.

Environmental Precautions: Avoid runoff into storm sewers, ditches, and waterways.

Spill Cleanup Measures: Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical

waste container. Provide ventilation. Clean up spills immediately observing

precautions in the protective equipment section.

SECTION 7 - HANDLING and STORAGE

Handling: Use with adequate ventilation. Avoid breathing vapor and contact with eyes, skin

Store in a cool, dry, well ventilated area away from sources of heat, combustible Storage:

materials, and incompatible substances. Keep container tightly closed when not in

Hygiene Practices: Wash thoroughly after handling. A void contact with eyes and skin. A void inhaling

vapor or mist.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls: Use appropriate engineering control such as process enclosures, local exhaust

> ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training,

inspection and maintenance of the personal protective equipment.

Eye/Face Protection: Wear appropriate protective glasses or splash goggles as described by 29 CFR

1910.133, OSHA eye and face protection regulation, or the European standard EN

Skin Protection Description: $Chemical\mbox{-resistant gloves and chemical goggles, face-shield and synthetic apron}$

or coveralls should be used to prevent contact with eyes, skin or clothing Wear appropriate protective gloves. Consult glove manufacturer's data for

permeability data.

Respiratory Protection: A NIOSH approved air-purifying respirator with an organic vapor cartridge or

> canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide

adequate protection.

Other Protective: Facilities storing or utilizing this material should be equipped with an eyewash

facility and a safety shower.

EXPOSURE GUIDELINES

Titanium dioxide:

Guideline ACGIH: TLV-TWA: 10 mg/m3 Guideline OSHA: OSHA-TWA: 15 mg/m3

Ethylene glycol:

Vapor Pressure:

Guideline ACGIH: TLV-STEL: C 100 mg/m3 (Aerosol only)

SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

Physical State Appearance: Liquid. Color: White **Boiling Point:** No Data Melting Point: No Data Density: 10 - 12 Lbs./gal. Greater than 1 (Air = 1). Vapor Density: Greater than 1 (Air = 1).

No Data Molecular Formula: Mixture Molecular Weight: Mixture Flash Point: No Data

VOC Content: Material VOC: 56 gm/l (Includes Water) Coating VOC.: 140 gm/l (Excludes Water)

SECTION 10 - STABILITY and REACTIVITY

Chemical Stability: Stable under normal temperatures and pressures.

Hazardous Polymerization: Not reported.

Conditions to Avoid: Heat, flames, incompatible materials, and freezing or temperatures below 32 deg.

F.

Incompatible Materials: Oxidizing agents. Strong acids and alkalis.

Special Decomposition Products: Incomplete combustion may produce carbon monoxide and other toxic gases.

SECTION 11 - TOXICOLOGICAL INFORMATION

Titanium dioxide:

RTECS Number: XR2275000

Skin: Skin - Rabbit; Standard Draize Test.: 300 ug/3D; (Intermittent) mild. (RTECS)

Ingestion: Ingestion - Rat TDLo: 60 gm/kg: Gastrointestinal - hypermotility, diarrhea

Gastrointestinal - other changes. (RTECS)

2,2,4-Trimethyl-1,3-Pentanediol Monoisobutyrate:

RTECS Number: UF6000000

Ingestion: Ingestion - Rat LD50: 3200 mg/kg - Details of toxic effects not reported other

than lethal dose value.

Ingestion - Mouse LD50: 3200 mg/kg - [Details of toxic effects not reported other

than lethal dose value.. (RTECS)

Ethylene glycol:

Inhalation:

RTECS Number: KW2975000

Eye: Eye - Rabbit; Standard Draize Test. : 500 mg/24H; mild.

Eye - Rabbit; Standard Draize Test.: 1440 mg/6H; Moderate. (RTECS)

Skin - Rabbit; Open irritation : 555 mg; mild. (RTECS)

Inhalation - Rat LC: >200 mg/m3/4H; Details of toxic effects not reported other

than lethal dose value.

Inhalation - Mouse LC: >200 mg/m3/2H; Details of toxic effects not reported

other than lethal dose value. (RTECS)

Ingestion: Ingestion - Rat LD50: 4700 mg/kg; Details of toxic effects not reported other

than lethal dose value.. (RTECS)

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity: No ecotoxicity data was found for the product.

Environmental Fate: No environmental information found for this product.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the

classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local

guidelines.

SECTION 14 - TRANSPORT INFORMATION

DOT UN Number: No Data
DOT Hazard Class: No Data

SECTION 15 - REGULATORY INFORMATION

California PROP 65: WARNING: This product contains a chemical known to the state of California to

cause cancer and birth defects or other reproductive harm.

<u>Titanium dioxide</u>:

TSCA Inventory Status: Listed

State Regulations: Listed in the New Jersey State Right to Know List.

Listed in the Pennsylvania State Hazardous Substances List.

Canada DSL: Listed

Nepheline Syenite:

TSCA Inventory Status: Not listed
Canada DSL: Listed
2,2,4-Trimethyl-1,3-Pentanediol Monoisobutyrate:

TSCA Inventory Status: Listed Canada DSL: Listed

Ethylene glycol:

TSCA Inventory Status: Listed

State Regulations: Listed in the New Jersey State Right to Know List.

Listed in the Pennsylvania State Hazardous Substances List.

Canada DSL: Listed

SECTION 16 - ADDITIONAL INFORMATION

HMIS Health Hazard:

HMIS Fire Hazard: 1
HMIS Reactivity: 0
HMIS Other: x

MSDS Creation Date: January 30, 2007
MSDS Revision Date: January 31, 2010
MSDS Revision Notes: Quarterly formula update
MSDS Author: Actio Corporation

Disclaimer: This Health and Safety Information is correct to the best of our knowledge and

belief at the date of its publication but we cannot accept liability for any loss, injury or damage which may result from its use. We shall ensure, so far as is reasonably practicable, that any revision of this Data Sheet is sent to all customers to whom we have directly supplied this substance, but must point out that it is the responsibility of any intermediate supplier to ensure that such revision is passed to the ultimate user. The information given in the Data Sheet is designed only as a guidance for safe handling, storage and the use of the substance. It is not a specification nor does it guarantee any specific properties. All chemicals should be handled only by competent personnel, within a controlled environment. Should further information be required, this can be obtained through

the sales office whose address is at the top of this data sheet.

Trademark: The trademarks, service marks, graphics and logos used on this MSDS are

registered or unregistered trademarks of BEHR Process Corporation. All Rights

Reserved.

 $Copyright @ \ 1996-2010 \ \underline{Actio\ Software\ Corporation}. \ All\ Rights\ Reserved.$

Masonry, Stucco & Brick Paint Satin White Revison:1/31/2010, Version:0