

# CONNECTED

# HOT WATER

## WHY ECONET?

- Water leak detection and auto system shut-off\*
- Mobile alerts for notifications & maintenance reminders
- Gas and water usage reports
- Integration with Nest® and Wink® smart home systems
- Mobile Water Temperature Control

## WHY TANKLESS?

- Continuous Hot Water
- High Energy Efficiency
- Space Saving Wall Hang Design
- Indoor & Outdoor Models
- Water Saving Settings
- Ultra Low NOx Burners
- PVC Venting Options



## TANKLESS WITH BUILT-IN ECONET®

Select Rheem tankless gas water heaters are available with EcoNet® built-in to save time on installation and add smart home connected features for homeowners. No additional accessories required.

DESCRIPTION				FEATURES					ROUGHING IN DIMENSIONS (SHOWN IN INCHES)					ENERGY INFO.		
MODEL NUMBER	GAS INPUT BTU/H	TYPE	NUMBER OF BATHROOMS**	TEMP. RANGE	MIN. FLOW/ACTIVATION GPM	GPM @ 67° RISE MAX.	GPM @ 45° RISE MAX.	MAX. GPM	CONNECTION		HEIGHT	WIDTH	DEPTH	VENT DIAM.	SHIP WEIGHT (LBS.)	UNIFORM ENERGY FACTOR (UEF)
									WATER	GAS						
<b>Rheem Performance Platinum™ High Efficiency Condensing Models</b>																
ECO200DVELN3-1 (EcoNet® Included)	11,000-199,900	Indoor Direct Vent	4	85° to 140° F	0.26/0.40	5.7	8.5	9.5	3/4	3/4	27-1/2	18-1/2	9-3/4	2", 3" or 4" PVC 2-Pipe	82	0.93
ECO200XELN3-1 (EcoNet® Included)	11,000-199,900	Outdoor	4	85° to 140° F	0.26/0.40	5.6	8.5	9.5	3/4	3/4	27-1/2	18-1/2	9-3/4	N/A	82	0.93
ECO180DVELN3-1 (EcoNet® Included)	11,000-180,000	Indoor Direct Vent	3 - 4	85° to 140° F	0.26/0.40	5.2	7.7	9.0	3/4	3/4	27-1/2	18-1/2	9-3/4	2", 3" or 4" PVC 2-Pipe	82	0.93
ECO180XELN3-1 (EcoNet® Included)	11,000-180,000	Outdoor	3 - 4	85° to 140° F	0.26/0.40	5.2	7.7	9.0	3/4	3/4	27-1/2	18-1/2	9-3/4	N/A	82	0.93
<b>Rheem Performance Plus® Mid-Efficiency Models</b>																
ECO200DVELN3-1 (EcoNet® Included)	11,000-199,900	Indoor Direct Vent	3-4	85° to 140° F	0.26/0.40	5.0	7.4	9.5	3/4	3/4	25-5/8	13-7/8	9-7/8	3 by 5 CONCENTRIC	54	0.82
ECO200XELN3-1 (EcoNet® Included)	11,000-199,900	Outdoor	3-4	85° to 140° F	0.26/0.40	4.9	7.4	9.5	3/4	3/4	23-5/8	13-7/8	8-7/8	N/A	54	0.81
ECO180DVELN3-1 (EcoNet® Included)	11,000-180,000	Indoor Direct Vent	3	85° to 140° F	0.26/0.40	4.5	6.7	8.4	3/4	3/4	25-5/8	13-7/8	9-7/8	3 by 5 CONCENTRIC	54	0.82
ECO180XELN3-1 (EcoNet® Included)	11,000-180,000	Outdoor	3	85° to 140° F	0.26/0.40	4.5	6.7	8.4	3/4	3/4	23-5/8	13-7/8	8-7/8	N/A	54	0.81

\*Indoor models only.

\*\*Based on simultaneous showers using 2.5 gallons per minute. Flow rates vary depending on temperature of cold water supply. LP models also available, swap N (Natural Gas) for P (Liquid Propane in all models above).



The new degree of comfort.®