



# Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224  
Phone: 410-675-2100 or 800-543-3840

Revised: 3/7/14

## DAP® PLASTIC WOOD® Wood Putty

- Non-hardening wood putty that quickly repairs holes and minor defects after assembly and finishing to achieve a polished, finished look
- Hides countersunk nail holes, gouges, scratches & mitre joints
- Colors can be blended for custom color matching
- Interior use

**Packaging:** Net Weight 3.7 oz. ( g)

**Colors:** White, Natural Oak, Light Oak, Natural Pine, Red Oak, Light Walnut, Dark Walnut, Red Mahogany, Maple, Cherry, Ebony, Pickled Oak

**UPC Numbers:** 70798 21245, 70798 21247, 70798 21250, 70798 21251, 70798 21255,  
70798 21262, 70798 21266, 70798 21268, 70798 21270, 70798 21272, 70798 21276,  
70798 21274

### Company Identification:

Manufactured for: DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call 1-888-DAP-TIPS or visit [www.dap.com](http://www.dap.com) and click on “Ask the Expert”

Order Information: 800-327-3339

Fax Number: 410-558-1068

Also, visit the DAP website at [dap.com](http://dap.com)

### Product Description:

DAP® PLASTIC WOOD® Wood Putty is an easy-to-use, non-hardening wood putty that quickly repairs holes and minor defects in interior surfaces after assembly and finishing. Recommended for filling and hiding countersunk nail holes, gouges, scratches and mitre joints. Colors can be blended for custom color matching. Interior use only. Non-paintable.

### Suggested Uses:

*Ideal for quick repairs of minor scratches, gouges, nail holes and other minor imperfections on interior surfaces such as:*

- Baseboards
- Paneling
- Cabinetry
- Woodwork
- Molding
- Furniture
- Windows/Doors
- Mitre joints
- Other wood surfaces

### Surface Preparation & Application:

1. Surface to be filled must be clean and dry. Surface, wood putty and air temperature should be 40°F or higher.
2. Stain, seal or topcoat surface before applying wood putty. Product cannot be painted, stained or coated.
3. Press DAP® PLASTIC WOOD® Wood Putty firmly into nail holes or other imperfections.
4. Avoid excess contact with surrounding area. Wipe excess from surrounding area with a cloth, rag or towel.
5. Wood Putty will not harden to a sandable surface

6. Most repairs require just one fill. Deep holes may require more than one application.
7. Colors can be blended for custom matches. Test color match on scrap or inconspicuous area prior to application.

**For Best Results:**

- This product is designed to be applied as a final finish.
- This product is not stainable, sandable or paintable.

**Typical Physical & Chemical Characteristics:**

Consistency:	Knife Grade Putty
Vehicle:	Blend of vegetable and mineral oils
Volatile:	Aliphatic Hydrocarbons
Filler:	Inorganic fillers and color pigments
Weight Per Gallon:	18.1 ± 0.2 lbs.
Odor:	Mild, pleasant
Solids:	98.8 ± 0.7%
Application Temperature Range:	40°F Minimum
Time to Skin:	24 to 36 hours
Shelf Life:	12 months
MSDS No.:	00077064001

**Clean Up & Storage:**

Clean tools immediately after use with mineral spirits. Do not use mineral spirits to clean skin. Dried putty must be cut or scraped away. Be sure container lid is closed and tightly sealed. Store in a cool, dry place away from extreme heat or cold.

**Safety:**

**WARNING:** This product contains chemicals known to the State of California to cause cancer. May irritate skin. Wear gloves. Wash skin with soap and water. Do not take internally. **KEEP OUT OF REACH OF CHILDREN.** Get medical attention if complications arise from any exposure. For emergencies, call your poison control center at 1-800-222-1222. See product label and Safety Data Sheet (SDS) for additional safety information. You can request an SDS sheet by visiting our website at [www.dap.com](http://www.dap.com) or calling **1-888-DAP-TIPS.**

**Limited Warranty:**

DAP will not accept liability for more than replacement product or sales price refund.