

Stone Enhancer Matte Finish - Water Based

FILASTONE PLUS **eco**

 **SEALER**
WATER BASED

FILA[®]
surface care solutions

ALL NATURAL STONE



● **MATTE, COLOR ENHANCING, ECO-FRIENDLY PROTECTION.**

● **UV RESISTANT AND NON YELLOWING.**



Coverage:

1 QT (0.95 L)

Polished stone ▶ 405 sq.ft. (38 m²)

Natural stone ▶ 200-250 sq.ft. (19-24 m²)

Coverage rates are indicative and per coat.



Packaging:

0.5 GAL (1.89 L) 4 plastic bottles per box

1 QT (946 ml) 5 plastic bottles per box

WHAT IT'S FOR

- Enriches the color of polished, honed, textured and tumbled natural stone.
- Provides a matte finish that highlights the natural surface character.
- Protects the surface from dirt, water and oil stains.
- Intensifies the stone's natural color with a matte finish.
- Excellent protection for countertops, inlays and backsplashes.

ADVANTAGES

- Dual action: seals and enhances surfaces.
- Eco-friendly: water-based.
- Ideal for indoor and outdoor surfaces.
- Does not form a film or yellow over time.
- UV and weather resistant.
- Long lasting protection.
- Certified safe in food preparation areas.
- Provides very high coverage rates.
- Very low VOC emissions: contributes towards LEED credits. (LEED, is a certification for the design of green buildings.)

HOW TO USE IT

Instructions: On a clean, dry surface apply FILASTONE PLUS ECO with a paintbrush, lambswool applicator, sponge or other suitable applicator. Rub the surface to allow the product to completely penetrate; wipe away any excess. The surface can be walked on after just 4 hours. For a deeper, more intense color, apply 2-3 coats; wait at least 4 hours between coats. Remove any excess residue by rubbing the surface with a cloth soaked in FILASTONE PLUS ECO. **To increase stain protection** on unpolished, absorbent stone apply one coat of FILASTONE PLUS ECO, wait at least 4 hours, then apply a coat of FILAMP90 ECO PLUS. **Caution:** Once the surface has been treated with FILASTONE PLUS ECO, the treatment cannot be reversed; the stone cannot return to its original state. Before full application, test the product on a small, inconspicuous area or loose sample to check the effect and color on the stone. Does not protect marble, limestone and travertine from acid stains. Apply and leave the product to dry in a well ventilated area. Keep the product in a cool, dry place.

Storage temperature: between 41°F and 86°F (5°C and 30°C). Must be applied at temperatures between 50°F and 86°F (10°C and 30°C).

Fila Chemicals USA, Corp.
Miami, FL 33172
tel +1-305-513-0708
filausa@filasolutions.com

TOLL FREE 1-844-FILA123



Recommended by over

200 INTERNATIONAL TOP BRANDS

manufacturers of materials for floors and wall coverings

usa.filasolutions.com