NaviTrack® Locators



NAVITRACK SCOUT® LOCATOR

The NaviTrack Scout Locator is designed to solve the most demanding remote transmitter (sonde) locates using multi-directional locating technology.

EASIER LOCATES

The NaviTrack Scout multi-directional antenna technology sees the entire signal all of the time. Simply
maximize the signal strength and you have found the target. No nulls or false peaks to complicate the
locate.

ACCURACY

• This locator verifies the locate position using a micro-mapping display to mark distinctive poles in front of and behind the target, insuring an accurate locate.

AUTOMATIC DEPTH

• Depth is automatically calculated and displayed when over the target.

SPECIFICATIONS

- Weight − 3 lbs (1.4 kg)
- Power Source 4 C-Cell batteries
- Battery Life Approximately 24 hours



- Sonde 16 Hz, 512 Hz, 640 Hz, 874 kHz and 33 kHz
- Line Trace 128 Hz, 1 kHz, 8 kHz and 33 kHz
- Passive AC Line Trace 60 Hz, 50 Hz
- Meets FCC Class B and EN 55022 Class B requirements

Catalog No	Description	Weight	
Catalog No.		lb.	kg
19238	NaviTrack Scout Locator	3	1.4



Accessories

Catalog No.	Description	Weight	
		lb.	kg
14818	NaviTrack Line Transmitter	7.5	3.4
16728	Remote Transmitter, 512-AAA	0.4	0.18
19793	Float Sondes (2), Plus Extra Battery		
20168	NaviTrack Brick Transmitter	2	0.9



Catalog No.	Description
12543	Marker Chips and Clip
20248	Scout Carrying Case

