

SKT14-CW-non DLC Skytile LED Panel



General Information	
Product Type	LED Recessed troffer
Product weight	14.6 lbs
Finish	Brushed aluminum extruded frame with opal diffuser
Dimensions	11.75" x 47.75" x 0.41"
Recommended product location	Indoor use only, T grid ceiling systems
Method of fix	Hanger wire(not supplied)- see instruction sheet
Warranty	5 year extended
Electrical	
Input voltage(V~) Frequency(Hz)	100-277V~ 50/60Hz (Max 0.75 Amp)
Secondary running current	700mA
Secondary voltage	27-42VDC (50VDC Max)
Power correction factor	0.9
Input electrical connections	Line(hot), Neutral(white), ground
Output electrical connections	V+ (RED), V- (BLACK) plug & play connector
Dimmable	Yes, 0-10V(recommended dimmers: LEVITON PART No: IP710/DS710)
Dimming control connections	Dim + (Purple), Dim - (grey)
Dimming ratio	0-100%
Short circuit protection	yes
Performance	
Wattage	40W
Lumen output	3400
Lumens per circuit Watts	85
LED life(hours)	50,000
Color temperature	4000K
LOR(light output ratio)	100%
Photometry(IES/LDT) available	yes, on request
Construction	
Main chassis	Mild steel back plate
Diffuser	Opal polycarbonate
Lens	Clear acrylic
Heat sink	extruded aluminium
Driver housing	polycarbonate

Visit our website at: www.leviton.com

© 2016 Leviton Manufacturing Co., Inc. All rights reserved.
All trademarks are the property of the respective owners.

LEVITON MANUFACTURING CO., INC. WORLD HEADQUARTERS

201 North Service Road, Melville, NY 11747-3138
Telephone: 1-800-323-8920 Fax: 1-800-832-9538
Tech Line(8:30AM-7:00PM E.T. Monday-Friday):1-800-824-3005

