



INTERIOR DRYWALL PRIMER & SEALER

NO. 73



PRODUCT INFORMATION

BEHR PREMIUM PLUS® Interior Drywall Primer & Sealer is fast-drying and seals uncoated and previously painted interior drywall, wallboard, and wood to promote a uniform finish for topcoats. This 100% Acrylic formula provides outstanding adhesion and hiding properties for topcoat products.

RECOMMENDED USES:

Use for interior applications in low moisture areas on new or unpainted:

- Drywall/Gypsum Board
- Wallboard
- Plaster
- Wood

PRODUCT SPECIFICATIONS:

Tint Bases/Max Tint Load:

No. 73 126 oz. / 4 oz.

Resin Type: 100% Acrylic Latex

Weight per Gallon: 10.1 lbs.

% Solids by Volume: 23%

% Solids by Weight: 36.3%

VOC: <50 g/L

Flash Point: N/A

Viscosity: 100 KU

Recommended Film Thickness:

Wet: 6.4 mils/Dry: 1.4 @ 250 Sq. Ft./Gal.

Wet: 4.0 mils/Dry: 0.9 mils @ 400 Sq. Ft./Gal.

Coverage: 250-400 Sq. Ft./Gal. depending on application method and substrate porosity. Does not include the loss of material from spraying.

APPLICATION:

Brush: Nylon/polyester

Roller: 3/8" - 1/2" nap

Airless Spray: At package consistency

Tip: .015" - .019"

Filter: Remove

Thinning: Not recommended. Product is formulated for use at package consistency only.

Dry Time: @ 77° & 50% RH

Longer dry time may be required in cooler temperatures and higher humidity.

To Touch: 30 minutes

To Recoat: 1 hour

Full Cure: 2 Weeks

SURFACE PREPARATION:

All surfaces must be clean, free of dust, chalk, oil, grease, wax, polish, mold and mildew stains, loose and peeling paint, rust, and all other foreign substances.

New Drywall: All drywall surfaces should be sufficiently sanded smooth. Remove any remaining drywall dust prior to priming. Allow all drywall compounds to be completely dry prior to coating. **Glossy Surfaces:** For maximum adhesion, sand the surface thoroughly before coating.

New Plaster: New plaster should be thoroughly dry and cured for a minimum of 30 days before painting. When cured, clean using a mixed solution of one part vinegar and one part water to remove efflorescence and neutralize.

Previously Painted Plaster: Remove all loose and peeling paint and all other foreign substances. Clean any dirt and grease by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water. Set nails and fill holes, scratches, and gouges with the appropriate spackling material. Let dry completely and sand smooth. Remove all dust with a tack or wiping cloth. Fill all gaps with a 100% acrylic, siliconized, paintable caulking, and allow to completely dry prior to coating.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Center at 1-800-424-LEAD or visit www.epa.gov/lead.

CLEAN UP:

Clean all tools and equipment with clean water.

For disposal of empty containers and unused product, contact your household refuse collection service.

COMPLIES WITH THE BELOW AS OF 4/1/2017			
SCAQMD	YES	LEED v.3 (2009) [†]	YES
CARB SCM 2007	YES	LEED v.4 [†]	YES
CARB	YES	MPI#	50
OTC Phase II	YES	MPI X-Green	50
OTC	YES	GREENGUARD®	YES
LADCO	YES	CHPS	YES
AIM	YES	NAHB/ICC NGBS	YES

This coating conforms to USDA regulatory requirements for incidental food-contact materials intended for use on surfaces not in direct contact with food, such as walls, floors and ceilings.

[†]Please visit www.usgbc.org/LEED for additional details.

GREENGUARD is a registered trademark of UL Company.

CAUTIONS/LIMITATIONS:

- Protect from freezing.
- Do not use on floors.
- For best results, apply at temperatures between 50°F - 90°F. Temperatures above 90°F may affect the application such as drying too fast. Avoid painting in direct sun.
- NOTE:** If the surface is hot to the touch it should be considered too hot to apply this coating.
- Shelf life under normal conditions is two years unopened.

GENERAL INFORMATION:



Warning! Causes eye and skin irritation. Wear protective clothing, gloves, eye, and face protection. Do not eat, drink, or smoke when using this product. Take off contaminated clothing and wash it before reuse. Wash hands thoroughly after handling. Dispose of unused contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.

First aid: If in eyes: Rinse cautiously with water for several minutes and remove contacts if present and easy to do.

Continue rinsing and get medical attention if eye irritation persists. **If on skin:** Wash with plenty of soap and water.

If swallowed: Rinse mouth and get medical attention if you feel unwell.