



CRYSTAL CLEAR COAT

WATER BASED SEALER

100% ACRYLIC



1320

AVAILABLE SIZES
5 GALLON PAIL

RESIN: 100% Acrylic

COLOR: Clear Satin Sheen

SOLIDS BY WEIGHT: 28 %

VISCOSITY: 52KU@75F

WEIGHT PER GALLON: 8.56 lbs.

FLASH POINT: None

RECOMMENDED COVERAGE:
200 sq. ft. per gallon, per
coat, depending on the porosity
and age of the concrete surface.

DRYING TIME@70F&50%RH:
To touch: 2 hours
72 hours for vehicle traffic

Drying times are influenced by
ambient temperature and relative
humidity.

CLEANUP: Soap & Water

VOC: 94.7 grams/liter

USES, FEATURES & BENEFITS

Anvil 100% Acrylic Crystal Clear Coat Sealer is a water-based, non-yellowing clear coating for sealing concrete, pavers, Chattahoochee and Exposed Aggregate concrete, residential driveways, walkways patios and decks. Delivers a satin sheen when applied to a properly prepared surface and is highly resistant to the effects of hot automobile tires and water blushing. It is formulated for use on exterior/interior surfaces. Its' durable acrylic formula also resists fading, scuffing, cracking, peeling and blistering. Is milky white color in the can, but dries crystal clear.

DIRECTIONS FOR USE AND SURFACE PREPARATION

Proper preparation will insure maximum adhesion, durability, and uniform coloration, The surface must be clean and free of all wax, grease, oil, dirt, acid, mildew, release agents and all other surface contaminants. Failure to remove grease, oil, soap or other contamination will interfere with adhesion of the Crystal Clear Coat. To clean surface and etch, we recommend following label directions on Anvil 1450 Concrete & Masonry Cleaner/Etcher. Concrete should be at least 45 days old to reduce the possibility of the occurrence of efflorescence. Do not apply to surfaces where hydrostatic pressure is present or over 3 lbs. of moisture per 1000 sq. ft. ASTM F1869-04. Not intended for use over wood or areas of standing water.

APPLICATION

Hand stir product thoroughly before application. Apply in one thin coat by brush, roller, fan tip pump sprayer or airless sprayer. Avoid heavy application resulting in runs, ponding, flood coating or puddling. Allow two hours drying time, if relative humidity is high (> 80%), allow an extra period of drying time. Some surfaces such as inclined driveways, patios, steps etc. may require a slip resistant additive for safety. Add Anvil #9105 Talon Grip Slip Resistant Additive to the final coat. This product should not be used in place of a non-skid finish. Coverage is approximately 200 sq. ft. per coat on coarse concrete. Do not dilute. Do not apply if the threat of rain is imminent or if the air/surface temperature is expected to be below 50°F within the first 24 hours of application. Do not apply in extreme heat of day or in direct hot sunlight. Allow 3 days (72 hours) before allowing vehicle traffic on the coating. Full cure in 21 days. We recommend that a parked car stand on cardboard until full cure.

CLEAN-UP

Roller covers and spray equipment can be cleaned with soapy water. Dried sealer will be difficult to remove from any surface.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE. ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear an NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID;** if you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.

CLOSE CONTAINER AFTER EACH USE. USE WITH ADEQUATE VENTILATION. USE PROTECTIVE CLOTHING TO AVOID CONTACT WITH SKIN AND EYES. KEEP AWAY FROM CHILDREN. KEEP FROM FREEZING

VOC 94.7 grams/liter



100% ACRYLIC RESIN

SATIN GLOSS SEALER

CLEAR WHEN DRY

HARD, IMPACT RESISTANT

CONCRETE SURFACES

RESISTS FADING AND CRACKING

RESISTANT TO MILD AUTO
CHEMICALS

SOAP & WATER CLEAN-UP

INTERIOR OR EXTERIOR USE

Issued October 2012 Supersedes all prior publications
gro

