

Specifications-Sturd-I-Floor®

Plytanium® plywood Sturd-I-Floor® panels are ideal for residential and light commercial construction, and provide outstanding performance for sub-floors. They add proven performance and durability to new homes, room additions and renovations.

Available Sizes (Sized for 4' x 8')

Square Edge 3'-11%'' (1.216 m) x 7'-11\%'' (2.435 m) **Tongue & Groove** 3'-11%'' (1.206 m) x 7'-11\%'' (2.435 m)

Building Code Performance Categories, Panel Thickness

• 19/32 CAT, 0.578" (14.68 mm)

• 23/32 CAT, 0.703" (17.85 mm)

• 1-1/8 CAT, 1.091" (27.71 mm)

Specifications

Length/Width Tolerance $+0, -\frac{1}{16}$ " (+0, -1.6 mm)

Straightness Tolerance $\pm \frac{1}{16}$ " (± 1.6 mm)Squareness Tolerance $\pm \frac{1}{8}$ " (± 3.2 mm)Primary SpeciesSouthern Yellow Pine

Testing Agency APA®-The Engineered Wood Association

Classification Exposure 1 – OSB suitable for uses not permanently exposed to the weather. Panels classified

as Exposure 1 are intended to resist the effects of mositure on structural performance as may

occur due to construction delays, or other conditions of similar severity.

Code Fire Classification Class III or C

Flame Spread Rating 76-200, smoke-developed index <450

Building Code Compliance PS 1-09

Other Information

Forestry Certification Plytanium plywood Sturd-I-Floor panels are made from wood

sourced through a system that is third-party certified to the Sustainable Forestry Initiative® procurement standard.

dustamable rolestry initiative productivent standard.

Green Building Programs See our Plytanium plywood *Sustainability Fact Sheet* available at *www.builditbetter.com* for more information on potential point

contributions towards specific green building programs.

NAHB Green Approved

Plytanium plywood has been "Green Approved" by the NAHB

Research Center, which means you can be assured that Plytanium

Research Center, which means you can be assured that Plytanium plywood complies with specific green practice criteria in the National Green Building Standard. See our product listing on www.GreenApprovedProducts.com for more information.



Good for you. Good for our forests.[™]





Specifications-Sturd-I-Floor®

Product Warranty

Plytanium® plywood is covered by a Lifetime Limited Warranty. For terms and conditions, please refer to our Lifetime Limited Warranty available at www.builditbetter.com.

International Shipping

To prevent the introduction and spread of plant pests, *ISPM 15: International Standards for Phytosanitary Measures*, requires that internationally shipped solid wood pallets be debarked, treated with heat or fumigated with methyl bromide, and marked with a seal of compliance. **Pallets made with engineered wood, including Plytanium plywood, are exempt from ISPM 15 regulations.** This is because the process of manufacturing engineered wood destroys any live organisms in the wood. (Source: "Boxes, Crate and Reel Manufacturing," *www.PerformancePanels.com*)

Formaldehyde Emissions

Plytanium plywood Sturd-I-Floor® panels contain no added urea formaldehyde resins. PS 1 and PS 2 structural panels are exempt from testing by the California Air Resources Board (CARB) in the *Composite Wood Air Toxic Control Measure (ATCM)* and phenolic bonded structural panels are exempt from testing or monitoring by HUD in the *Manufactured Home Construction and Safety Standards*.

Manufacturing Locations

Location	APA Mill Number	Zip Code	Harvest Radius
Camden, TX	515	75934	90 miles
Corrigan, TX	516	75939	90 miles
Dudley, NC	348	28333	80 miles
Emporia, VA	230	23847	40 miles
Gurdon, AR	517	71743	60 miles
Madison, GA	404	30650	100 miles
Prosperity, SC	329	29127	80 miles
Taylorsville, MS	282	39168	50 miles
Warm Springs, GA	324	31830	450 miles