



BEHR® Chalk Decorative Paint

No. 7100 White Base
No. 7130 Deep Base

- Smooth Matte Finish
- Great Hide
- Easy to Apply
- Available in over 1,000 colors



Protect
from Freezing



1 Hr Dry Time
2 Hr Recoat Time



Up to **150 sq. ft.**
Coverage



Soap & Water
Clean-Up

FOR TINT BASES – DO NOT USE WITHOUT THE ADDITION OF TINTING COLORANTS

WHERE TO USE

BEHR Chalk Decorative Paint can be applied over most existing finishes with little surface preparation. Apply to old or new wood, cast stone, concrete, or even metal surfaces†.

PREPARATION

All surfaces must be clean, free of dust, chalk, oil, grease, wax, polish, mold and mildew stains, loose and peeling paint, rust and all other foreign substances. For maximum adhesion, scuff sand glossy surfaces thoroughly before coating. Remove all dust with a damp cloth and allow to dry.

PRIME

Use BEHR Chalk Decorative Paint on properly prepared uncoated or painted interior surfaces. For wood that contains tannins, such as Redwood and Cedar, a coat of primer such as BEHR PREMIUM PLUS® Multi-Surface Primer & Sealer No. 436 is recommended.

†For improved adhesion, prime all uncoated metal, cast stone and concrete surfaces before painting.

APPLICATION

Shake the container thoroughly before opening for application. Apply when air and surface temperatures are between 50-90° F (10-32° C). Stir paint occasionally. Intermix containers of same product to ensure color and sheen uniformity. Use a high quality foam or 3/8-1/2" nap roller cover or nylon/polyester brush.

This product is formulated to be rich and concentrated to provide excellent hide and coverage. If you find this product to be too thick, add up to 2 oz. of water per quart to thin it to the desired thickness for smooth and easy application. Certain colors may require more than one coat for complete hide. Darker colors may require additional dry time between coats. Cooler temperatures or higher humidity may prolong drying time.

DISPOSAL

For disposal of empty containers, unused paint and soiled rags, contact your household refuse collection service.

Visit behr.com for painting tips, project advice and color coordination with the ColorSmart by BEHR® Tool, or download the ColorSmart by BEHR App on your mobile device.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

***LIMITED WARRANTY** For one year from the date of purchase, Behr Process Corporation warrants to the original consumer purchaser, (1) that the product meets Behr's manufacturing specifications, and (2) the performance of this product when applied according to the label instructions and specifications. If this product is found not to perform as specified on the label within one year from the date of purchase, Behr Process Corporation will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. **This warranty excludes (1) labor and costs of labor for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. To the extent permitted by applicable law, any implied warranties including the implied warranties of merchantability and of fitness for a particular purpose, are limited to the duration of this express warranty. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state. Note to residents of the State of New Jersey: The provisions of this warranty, including its limitations, are intended to apply to the fullest extent permitted by the laws of the State of New Jersey. To obtain warranty service, call 1-800-854-0133. Behr Process Corporation reserves the right to inspect any and all application of the product prior to processing your claim made under this warranty.

To consult with a Behr Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

WARNING Cancer and Reproductive Harm – www.P65Warnings.ca.gov

CAUTION. IRRITANT. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.

To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.

BEHR
A Masco Company

©2018 Behr Process Corporation
Santa Ana, CA 92705 U.S.A. • behr.com
V.O.C. <50 g/L • REV. 07/18