



Safety Data Sheet

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II – Europe
Conforms to Regulation (EC) No 1272/2008 and aligns to the United Nations Globally Harmonized System
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of the Work Health and Safety Act

Section 1 - Chemical Product and Company Identification

1.1 Product Name: **SEF 4 Cycle**

1.2 VP Racing Fuels, Inc., 7124 Richter Road, Elmhurst, TX 78112, 210.635.7744

1.3 Recommended Use: Small Engine Fuel

1.4 **RESTRICTIONS on USE** **HIS PRODUCT IS FOR SMALL 4 CYCLE GASOLINE ENGINE USE ONLY!**

1.5 Emergency Response Number: **CHEMTREC 800-424-9300**

International Emergency Telephone Number: **+1-703-527-3887**

1.6 See Section 16.3 for CHEMTREC in Country Emergency Number

Section 2 - Hazards Identification

2.1 **GHS HAZARD**

Hazard Classes

Hazard Categories

Highly Flammable liquid/vapor

Category 2

Specific Target Organs toxicity single exposure

Category 3

Specific Target Organs repeated exposure

Category 1

Eye Irritation

Category 2B

Skin Irritation

Category 2

Acute Toxicity (Oral)

Category 4

Mutagenicity

Category 1B

Carcinogen

Category 1B

Reproductive Toxicity

Category 2

Aspiration Hazard

Category 1

Toxic to Aquatic Life long Lasting Effects

Category 2

2.2 Signal Word: **Danger**

SEF 4 Cycle

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II – Europe
Conforms to Regulation (EC) No 1272/2008 and aligns to the United Nations Globally Harmonized System
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of the Work Health and Safety Act



Flame Health Hazard Irritant Aquatic Hazard

2.3 Pictograms:

2.4 Hazard Statements

PHYSICAL HAZARDS:

H225: Highly flammable liquid and vapor

HEALTH HAZARDS:

H302: Harmful if swallowed
H304: May be fatal if swallowed and enter the airway
H315: Causes skin irritation
H319: Causes serious eye irritation
H336: May cause drowsiness or dizziness
H340: May cause genetic defects
H350: May cause cancer
H361: Suspected of damaging fertility or the unborn child
H372: Causes damage to organs

ENVIRONMENTAL HAZARDS:

H411: Toxic to aquatic life with long lasting effects

PRECAUTIONARY STATEMENTS:

P102: Keep out of reach of children
P202: Do not handle until all safety precautions have been read and understood
P210: Keep away from sparks and open flames- No smoking
P260: Do not breathe vapors
P280: Wear protective gloves, clothing and eye protection

RESPONSE STATEMENTS:

P301 +310+ P331: IF SWALLOWED: USA Immediately call the National POISON CENTER at **800-222-1222**. OUT SIDE USA Immediately call poison center or doctor. DO NOT induce vomiting
P303+P361+353: IF ON SKIN Take off immediately all contaminated clothing. Rinse skin with water
P304+340: IF INHALED, Remove to fresh air and keep comfortable for breathing
P305+P351: IF IN EYES rinse cautiously with water for at least 15 minutes
P306+P361: IF ON CLOTHING, Take off contaminated clothing
P370: In case of fire use foam, carbon dioxide, dry chemical to extinguish fire
P376: Stop leaks if safe to do so. See section 6 for proper clean up

SEF 4 Cycle

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II – Europe
Conforms to Regulation (EC) No 1272/2008 and aligns to the United Nations Globally Harmonized System
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of the Work Health and Safety Act

STORAGE STATEMENTS:

P403: Keep Cool Store in a well-ventilated place

DISPOSAL STATEMENTS:

P501: Dispose of content and/or container in accordance with local, regional, national or international regulations

2.5 Hazards not otherwise classified (HNOC) or not covered by GHS: Repeated exposure may cause skin dryness or cracking.

Section 3 - Composition / Information on Ingredients

3.1

CAS#	EC#	Chemical Names	Percent	Other Identifiers
N/A	N/A	Blend of Aliphatic and Aromatic Hydrocarbons C-2 to C-20	100%	None

3.2 Blend

Chemical Names	CAS#	EC#
1,1,2-Trimethylethane	78-78-4	201-142-8
Phenylmethane	108-88-3	203-625-9
Alkylate Full Range	64741-64-6	265-066-7
Hydrotreated light distillate	64742-47-8	265-149-8

3.3 Trade Secret Provision and Chemical Concentration Disclosure: In accordance with OSHA and GHS Regulations we have withheld specific percentages of the chemicals in this mixture. The chemical concentrations have been disclosed as a blend and are applicable to the hazards as identified in this Safety Data Sheet

Section 4 - First Aid Measures

4.1 Eye: Contact with the eyes can cause serious irritation. Symptoms may include discomfort or pain and redness. Severe overexposure can result in swelling of the conjunctiva along with tissue damage.

Eyes: Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

4.2 Skin: Prolonged and repeated liquid contact can cause defatting and drying of the skin and can lead to irritation and/or dermatitis.

Skin: Flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical aid immediately. Wash clothing before reuse.

4.3 Ingestion: Liquid ingestion can cause inebriation, headache, gastrointestinal pain, nausea, and vomiting leading to central nervous system depression. Aspiration of liquid into the lungs must be avoided as even small quantities in the lungs can produce chemical pneumonia, pulmonary edema and even death.

Ingestion: Do NOT induce vomiting. Get medical aid immediately.

SEF 4 Cycle

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II – Europe
Conforms to Regulation (EC) No 1272/2008 and aligns to the United Nations Globally Harmonized System
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of the Work Health and Safety Act

4.4 Inhalation: Prolonged breathing of high vapor concentrations can produce headache, dizziness, nausea, and impaired vision. Excessive overexposure can cause central nervous system depression, loss of consciousness, liver damage and death resulting from respiratory failure.

Inhalation: Remove from exposure to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult and **IF TRAINED**, give oxygen. Get medical aid. Do NOT use mouth-to-mouth resuscitation without protection.

4.5 After first aid, get appropriate paramedic, or community medical support. The severity of outcome following ingestion may be more related to the time between ingestion and treatment, rather than the amount ingested. Therefore, there is a need for rapid treatment of any ingestion exposure.

4.6 Note to Physicians: If you determine that a medical emergency exists and the specific chemical identity is necessary for emergency or first-aid treatment we will immediately disclose the specific chemical identity. Call CHEMTREC 800-424-9300 or +1-703-527-3887. We will require a written statement of need and confidentiality agreement, in accordance with OSHA's Trade Secret Regulations as soon as circumstances permit. In non-emergency situations, we will upon written request disclose a specific chemical identity

Section 5 - Fire-Fighting Measures

5.1 General Fire Hazards

Use water to cool containers exposed to fire

5.2 Hazardous Combustion Products

Avoid fumes of burning product.

5.3 Extinguishing Media

Carbon dioxide, dry chemical, foam

5.4 Fire Fighting Equipment/Instructions

Fire fighters should wear full-face, self-contained breathing apparatus and impervious protective clothing. Fire fighters should avoid inhaling any combustion products.

Section 6 - Accidental Release Measures

6.1 Spill /Leak Procedures: Ventilate area highly flammable. Spillages of liquid product will create a fire hazard and may form an explosive atmosphere. Keep all sources of ignition away from the spill.

6.2 Spills: Avoid direct contact with material. Stop leak if without risk. Move containers from spill area. Prevent entry into sewers or waterways. Contain and collect spillage with non-combustible, absorbent material such as sand, earth, vermiculite or diatomaceous earth and place in a container for disposal.

Section 7 - Handling and Storage

7.1 Handling Precautions: Wash hands and exposed skin thoroughly after handling. Remove contaminated clothing and wash before reuse. Use with adequate ventilation. Avoid ingestion and contact with eyes, skin or clothing. Keep container tightly closed. Avoid inhalation.

7.2 Storage Requirements: Store in a tightly closed container in a cool, dry and well-ventilated area.

SEF 4 Cycle

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II – Europe
Conforms to Regulation (EC) No 1272/2008 and aligns to the United Nations Globally Harmonized System
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of the Work Health and Safety Act

Section 8 - Exposure Controls / Personal Protection

8.1

Chemical Names	ACGIH- TLV	OSHA - PEL
Blend of Aliphatic and Aromatic Hydrocarbons C-2 to C-20	20 - 300 ppm TWA	20- 300 ppm TWA

8.2.

ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value.

OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits.

NOTE: TWA Means "TWA is the employee's average airborne exposure in any 8-hour work shift of a 40-hour work week which shall not be exceeded.

8.3 Ventilation: Provide general or local exhaust ventilation systems to maintain airborne concentrations below TLV/PELs Local exhaust ventilation are preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

8.4 Contaminated Equipment: Separate contaminated work clothes from street clothes and launder before reuse. Remove this material from your shoes and clean personal protective equipment.

8.5 Personal protective equipment

8.5.1 Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

8.5.2 Hand protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique to avoid skin contact with this product. Dispose of contaminated gloves after use. Select gloves tested to the ANSI/ISEA 105-2011 or European EN374 Standard.

Full contact: Nitrile rubber

Splash contact: Nitrile rubber

8.5.3 Eye protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

8.5.4 Skin and body protection

Impervious clothing, Flame retardant antistatic protective clothing, the type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

8.6 Protective Clothing Pictograms



Splash Goggles



Gloves



Protective Apron



Vapor Respirator

SEF 4 Cycle

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II – Europe
Conforms to Regulation (EC) No 1272/2008 and aligns to the United Nations Globally Harmonized System
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of the Work Health and Safety Act

Section 9 - Physical and Chemical Properties

9.1

Physical State: Liquid

Appearance: Clear

Odor: Aromatic Hydrocarbon Odor

Vapor Pressure: Not Available

Vapor Density (Air=1): 3.9

Specific Gravity (H₂O=1.): 0.70

Relative Density: Not Available

Odor Threshold: Not Available

Flammability (solid, gas): Not applicable.

Evaporation rate: Not Available

Partition coefficient octanol/water: Not Available

Water Solubility: Insoluble

Melting point/freezing point: Not Available

Flash Point: -40°F (-40°C) close cup

Boiling Point / Range: 97.7 – 402.1°F
(36.5 – 205.6°C)

Lower Explosive Limits (vol % in air): 1%

Upper Explosive Limits (vol % in air): 8%

Viscosity: Not Available

Auto ignition Temperature: Not Available

Decomposition temperature: Not Available

pH: None

Section 10 - Stability and Reactivity

10.1 Stability: Stable under ordinary conditions of use and storage

10.2 Polymerization: Hazardous polymerization has not been reported

10.3 Chemical Incompatibilities: Strong oxidizing agents

10.4 Hazardous Decomposition Products: Combustion produces carbon monoxide and carbon dioxide

10.5 Conditions to Avoid: Avoid heat, sparks open flames and other ignition sources

Section 11- Toxicological Information

11.1 Product Name	Results	Species	Dose	Exposure
Blend of Aliphatic and Aromatic Hydrocarbons C-2 to C-20	Oral LD50	Rat	>300mg/kg <2000 mg/kg	Non Listed

11.2 Route of Entry: Inhalation, Ingestion, Absorption, Skin and/or Eye Contact

11.3 Aspiration Hazard: May be fatal if swallowed and enters airways

11.4 Acute Toxicity: OECD Guideline 401 Tests results found in the European Chemical Agency Data Base shows that components of this product to cause Oral Toxicity.

11.5 Mutagenicity: OECD Guideline 476 Tests results found in the European Chemical Agency Data Base show components of this product to cause genetic defects.

11.6 Skin Corrosion/Irritation: Causes skin irritation. Repeated exposure may cause skin dryness or cracking.

11.7 Serious Eye Damage/Irritation: Causes serious eye irritation.

11.8 Reproductive toxicity: OECD Guideline 421 Tests results found in the European Chemical Agency Data Base show components of this product to cause damage to fertility or the unborn child.

SEF 4 Cycle

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II – Europe
Conforms to Regulation (EC) No 1272/2008 and aligns to the United Nations Globally Harmonized System
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of the Work Health and Safety Act

11.9 Specific Target Organ Toxicity (Single Exposure): May cause drowsiness and dizziness.

11.10 Specific Target Organ Toxicity (Repeated Exposure): Contains material which may cause damage to the following organs: kidneys, lungs, liver, upper respiratory tract, skin, eyes, central nervous system (CNS).

11.11 Signs and Symptoms: Contains material which may cause damage to the following organs: Eyes, Kidney, Liver, Heart, Central nervous system. Effects due to ingestion may include: Headache, Dizziness, Drowsiness, Metabolic Acidosis, Coma, Seizures. Symptoms may be delayed.

11.12 Carcinogenicity: OECD Guideline 453 Tests results found in the European Chemical Agency Data Base shows that components of this product to cause cancer.

Chemical Name	IARC	ACGIH	NTP	OSHA
Blend of Aliphatic and Aromatic Hydrocarbons C-2 to C-20	Not classifiable as a human carcinogen	Not classifiable as a human carcinogen	Not listed	Not listed

Section 12 - Ecological Information

12.1

Product Name	Results	Species	Exposure
Blend of Aliphatic and Aromatic Hydrocarbons C-2 to C-20	Expected to be toxic to aquatic organisms. May cause long-term adverse effects in the environment		

Toxicity: OECD Guideline 204 Test results found in the European Chemical Agency Data Base show components of this product to cause long-term toxicity to fish.

12.2 Mobility: Floats on water

12.3 Persistence/degradability: No date available on this product

12.4 Bioaccumulation: No date available on this product

12.5 Other adverse effects: No date available on this product

Section 13 - Disposal Considerations

13.1 Disposal: DO NOT REUSE EMPTY CONTAINER! Container should be completely emptied prior to discard. Container with residues should be considered to be hazardous wastes. Contact a licensed contractor for detailed recommendations. Follow applicable federal, state, and local regulations.

SEF 4 Cycle

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II – Europe
Conforms to Regulation (EC) No 1272/2008 and aligns to the United Nations Globally Harmonized System
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of the Work Health and Safety Act

Section 14 - Transport Information

14.1 DOT Transport Information



ID No.: UN 1203

Shipping Name: Gasoline

Hazard Class: 3

Packing Group: II

Label: Flammable

Placard: Flammable

Marking: MARINE POLLUTANT Alkylate full Range when shipping ground greater than 119 gallons single container or any quantity by water

14.2 TDG Canadian Transport Information



ID No.: UN 1203

Shipping Name: Gasoline

Hazard Class: 3

Packing Group: II

Label: Flammable

Placard: Flammable

Marking: MARINE POLLUTANT Alkylate full Range Not regulated if shipped by road or rail

14.3 IMDG Transport Information



ID No.: UN 1203

Shipping Name: GASOLINE

Hazard Class: 3

Packing Group: II

Flash Point: (-40°C c.c.)

EmS Number: F-E, S-E

Label: Flammable

Placard: Flammable

Marking: Marine Pollutant Alkylate full Range

SEF 4 Cycle

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

Conforms to The United Nations Regulation Globally Harmonized System

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II – Europe

Conforms to Regulation (EC) No 1272/2008 and aligns to the United Nations Globally Harmonized System

Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of the Work Health and Safety Act

14.4 ADR/RID Transport Information



ID No.: UN 1203

Shipping Name: Gasoline

Hazard Class: 3

Packing Group: II

Label: Flammable

Placard: Flammable

Marking: Marine Alkylate full Range

Classification Code: F1

14.5 Australian Dangerous Goods Transport Information



ID No.: ID No.: UN1203

Shipping Name: Gasoline

Hazard Class: 3


Packing Group: II

Label: Flammable

Placard: Flammable

Marking: Marine Pollutant Alkylate full Range

Marking: MARINE POLLUTANT The marine pollutant mark is only applicable for packages containing more than 5 liter for liquids.



Use marking when shipping as a consumer commodity ground in the US

14.6 DOT Transport Limited Quantity/Consumer Commodity


Inner packaging not over

1.0L (0.3 gallons) net capacity each.

Outer Package not over 30kg (66lbs) each

SEF 4 Cycle


Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II – Europe
Conforms to Regulation (EC) No 1272/2008 and aligns to the United Nations Globally Harmonized System
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of the Work Health and Safety Act



Use marking when shipping as a limited quantity ground in the Canada

14.7 TDG Canada Transport Limited Quantity

Inner packaging not over
1.0L (0.3 gallons) net capacity each.
Outer Package not over 30kg (66lbs) each



Use marking when shipping as a limited quantity by vessel.

14.8 IMDG Transport Limited Quantity

Inner packaging not over
1.0L (0.3 gallons) net capacity each.
Outer Package not over 30kg (66lbs) each

ID No.: UN 1203

Shipping Name: GASOLINE LTD.QTY.

Hazard Class: 3

Packing Group: II

Flash Point: (-35.5° C c.c.)

EmS Number: F-E, S-E

NOTE: Because the MARINE POLLUTANT Naphtha (petroleum), full-range alkylate in the inner packaging of the combination packaging is a net quantity of 5 L or less. The MARINE POLLUTANT marking is not required

Section 15 - Regulatory Information

15.1 US Regulations

US. Toxic Substances Control Act: All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30

CERCLA Hazardous Substances and corresponding RQs: Phenylmethane 1000

SARA Community Right-to-Know Program: Phenylmethane

Clean Water Act: Phenylmethane

Clean Air Act: None

OSHA: All ingredients are regulated by 1910.1200

State Regulations

California prop. 65: Phenylmethane Reproductive

SEF 4 Cycle

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II – Europe
Conforms to Regulation (EC) No 1272/2008 and aligns to the United Nations Globally Harmonized System
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of the Work Health and Safety Act

Chemicals on the following State Right to Know Lists:

Massachusetts: All components of this product are on the Massachusetts Inventory or are exempt from Inventory requirements.

New Jersey All components of this product are on the New Jersey inventory or are exempt from Inventory requirements.

Pennsylvania: All components of this product are on the Pennsylvania Inventory or are exempt from Inventory requirements.

15.2 Canadian Regulation:

The following substances are specified on the public Portion of the Domestic Substances List (DSL): All substances contained in this product are listed on the Canadian Domestic Substances List (DSL) or are not required to be listed.

15.3 Europe Regulations

Classification and labeling have been determined according to EU Directives 67/548/EEC and 1999/45/EC (Including amendments) and take into account the intended product use.

Europe inventory:

All substances contained in this product are listed on the EU directives or are not required to be listed.

International Regulations:

Australian Inventory of Chemical Substance: All components of this product are on the Inventory or are exempt from Inventory requirements

National Existing Chemical Inventory in Taiwan: All components of this product are on Inventory or are exempt from Inventory requirements

Philippine Inventory of Chemicals and Chemical Substances All components of this product are on the Inventory or are exempt from Inventory requirements

China Existing Chemical Inventory: All components of this product are on the Inventory or are exempt from Inventory requirements

SEF 4 Cycle

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II – Europe
Conforms to Regulation (EC) No 1272/2008 and aligns to the United Nations Globally Harmonized System
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of the Work Health and Safety Act

Section 16 - Other Information

16.1 Disclaimer: The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER NO responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information provided above is furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use.

16.2 References: CHEMpendium data base of Canadian Centre for Occupational Health and Safety (CCOHS), JJ Keller on Line, European Chemical Agency Data Base and MSDS and SDS of chemicals in this mixture.

16.3 CHEMTREC In country emergency dial numbers:

Australia (Sydney) + (61)-290372994
China 4001-204937 must be call within China
Germany 0800-181-7059 must be call within Germany
Germany (Frankfurt) + (49)-6964350840
Russia 8-800-100-6346 Must be call within Russia

16.4 SDS Preparation Date 11/19/2015

SDS Previous issue Date: None

Prepared by SJC Compliance Education, Inc
16516 El Camino Real Suite 417
Houston, TX 77062

The logo for Small Engine Fuels features a large, stylized 'SEF' in blue and red. To the right of the 'SEF' is a red circle containing a white registered trademark symbol (®). Below the 'SEF' and the circle, the words 'SMALL ENGINE FUELS' are written in a bold, italicized, blue font with a white outline.

**SMALL
ENGINE
FUELS**