

# Polyblend®Plus Sanded Grout

## 1 Product Name

Polyblend®Plus Sanded Grout

## 2 Manufacturer

Custom Building Products  
 Technical Services  
 10400 Pioneer Boulevard, Unit 3  
 Santa Fe Springs, CA 90670  
 Customer Support: 800-272-8786  
 Technical Services: 800-282-8786  
 Fax: 800-200-7765  
 Email: [contactus@cbpmail.net](mailto:contactus@cbpmail.net)  
[custombuildingproducts.com](http://custombuildingproducts.com)

## 3 Product Description

Polyblend Plus has all of the great features of original Polyblend, plus some new value-added enhancements to improve performance, finished color, and color consistency. It is now an ANSI A118.7 polymer-modified, cement-based sanded grout that produces hard, dense joints that resist shrinking, cracking, and wear. Formulated for durability, Polyblend Plus Sanded Grout accommodates 1/8"-1/2" (3.1-12.7 mm) joints for interior or exterior installations, including floors, countertops, walls, ceilings, showers, fountains, and pools.

### Key Features

- Brighter, more vivid finished color
- Enhanced color consistency
- Better resistance to efflorescence
- Meets ANSI 118.7 High Performance Grout Standard without additive
- Easy to use - Just mix with water
- Polymer fortified for hard, durable, professional results

### Uses

- Use to fill joint widths 1/8" to 1/2" (3.1 to 12.7 mm)
- May be used for both floor and wall installations
- Interior and exterior applications
- Residential and commercial applications
- Countertops, tub surrounds, showers and high traffic areas
- Submerged conditions (swimming pools, spas, water features and fountains)

### Suitable Tile Types

- Vitreous, semi-vitreous or non-vitreous tile: ceramic, mosaic, quarry, cement body tiles
- Impervious porcelain and glass tile
- Brick and stone veneer
- Cement-based precast terrazzo
- Natural stone tile

### Composition of Product

Polyblend® Plus Sanded Grout is a dry, Portland cement based grout with silica sand, inorganic aggregates and chemicals.

### Benefits of Product in the Installation

- Hard, durable grout joints
- Resists shrinking, cracking, powdering and wear



### Limitations to the Product

- Should not be installed when ambient or surface temperature is lower than 50°F (10°C) or higher than 100°F (38°C).
- Some ceramic, glass, metal, marble or stone tiles can be scratched or damaged by the silica aggregate filler. Perform a test on a small area prior to use. Polyblend® Plus NonSanded Grout may be appropriate for joints up to 1/8" or for tile not suited for sanded grout.
- Tile or stone with high absorption, surfaces that are porous or rough, textured surfaces and some types of porcelain tile may require sealing prior to grouting to prevent possible staining. Use Aqua Mix® Grout Release or TileLab® SurfaceGard® Sealer to prevent staining when required.
- Color variation can occur due to tile type, tile porosity, jobsite and climatic conditions, application and cleaning techniques. Variation can be minimized by following directions and using as little water as possible for cleanup.
- A CUSTOM grout color card is truest representation of the grout formula. Refer to the latest CUSTOM grout color card to choose a color. Perform a mockup to determine suitability. Various lighting types and conditions will affect the final grout and tile colors' appearance.
- Not for use in either industrial applications or in areas subjected to harsh or continuous chemicals, high heat or high-pressure cleaning. For heavy industrial tile installations, use CEG-IG 100% Solids Epoxy Grout.
- Chemicals in salt-based pool filtration systems can cause a reaction with blue, green and red grouts. Contact Technical Services for recommendations.
- Not for use in movement joints or changes of plane in the tile installation. In these areas, use an appropriate caulk or sealant such as Commercial 100% Silicone Sealant or Ceramic Tile Caulk.

### Packaging

Available in 2 sizes:

- 7 lb (3.17 kg) box
- 25 lb (11.34 kg) bag

25 lb bag and 7 lb box are available in 40 standard colors; color matching is available.



# Polyblend®Plus Sanded Grout

## 4 Technical Data

### Applicable Standards

American National Standards Institute (ANSI) ANSI A108.10, A118.6 & A118.7 of the American National Standards for the Installation of Ceramic Tile ASTM International (ASTM)

- ASTM C109 Standard Test Method for Compressive Strength of Hydraulic Cement Mortars (Using 2-in. or (50-mm) Cube Specimens)
- ASTM C531 Standard Test Method for Linear Shrinkage
- ASTM C580 Standard Test method for Flexural Strength
- ISO 13007-3

### Approvals

Polyblend® Plus Sanded Grout exceeds ANSI A118.6 & A118.7 standards.

### Technical Chart

Property	Test Method	Requirement	Typical Results
Pot Life	ANSI A118.7		1 - 2 Hours
28 Day Shrinkage	Section 3.3	< 0.20%	< 0.20%
28 Day Water Absorption	Section 3.4	< 5%	< 5%
1 Day Compressive Strength	Section 3.5	> 500 psi (35.2 kg/cm sq)	> 500 psi (35.2 kg/cm sq)
28 Day Compressive Strength	Section 3.5	> 3000 psi (210.9 kg/cm sq) > 3000 psi	> 3000 psi (210.9 kg/cm sq)
28 Day Tensile Strength	Section 3.6	> 500psi (35.2 kg/cm sq)	> 500psi (35.2 kg/cm sq)
28 Day Flexural Strength	Section 3.7	> 1000psi (70.3 kg/cm sq)	> 1000psi (70.3 kg/cm sq)

### Environmental Consideration

Custom® Building Products is committed to environmental responsibility in both products produced and in manufacturing practices. Use of this product can contribute towards LEED® v3 certification:

- Up to 2 points towards MR Credit 5, Regional Materials
- Up to 1 point towards IEQ Credit 4.1, Low-Emitting Materials – Adhesives & Sealants

## 5 Instructions

### General Surface Prep

**USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product.**

Tile or stone must be firmly bonded to a sound substrate, and setting material must be cured a minimum 24-48 hours before cement grout is applied, unless rapid-setting mortars are used. See the corresponding data sheet for the bonding mortars used in your application. Remove spacers and ensure that the grout joints are uniform in depth and width and free of loose debris, contaminants and excess mortar. Use [TileLab® SurfaceGard® Sealer](#) or [Aqua Mix® Grout Release](#) to seal tile or stone subject to staining or when using a grout that contrasts with the color of the tile.

### Mixing Ratios

- Mix 2 qt (1.89 L) clean water to 25 lb (11.34 kg) grout.
- Mix 1 pt (.473 L) clean water to 7 lb (3.17 kg) grout.

### Mixing Procedures

When installing more than 1 container of grout at a time, blend dry powders prior to mixing with water. Mix with a trowel or low speed mixer (less than 300 rpm) to achieve a smooth, lump-free consistency (approximately 3 minutes). Let the mixture stand (slake) for 5 minutes, and then remix and use. Periodically remix to keep the mixture workable, but do not add water, which can weaken the grout, cause color variation and possible cause shrinkage, cracks and pinholes. Discard grout when it becomes too stiff to work.

### Application of Product

Installation must conform to ANSI A108.10. Lightly dampen absorptive, highly porous tile with clean, cool water, but leave no standing water in the joints. Holding a rubber grout float at a 45° angle, completely fill the joints. Holding the edge of the float at a 90° angle, remove excess grout. At 70° F, do not spread more grout than can be cleaned within 30 minutes of the grout firming and use as little water as possible for grout clean-up (higher temperatures may shorten this time frame). Using a damp, small pore grout sponge in a circular motion, smooth and level joints and remove excess grout. Change the water and rinse the sponge frequently. Haze can be removed after 3 hours with cheesecloth or wrung-out sponge. If haze persists, the installation can be washed after three days with [Aqua Mix NanoScrub](#) or after ten days with [Aqua Mix® Sulfamic Acid Crystals](#), [TileLab® Sulfamic Acid Cleaner](#) or [Aqua Mix® Cement Grout Haze Remover](#). Perform a test in an inconspicuous area prior to complete application. Movement joints are required for perimeters and other changes of plane in all installations. See TCNA Detail EJ171 for recommendations.

### Curing of Product

Curing time is affected by ambient and surface temperatures and humidity. For exterior applications, it is recommended that the installation is misted periodically with clean, cool water for 3 days.

Exterior applications must be protected from rain, snow and other wet conditions for at least 7 days with temperature above 50° F (10° C). If inclement weather is expected, protect the work area with tenting at least 1 foot (30 cm) above the finished surface to allow air flow.

Enclose and protect installations and maintain >50° F (10° C) temperatures for at least 72 hours for proper cure.

### Sealing of Grout



# Polyblend®Plus Sanded Grout

---

Use a pH-neutral, water-based, penetrating sealer such as [AquaMix Sealer's Choice Gold](#) or [TileLab Surface Guard](#).

## **Cleaning of equipment**

Clean tools and hands with water before the material dries.

## **Health Precautions**

This product contains Portland cement. Avoid eye contact or prolonged contact with skin. Wash thoroughly after handling. If eye contact occurs, flush with water for 15 minutes and consult a physician. Use with adequate ventilation; do not breathe dust and wear a NIOSH approved respirator. If ingested, do not induce vomiting; call a physician immediately.

## **Conformance to Building Codes**

Installation must comply with the requirements of all applicable local, state and federal code jurisdictions.

# Polyblend®Plus Sanded Grout

## 6 Availability & Cost

Location	Grout Color	Item Code	Size	Package	Item Code	Size	Package
USA	#09 NATURAL GRAY	PBPG097-4	7 lb (3.17 kg)	Box	PBPG0925	25 lb (11.34 kg)	Bag
USA	#10 ANTIQUE WHITE	PBPG107-4	7 lb (3.17 kg)	Box	PBPG1025	25 lb (11.34 kg)	Bag
USA	#11 SNOW WHITE	PBPG117-4	7 lb (3.17 kg)	Box	PBPG1125	25 lb (11.34 kg)	Bag
USA	#19 PEWTER	PBPG197-4	7 lb (3.17 kg)	Box	PBPG1925	25 lb (11.34 kg)	Bag
USA	#52 TOBACCO BROWN	PBPG527-4	7 lb (3.17 kg)	Box	PBPG5225	25 lb (11.34 kg)	Bag
USA	#59 SADDLE BROWN	PBPG597-4	7 lb (3.17 kg)	Box	PBPG5925	25 lb (11.34 kg)	Bag
USA	#60 CHARCOAL	PBPG607-4	7 lb (3.17 kg)	Box	PBPG6025	25 lb (11.34 kg)	Bag
USA	#95 SABLE BROWN	PBPG957-4	7 lb (3.17 kg)	Box	PBPG9525	25 lb (11.34 kg)	Bag
USA	#105 EARTH	PBPG1057-4	7 lb (3.17 kg)	Box	PBPG10525	25 lb (11.34 kg)	Bag
USA	#115 PLATINUM	PBPG1157-4	7 lb (3.17 kg)	Box	PBPG11525	25 lb (11.34 kg)	Bag
USA	#122 LINEN	PBPG1227-4	7 lb (3.17 kg)	Box	PBPG12225	25 lb (11.34 kg)	Bag
USA	#135 MUSHROOM	PBPG1357-4	7 lb (3.17 kg)	Box	PBPG13525	25 lb (11.34 kg)	Bag
USA	#145 LIGHT SMOKE	PBPG1457-4	7 lb (3.17 kg)	Box	PBPG14525	25 lb (11.34 kg)	Bag
USA	#165 DELOREAN GRAY	PBPG1657-4	7 lb (3.17 kg)	Box	PBPG16525	25 lb (11.34 kg)	Bag
USA	#172 URBAN PUTTY	PBPG1727-4	7 lb (3.17 kg)	Box	PBPG17225	25 lb (11.34 kg)	Bag
USA	#183 CHATEAU	PBPG1837-4	7 lb (3.17 kg)	Box	PBPG18325	25 lb (11.34 kg)	Bag
USA	#185 NEW TAUPE	PBPG1857-4	7 lb (3.17 kg)	Box	PBPG18525	25 lb (11.34 kg)	Bag
USA	#186 KHAKI	PBPG1867-4	7 lb (3.17 kg)	Box	PBPG18625	25 lb (11.34 kg)	Bag
USA	#333 ALABASTER	PBPG3337-4	7 lb (3.17 kg)	Box	PBPG33325	25 lb (11.34 kg)	Bag
USA	#335 WINTER GRAY	PBPG3357-4	7 lb (3.17 kg)	Box	PBPG33525	25 lb (11.34 kg)	Bag
USA	#370 DOVE GRAY	PBPG3707-4	7 lb (3.17 kg)	Box	PBPG37025	25 lb (11.34 kg)	Bag
USA	#380 HAYSTACK	PBPG3807-4	7 lb (3.17 kg)	Box	PBPG38025	25 lb (11.34 kg)	Bag
USA	#381 BRIGHT WHITE	PBPG3817-4	7 lb (3.17 kg)	Box	PBPG38125	25 lb (11.34 kg)	Bag
USA	#382 BONE	PBPG3827-4	7 lb (3.17 kg)	Box	PBPG38225	25 lb (11.34 kg)	Bag



# CUSTOM®

# Polyblend®Plus Sanded Grout

USA	#386 OYSTER GRAY	PBPG3867-4	7 lb (3.17 kg)	Box	PBPG38625	25 lb (11.34 kg)	Bag
USA	#540 TRUFFLE	PBPG5407-4	7 lb (3.17 kg)	Box	PBPG54025	25 lb (11.34 kg)	Bag
USA	#541 WALNUT	PBPG5417-4	7 lb (3.17 kg)	Box	PBPG54125	25 lb (11.34 kg)	Bag
USA	#542 GRAYSTONE	PBPG5427-4	7 lb (3.17 kg)	Box	PBPG54225	25 lb (11.34 kg)	Bag
USA	#543 DRIFTWOOD	PBPG5437-4	7 lb (3.17 kg)	Box	PBPG54325	25 lb (11.34 kg)	Bag
USA	#544 ROLLING FOG	PBPG5447-4	7 lb (3.17 kg)	Box	PBPG54425	25 lb (11.34 kg)	Bag
USA	#545 BLEACHED WOOD	PBPG5457-4	7 lb (3.17 kg)	Box	PBPG54525	25 lb (11.34 kg)	Bag
USA	#546 CAPE GRAY	PBPG5467-4	7 lb (3.17 kg)	Box	PBPG54625	25 lb (11.34 kg)	Bag
USA	#640 ARCTIC WHITE	PBPG6407-4	7 lb (3.17 kg)	Box	PBPG64025	25 lb (11.34 kg)	Bag
USA	#641 COOL WHITE	PBPG6417-4	7 lb (3.17 kg)	Box	PBPG64125	25 lb (11.34 kg)	Bag
USA	#642 ASH	PBPG6427-4	7 lb (3.17 kg)	Box	PBPG64225	25 lb (11.34 kg)	Bag
USA	#643 WARM GRAY	PBPG6437-4	7 lb (3.17 kg)	Box	PBPG64325	25 lb (11.34 kg)	Bag
USA	#644 SHADOW	PBPG6447-4	7 lb (3.17 kg)	Box	PBPG64425	25 lb (11.34 kg)	Bag
USA	# 645 STEEL BLUE	PBPG6457-4	7 lb (3.17 kg)	Box	PBPG64525	25 lb (11.34 kg)	Bag
USA	#646 COFFEE BEAN	PBPG6467-4	7 lb (3.17 kg)	Box	PBPG64625	25 lb (11.34 kg)	Bag
USA	#647 BROWN VELVET	PBPG6477-4	7 lb (3.17 kg)	Box	PBPG64725	25 lb (11.34 kg)	Bag
USA - Special Order	All 40 colors				PBGXX50	50 lb (22.68 kg)	Bag



# CUSTOM®

# Polyblend®Plus Sanded Grout

Location	Grout Color	Item Code	Size	Package	Item Code	Size	Package
Canada	#09 NATURAL GRAY	CPBPG097-4	7 lb (3.17 kg)	Box	CPBPG0925	25 lb (11.34 kg)	Bag
Canada	#10 ANTIQUE WHITE	CPBPG107-4	7 lb (3.17 kg)	Box	CPBPG1025	25 lb (11.34 kg)	Bag
Canada	#11 SNOW WHITE	CPBPG117-4	7 lb (3.17 kg)	Box	CPBPG1125	25 lb (11.34 kg)	Bag
Canada	#19 PEWTER	CPBPG197-4	7 lb (3.17 kg)	Box	CPBPG1925	25 lb (11.34 kg)	Bag
Canada	#52 TOBACCO BROWN	CPBPG527-4	7 lb (3.17 kg)	Box	CPBPG5225	25 lb (11.34 kg)	Bag
Canada	#59 SADDLE BROWN	CPBPG597-4	7 lb (3.17 kg)	Box	CPBPG5925	25 lb (11.34 kg)	Bag
Canada	#60 CHARCOAL	CPBPG607-4	7 lb (3.17 kg)	Box	CPBPG6025	25 lb (11.34 kg)	Bag
Canada	#95 SABLE BROWN	CPBPG957-4	7 lb (3.17 kg)	Box	CPBPG9525	25 lb (11.34 kg)	Bag
Canada	#105 EARTH	CPBPG1057-4	7 lb (3.17 kg)	Box	CPBPG10525	25 lb (11.34 kg)	Bag
Canada	#115 PLATINUM	CPBPG1157-4	7 lb (3.17 kg)	Box	CPBPG11525	25 lb (11.34 kg)	Bag
Canada	#122 LINEN	CPBPG1227-4	7 lb (3.17 kg)	Box	CPBPG12225	25 lb (11.34 kg)	Bag
Canada	#135 MUSHROOM	CPBPG1357-4	7 lb (3.17 kg)	Box	CPBPG13525	25 lb (11.34 kg)	Bag
Canada	#145 LIGHT SMOKE	CPBPG1457-4	7 lb (3.17 kg)	Box	CPBPG14525	25 lb (11.34 kg)	Bag
Canada	#165 DELOREAN GRAY	CPBPG1657-4	7 lb (3.17 kg)	Box	CPBPG16525	25 lb (11.34 kg)	Bag
Canada	#172 URBAN PUTTY	CPBPG1727-4	7 lb (3.17 kg)	Box	CPBPG17225	25 lb (11.34 kg)	Bag
Canada	#183 CHATEAU	CPBPG1837-4	7 lb (3.17 kg)	Box	CPBPG18325	25 lb (11.34 kg)	Bag
Canada	#185 NEW TAUPE	CPBPG1857-4	7 lb (3.17 kg)	Box	CPBPG18525	25 lb (11.34 kg)	Bag



# CUSTOM®

# Polyblend®Plus Sanded Grout

Canada	#186 KHAKI	CPBPG1867-4	7 lb (3.17 kg)	Box	CPBPG18625	25 lb (11.34 kg)	Bag
Canada	#333 ALABASTER	CPBPG3337-4	7 lb (3.17 kg)	Box	CPBPG33325	25 lb (11.34 kg)	Bag
Canada	#335 WINTER GRAY	CPBPG3357-4	7 lb (3.17 kg)	Box	CPBPG33525	25 lb (11.34 kg)	Bag
Canada	#370 DOVE GRAY	CPBPG3707-4	7 lb (3.17 kg)	Box	CPBPG37025	25 lb (11.34 kg)	Bag
Canada	#380 HAYSTACK	CPBPG3807-4	7 lb (3.17 kg)	Box	CPBPG38025	25 lb (11.34 kg)	Bag
Canada	#381 BRIGHT WHITE	CPBPG3817-4	7 lb (3.17 kg)	Box	CPBPG38125	25 lb (11.34 kg)	Bag
Canada	#382 BONE	CPBPG3827-4	7 lb (3.17 kg)	Box	CPBPG38225	25 lb (11.34 kg)	Bag
Canada	#386 OYSTER GRAY	CPBPG3867-4	7 lb (3.17 kg)	Box	CPBPG38625	25 lb (11.34 kg)	Bag
Canada	#540 TRUFFLE	CPBPG5407-4	7 lb (3.17 kg)	Box	CPBPG54025	25 lb (11.34 kg)	Bag
Canada	#541 WALNUT	CPBPG5417-4	7 lb (3.17 kg)	Box	CPBPG54125	25 lb (11.34 kg)	Bag
Canada	#542 GRAYSTONE	CPBPG5427-4	7 lb (3.17 kg)	Box	CPBPG54225	25 lb (11.34 kg)	Bag
Canada	#543 DRIFTWOOD	CPBPG5437-4	7 lb (3.17 kg)	Box	CPBPG54325	25 lb (11.34 kg)	Bag
Canada	#544 ROLLING FOG	CPBPG5447-4	7 lb (3.17 kg)	Box	CPBPG54425	25 lb (11.34 kg)	Bag
Canada	#545 BLEACHED WOOD	CPBPG5457-4	7 lb (3.17 kg)	Box	CPBPG54525	25 lb (11.34 kg)	Bag
Canada	#546 CAPE GRAY	CPBPG5467-4	7 lb (3.17 kg)	Box	CPBPG54625	25 lb (11.34 kg)	Bag
Canada	#640 ARCTIC WHITE	CPBPG6407-4	7 lb (3.17 kg)	Box	CPBPG64025	25 lb (11.34 kg)	Bag
Canada	#641 COOL WHITE	CPBPG6417-4	7 lb (3.17 kg)	Box	CPBPG64125	25 lb (11.34 kg)	Bag

Canada	#642 ASH	CPBPG6427-4	7 lb (3.17 kg)	Box	CPBPG64225	25 lb (11.34 kg)	Bag
Canada	#643 WARM GRAY	CPBPG6437-4	7 lb (3.17 kg)	Box	CPBPG64325	25 lb (11.34 kg)	Bag
Canada	#644 SHADOW	CPBPG6447-4	7 lb (3.17 kg)	Box	CPBPG64425	25 lb (11.34 kg)	Bag
Canada	# 645 STEEL BLUE	CPBPG6457-4	7 lb (3.17 kg)	Box	CPBPG64525	25 lb (11.34 kg)	Bag
Canada	#646 COFFEE BEAN	CPBPG6467-4	7 lb (3.17 kg)	Box	CPBPG64625	25 lb (11.34 kg)	Bag
Canada	#647 BROWN VELVET	CPBPG6477-4	7 lb (3.17 kg)	Box	CPBPG64725	25 lb (11.34 kg)	Bag

See our color card for truest color representation when selecting or specifying a grout color. Final installed shade may vary with the tile type, color and porosity as well as jobsite conditions and finishing techniques. For best results, perform a test on a small, inconspicuous area or create a sample board prior to installation.



# CUSTOM®

# Polyblend®Plus Sanded Grout

---

## 7 Product Warranty

Obtain the applicable **LIMITED PRODUCT WARRANTY** at [www.custombuildingproducts.com/product-warranty](http://www.custombuildingproducts.com/product-warranty) or send a written request to Custom Building Products, Inc., Five Concourse Parkway, Atlanta, GA 30328, USA. Manufactured under the authority of Custom Building Products, Inc. © 2017 Quikrete International, Inc.

## 8 Product Maintenance

Clean with a pH-neutral cleaner such as [Aqua Mix AquaKleen](#), [Aqua Mix Concentrated Tile & Stone Cleaner](#) or [TileLab Grout & Tile Cleaner](#).

## 9 Technical Services Information

For technical assistance, contact Custom® technical services at 800-272-8786 or visit [custombuildingproducts.com](http://custombuildingproducts.com).

## 10 Filing System

Additional product information is available from the manufacturer upon request.

---

### Related Products

Ceramic Tile Caulk

Commercial 100% Silicone Sealant

TileLab® SurfaceGard® Sealer

StainBlocker for Grout

Polyblend® Non-Sanded Grout



# Polyblend®Plus Sanded Grout

## Coverage

For 25 lb. bag of Polyblend in ft<sup>2</sup> (m<sup>2</sup>) per bag

Tile Size	Joint Width				
	1/8" (3 mm)	3/16" (4.8 mm)	1/4" (6.3 mm)	3/8" (9.5 mm)	1/2" (13 mm)
Width x Length x Thickness					
1" x 1" x 1/4" (2.5 x 2.5 x .64 cm)	54 ft <sup>2</sup> (5 m <sup>2</sup> )	40 ft <sup>2</sup> (3.7 m <sup>2</sup> )	33 ft <sup>2</sup> (3.1 m <sup>2</sup> )	27 ft <sup>2</sup> (2.5 m <sup>2</sup> )	24 ft <sup>2</sup> (2.2 m <sup>2</sup> )
2" x 2" x 1/4" (5 x 5 x .64 cm)	96 ft <sup>2</sup> (8.9 m <sup>2</sup> )	68 ft <sup>2</sup> (6.3 m <sup>2</sup> )	54 ft <sup>2</sup> (5.0 m <sup>2</sup> )	40 ft <sup>2</sup> (3.7 m <sup>2</sup> )	33 ft <sup>2</sup> (3.1 m <sup>2</sup> )
3" x 3" x 1/4" (7.6 x 7.6 x .64 cm)	138 ft <sup>2</sup> (12.9 m <sup>2</sup> )	96 ft <sup>2</sup> (8.9 m <sup>2</sup> )	74 ft <sup>2</sup> (7 m <sup>2</sup> )	54 ft <sup>2</sup> (5 m <sup>2</sup> )	43 ft <sup>2</sup> (4 m <sup>2</sup> )
4.25" x 4.25" x 1/4" (10.8 x 10.8 x .64 cm)	192 ft <sup>2</sup> (17.8 m <sup>2</sup> )	131 ft <sup>2</sup> (12.2 m <sup>2</sup> )	101 ft <sup>2</sup> (9.4 m <sup>2</sup> )	71 ft <sup>2</sup> (6.6 m <sup>2</sup> )	56 ft <sup>2</sup> (5.2 m <sup>2</sup> )
6" x 6" x 1/4" (15.2 x 15.2 x .64 cm)	266 ft <sup>2</sup> (24.7 m <sup>2</sup> )	181 ft <sup>2</sup> (16.8 m <sup>2</sup> )	139 ft <sup>2</sup> (12.9 m <sup>2</sup> )	96 ft <sup>2</sup> (8.9 m <sup>2</sup> )	75 ft <sup>2</sup> (7.0 m <sup>2</sup> )
8" x 8" x 3/8" (20.3 x 20.3 x 1 cm)	234 ft <sup>2</sup> (21.7 m <sup>2</sup> )	158 ft <sup>2</sup> (14.7 m <sup>2</sup> )	121 ft <sup>2</sup> (11.2 m <sup>2</sup> )	83 ft <sup>2</sup> (7.7 m <sup>2</sup> )	64 ft <sup>2</sup> (6 m <sup>2</sup> )
12" x 12" x 3/8" (30.5 x 30.5 x 1 cm)	348 ft <sup>2</sup> (32.3 m <sup>2</sup> )	234 ft <sup>2</sup> (21.7 m <sup>2</sup> )	177 ft <sup>2</sup> (16.5 m <sup>2</sup> )	121 ft <sup>2</sup> (11.2 m <sup>2</sup> )	92 ft <sup>2</sup> (8.6 m <sup>2</sup> )
16" x 16" x 3/8" (40.6 x 40.6 x 1 cm)	462 ft <sup>2</sup> (42.8 m <sup>2</sup> )	310 ft <sup>2</sup> (28.8 m <sup>2</sup> )	234 ft <sup>2</sup> (21.7 m <sup>2</sup> )	158 ft <sup>2</sup> (14.7 m <sup>2</sup> )	121 ft <sup>2</sup> (11.2 m <sup>2</sup> )
18" x 18" x 3/8" (45.7 x 45.7 x 1 cm)	518 ft <sup>2</sup> (48.1 m <sup>2</sup> )	348 ft <sup>2</sup> (32.3 m <sup>2</sup> )	262 ft <sup>2</sup> (24.4 m <sup>2</sup> )	177 ft <sup>2</sup> (16.5 m <sup>2</sup> )	135 ft <sup>2</sup> (12.5 m <sup>2</sup> )
20" x 20" x 3/8" (50.8 x 50.8 x 1 cm)	574 ft <sup>2</sup> (53.4 m <sup>2</sup> )	385 ft <sup>2</sup> (35.8 m <sup>2</sup> )	291 ft <sup>2</sup> (27 m <sup>2</sup> )	196 ft <sup>2</sup> (18.2 m <sup>2</sup> )	149 ft <sup>2</sup> (13.8 m <sup>2</sup> )
24" x 24" x 3/8" (61 x 61 x 1 cm)	688 ft <sup>2</sup> (63.9 m <sup>2</sup> )	461 ft <sup>2</sup> (42.8 m <sup>2</sup> )	348 ft <sup>2</sup> (32.3 m <sup>2</sup> )	234 ft <sup>2</sup> (21.7 m <sup>2</sup> )	177 ft <sup>2</sup> (16.5 m <sup>2</sup> )
6" x 24" x 3/8" (15.2 x 61 x 1 cm)	279 ft <sup>2</sup> (26 m <sup>2</sup> )	189 ft <sup>2</sup> (17.5 m <sup>2</sup> )	143 ft <sup>2</sup> (13.3 m <sup>2</sup> )	98 ft <sup>2</sup> (9.1 m <sup>2</sup> )	75 ft <sup>2</sup> (7 m <sup>2</sup> )
12" x 24" x 3/8" (30.5 x 61 x 1 cm)	461 ft <sup>2</sup> (42.8 m <sup>2</sup> )	310 ft <sup>2</sup> (28.8 m <sup>2</sup> )	234 ft <sup>2</sup> (21.7 m <sup>2</sup> )	158 ft <sup>2</sup> (14.7 m <sup>2</sup> )	121 ft <sup>2</sup> (11.2 m <sup>2</sup> )
6" x 36" x 3/8" (15.2 x 91.4 x 1 cm)	299 ft <sup>2</sup> (27.8 m <sup>2</sup> )	202 ft <sup>2</sup> (18.7 m <sup>2</sup> )	153 ft <sup>2</sup> (14.2 m <sup>2</sup> )	104 ft <sup>2</sup> (9.7 m <sup>2</sup> )	80 ft <sup>2</sup> (7.4 m <sup>2</sup> )
9 x 36" x 3/8" (22.9 x 91.4 x 1 cm)	416 ft <sup>2</sup> (38.6 m <sup>2</sup> )	279 ft <sup>2</sup> (26 m <sup>2</sup> )	211 ft <sup>2</sup> (19.6 m <sup>2</sup> )	143 ft <sup>2</sup> (13.3 m <sup>2</sup> )	109 ft <sup>2</sup> (10.2 m <sup>2</sup> )
12" x 48" x 3/8" (30.5 x 122 x 1 cm)	552 ft <sup>2</sup> (51.3 m <sup>2</sup> )	370 ft <sup>2</sup> (34.4 m <sup>2</sup> )	279 ft <sup>2</sup> (26 m <sup>2</sup> )	189 ft <sup>2</sup> (17.5 m <sup>2</sup> )	143 ft <sup>2</sup> (13.3 m <sup>2</sup> )

For 7 lb bag of Polyblend (sq ft/sq m per bag)

Tile Size	Joint Width				
	1/8" (3 mm)	3/16" (4.8 mm)	1/4" (6.3 mm)	3/8" (9.5 mm)	1/2" (13 mm)
Width x Length x Thickness					
1" x 1" x 1/4" (2.5 x 2.5 x .64 cm)	15 ft <sup>2</sup> (1.4 m <sup>2</sup> )	11 ft <sup>2</sup> (1 m <sup>2</sup> )	9 ft <sup>2</sup> (.9 m <sup>2</sup> )	8 ft <sup>2</sup> (.7 m <sup>2</sup> )	7 ft <sup>2</sup> (.6 m <sup>2</sup> )
2" x 2" x 1/4" (5 x 5 x .64 cm)	27 ft <sup>2</sup> (2.5 m <sup>2</sup> )	19 ft <sup>2</sup> (1.8 m <sup>2</sup> )	15 ft <sup>2</sup> (1.4 m <sup>2</sup> )	11 ft <sup>2</sup> (1 m <sup>2</sup> )	9 ft <sup>2</sup> (.9 m <sup>2</sup> )
3" x 3" x 1/4" (7.6 x 7.6 x .64 cm)	39 ft <sup>2</sup> (3.6 m <sup>2</sup> )	27 ft <sup>2</sup> (2.5 m <sup>2</sup> )	21 ft <sup>2</sup> (1.9 m <sup>2</sup> )	15 ft <sup>2</sup> (1.4 m <sup>2</sup> )	12 ft <sup>2</sup> (1.1 m <sup>2</sup> )
4.25" x 4.25" x 1/4" (10.8 x 10.8 x .64 cm)	54 ft <sup>2</sup> (5 m <sup>2</sup> )	37 ft <sup>2</sup> (3.4 m <sup>2</sup> )	28 ft <sup>2</sup> (2.6 m <sup>2</sup> )	20 ft <sup>2</sup> (1.9 m <sup>2</sup> )	16 ft <sup>2</sup> (1.5 m <sup>2</sup> )
6" x 6" x 1/4" (15.2 x 15.2 x .64 cm)	74 ft <sup>2</sup> (6.9 m <sup>2</sup> )	51 ft <sup>2</sup> (4.7 m <sup>2</sup> )	39 ft <sup>2</sup> (3.6 m <sup>2</sup> )	27 ft <sup>2</sup> (2.5 m <sup>2</sup> )	21 ft <sup>2</sup> (1.9 m <sup>2</sup> )
8" x 8" x 3/8" (20.3 x 20.3 x 1 cm)	66 ft <sup>2</sup> (6.1 m <sup>2</sup> )	44 ft <sup>2</sup> (4.1 m <sup>2</sup> )	34 ft <sup>2</sup> (3.1 m <sup>2</sup> )	23 ft <sup>2</sup> (2.2 m <sup>2</sup> )	18 ft <sup>2</sup> (1.7 m <sup>2</sup> )
12" x 12" x 3/8" (30.5 x 30.5 x 1 cm)	97 ft <sup>2</sup> (9 m <sup>2</sup> )	66 ft <sup>2</sup> (6.1 m <sup>2</sup> )	50 ft <sup>2</sup> (4.6 m <sup>2</sup> )	34 ft <sup>2</sup> (3.1 m <sup>2</sup> )	26 ft <sup>2</sup> (2.4 m <sup>2</sup> )
16" x 16" x 3/8" (40.6 x 40.6 x 1 cm)	129 ft <sup>2</sup> (12 m <sup>2</sup> )	87 ft <sup>2</sup> (8.1 m <sup>2</sup> )	66 ft <sup>2</sup> (6.1 m <sup>2</sup> )	44 ft <sup>2</sup> (4.1 m <sup>2</sup> )	34 ft <sup>2</sup> (3.1 m <sup>2</sup> )
18" x 18" x 3/8" (45.7 x 45.7 x 1 cm)	145 ft <sup>2</sup> (13.5 m <sup>2</sup> )	97 ft <sup>2</sup> (9 m <sup>2</sup> )	73 ft <sup>2</sup> (6.8 m <sup>2</sup> )	50 ft <sup>2</sup> (4.6 m <sup>2</sup> )	38 ft <sup>2</sup> (3.5 m <sup>2</sup> )
20" x 20" x 3/8" (50.8 x 50.8 x 1 cm)	161 ft <sup>2</sup> (14.9 m <sup>2</sup> )	108 ft <sup>2</sup> (10 m <sup>2</sup> )	81 ft <sup>2</sup> (7.6 m <sup>2</sup> )	55 ft <sup>2</sup> (5.1 m <sup>2</sup> )	42 ft <sup>2</sup> (3.9 m <sup>2</sup> )
24" x 24" x 3/8" (61 x 61 x 1 cm)	193 ft <sup>2</sup> (17.9 m <sup>2</sup> )	129 ft <sup>2</sup> (12 m <sup>2</sup> )	97 ft <sup>2</sup> (9 m <sup>2</sup> )	66 ft <sup>2</sup> (6.1 m <sup>2</sup> )	50 ft <sup>2</sup> (4.6 m <sup>2</sup> )
6" x 24" x 3/8" (15.2 x 61 x 1 cm)	78 ft <sup>2</sup> (7.3 m <sup>2</sup> )	53 ft <sup>2</sup> (4.9 m <sup>2</sup> )	40 ft <sup>2</sup> (3.7 m <sup>2</sup> )	27 ft <sup>2</sup> (2.5 m <sup>2</sup> )	21 ft <sup>2</sup> (2.0 m <sup>2</sup> )
12" x 24" x 3/8" (30.5 x 61 x 1 cm)	129 ft <sup>2</sup> (12 m <sup>2</sup> )	87 ft <sup>2</sup> (8.1 m <sup>2</sup> )	66 ft <sup>2</sup> (6.1 m <sup>2</sup> )	44 ft <sup>2</sup> (4.1 m <sup>2</sup> )	34 ft <sup>2</sup> (3.1 m <sup>2</sup> )
6" x 36" x 3/8" (15.2 x 91.4 x 1 cm)	84 ft <sup>2</sup> (7.8 m <sup>2</sup> )	56 ft <sup>2</sup> (5.2 m <sup>2</sup> )	43 ft <sup>2</sup> (4 m <sup>2</sup> )	29 ft <sup>2</sup> (2.7 m <sup>2</sup> )	22 ft <sup>2</sup> (2.1 m <sup>2</sup> )
9 x 36" x 3/8" (22.9 x 91.4 x 1 cm)	116 ft <sup>2</sup> (10.8 m <sup>2</sup> )	78 ft <sup>2</sup> (7.3 m <sup>2</sup> )	59 ft <sup>2</sup> (5.5 m <sup>2</sup> )	40 ft <sup>2</sup> (3.7 m <sup>2</sup> )	31 ft <sup>2</sup> (2.8 m <sup>2</sup> )
12" x 48" x 3/8" (30.5 x 122 x 1 cm)	155 ft <sup>2</sup> (14.4 m <sup>2</sup> )	104 ft <sup>2</sup> (9.6 m <sup>2</sup> )	78 ft <sup>2</sup> (7.3 m <sup>2</sup> )	53 ft <sup>2</sup> (4.9 m <sup>2</sup> )	40 ft <sup>2</sup> (3.7 m <sup>2</sup> )

Chart for estimating purposes. Coverage may vary based on installation practices and jobsite conditions. For more tile and joint sizes, use the [Material Calculator](#) at CustomBuildingProducts.com or contact CUSTOM Technical Services at 800-282-8786.

