

A KOHLER COMPANY

Features

- Compression molded from Sterling's exclusive solid Vikrell_® material
- Gentle sloping back, neck, and armrest in bath design
- Lightly pebbled bottom surface for sure footing
- Durable high gloss finish
- 10 year consumer/3 year commercial limited warranty
- Integral apron with removable access panel
- 16" (40.6 cm) bath depth (floor to top of dam)
- 3" (7.6 cm) wainscot/tile ledge
- 60" (152.4 cm) x 37-1/2" (95.3 cm) x 20" (50.8 cm) rough-in dimensions include flanges
- 60" (152.4 cm) x 36" (91.4 cm) x 19" (48.3 cm) finished dimensions

Codes/Standards Applicable

Specified model meets or exceeds the following:


- ASTM E162
- ASTM E662
- ANSI Z124.1.2
- IAPMO/UPC

Specified Model

36" (91.4 cm) OVAL BATH WITH ACCESS PANEL **71101117** ALSO 71101127

ENSEMBLETM





Colors/Finishes

- 0: White
- Other: Refer to Price Book for additional colors/finishes

Model	Complete Unit Description Colors/Finishes		
71101117	36" (91.4 cm) oval bath with access panel, left drain (shown)	0 🗆	Other
71101127	36" (91.4 cm) oval bath with access panel, right drain	0	Other

SterlingPlumbing.com

Visit us online for fixture color choices, detailed product information, color photos, installation instructions, care guides, and warranties. Sterling offers additional lines of plumbing products to complement the Sterling product you've chosen. Sign up for the Sterling e-newsletter to learn more about our latest product innovations. You may also reach us by calling the Sterling Answer Center from within the USA at 1-888-STERLING in addition to consulting with your local dealer.

ENSEMBLETM

Technical Information

Fixture*:						
Bathing well		40" (101.6 cm) x 21" (53.3 cm)				
Top area		52" (132.1 cm) x 29" (73.7 cm)				
To overflow:						
Water depth		11″ (27.9 cm)				
Capacity		40 gal (151.4 L)				
* Approximate measurements for comparison only.						
Model doo wic		or maximum Ith	door maximum height			
71101117 58-1 71101127		·1/2" (148.6 cm)	NA*			
* Varies with alternative walls.						

Installation Notes

Install this product according to the installation guide. Size the drain cutout to fit the drain assembly that will be used.

Stud positioning is critical.

Studs should be positioned roughly as shown for support clip or roofing nail installation.

KOHLER COMPA

