

# Chlorinating Tabs

## 3-in-1 Formula



### DIRECTIONS FOR USE:

It is a violation of Federal Law to use this product in any manner inconsistent with its labeling. Read entire label and use strictly in accordance with precautionary statements, storage, disposal and directions.

#### ***Before You Begin:***

- Ensure all pool equipment is working properly. Adjust stabilizer levels to 40-50 ppm with Chlorine Stabilizer.
- Check water pH, alkalinity and calcium hardness with a test kit. Adjust pH to 7.2-7.6 by adding pH Down to lower pH, or by adding pH Up to raise pH. Adjust alkalinity to 80-125 ppm for plaster pools, 125-150 ppm for vinyl or fiberglass pools by adding Alkalinity Increaser. Adjust calcium hardness to 200-275 ppm for plaster pools, 175-225 ppm for vinyl or fiberglass pools by adding Calcium Hardness Increaser. Be sure to follow label directions.
- Check residual chlorine level with a test kit and adjust to 1-4 ppm by adding a stabilized granular chlorinator.

#### ***Start-up/Initial Treatment:***

- If water is cloudy or green, superchlorinate pool with appropriate shock product per label directions until pool is clear.
- Test chlorine level and add this product to feeder or floater to bring level to 1-4 ppm. If pool has a plastic skimmer, add one tablet per 10,000 gallons of pool water. Add additional product to maintain a chlorine level of 1-4 ppm.
- When chlorine level is adjusted to 1-4 ppm, add the algicide appropriate to your needs.

#### ***Routine Maintenance:***

- Fill feeding device with product to ensure constant chlorine level of 1-4 ppm. Check feeding device often and refill as needed.
- Re-entry into treated swimming pools is prohibited above levels of 4 ppm chlorine due to risk of body injury.

### **IN CASE OF MEDICAL EMERGENCY, CALL 1-877-800-5553.**

**PHYSICAL OR CHEMICAL HAZARDS:** STRONG OXIDIZING AGENT: Do not mix with other chemicals. Mix only with water. Never add water to product. Always add product to large quantities of water. When using automatic feeding devices, always follow manufacturer's directions as to the proper addition of sanitizer product to chlorinators. Use clean dry utensils. Do not add this product to any dispensing device containing remnants of any other product. Such use may cause a violent reaction leading to fire or explosion. Contamination with moisture, organic matter or other chemicals will start a chemical reaction and generate heat, hazardous gas, possible fire and explosion. In case of contamination or decomposition, do not reseal container. If possible, isolate container in open air or well ventilated area. Flood area with large volumes of water.

**ENVIRONMENTAL HAZARDS:** This pesticide is toxic to fish and aquatic organisms.

**NOTE:** User assumes all responsibility for use not in accordance with directions.