




# 5.5 HP\* Gas Air Compressor

Model MAC5501G

## "V" TWIN STYLE PUMP RUNS COOLER AND PROVIDES 12.5 CFM AT 100 PSI

- Powerful Honda GX160 4-stroke engine for increased performance and superior reliability
- 10-gallon twin tanks provide air supply to multiple nailers
- Cast iron pump with Big Bore™ cylinder and piston is engineered to provide durability and faster recovery time for improved performance
- Industrial-grade recoil starter with ergonomic grip and recoil rope design for faster, easier starts
- Automatic idle control engineered to reduce gas consumption and service life

### PERFORMANCE



"V" Twin Style Pump runs cooler and provides 12.5 CFM at 100 PSI for faster recovery time

### POWER



Powerful Honda GX160 4-stroke engine for increased performance and superior reliability

### CAPACITY



10-gallon twin tanks provide air supply to multiple nailers

### DURABILITY



Cast iron pump engineered to provide longer durability



# PERFORMANCE YOU NEED

# 5.5 HP\* Gas Air Compressor

## Model MAC5501G

### FEATURES & BENEFITS

- "V" Twin Style Pump runs cooler and provides 12.5 CFM at 100 PSI
  - Powerful Honda GX160 4-stroke engine for increased performance and superior reliability
  - 10-gallon twin tanks provide air supply to multiple nailers
  - Cast iron pump with Big Bore™ cylinder and piston is engineered to provide durability and faster recovery time for improved performance
  - Industrial-grade recoil starter with ergonomic grip and recoil rope design for faster, easier starts
  - Automatic idle control engineered to reduce gas consumption and service life
  - 10" non-flat tire for easier job site portability
  - Pump is oil-lubricated for cooler running temperatures and reduced wear
  - Large automotive style industrial air filters for increased air intake and greater efficiency
  - Convenient oil drain valve at the front of the pump for easier access
  - Integrated control panel with oversized pressure gauges for easier visibility of tank and hose pressure
  - Lever-handle ball valve tank drain improves upon standard petcock design for easier maintenance and air tank release
  - Anti-vibration rubberized feet for less vibration and reduced "crawling" during use
  - Fully enclosed belt drive with large fly-wheel for more efficient cooling of the pump
  - Stainless steel braided discharge hose for increased corrosion resistance and durability
  - Low profile design for easier transport and storage
  - Oil sight glass for fast, easy and efficient maintenance
  - Two universal brass couplers for increased durability and reduced corrosion
  - Ideal for framers, roofers, siding installation, decking, fencing, farming, general contractors, rental industry and more
- \*Maximum horsepower



Model MAC5501G



### SPECIFICATIONS

Motor	5.5 HP
Tank	10 gal.
Performance:	40 PSI 14 CFM
	90 PSI 12.5 CFM
Maximum Pressure	135 PSI
Overall Length	46"
Net Weight	190 lbs.
UPC	088381-685634

### OPTIONAL ACCESSORIES

- 2 ea. Universal Quick Couplers (447013-E)



Makita offers a wide variety of accessories. For a complete listing, please refer to the Makita General Catalog or visit our website at [makitatools.com](http://makitatools.com), or call 1-800-4MAKITA.

All specifications subject to change without prior notice. All models and accessories subject to stock on hand.  
The Makita Teal Color is the trade dress of Makita Corporation and is protected under common law and registered with the U.S. Patent and Trademark Office  
NTF-1214 MA-4398-14