



## Description & Features:

- Lead free wetted parts
- Economical pressure gauge and valve body assembly used for pressure testing
- Swivel hose adaptor on the Water Test Gauge
- Black steel case
- Dual scale (PSI/kPa)
- $\pm 3-2-3\%$  accuracy
- CRN registered
- 5 year warranty

## Applications:

- Residential & commercial pressure testing of water lines

## Specifications

<b>Dial</b>	2.5" (63 mm) white aluminum with black and red markings
<b>Case</b>	Steel painted black
<b>Lens</b>	Polycarbonate
<b>Ring</b>	Steel, painted black
<b>Bourdon Tube</b>	Lead free phosphor bronze
<b>Movement</b>	Lead free brass
<b>Pointer</b>	Aluminum, black
<b>Connection</b>	$\frac{3}{4}$ " female swivel hose connection (lead free)
<b>Welding</b>	#50 tin solder
<b>Ambient/Process Temperature</b>	-40°F to 150 °F (-40°C to 65°C)
<b>Water Test</b>	32°F to 150 °F (0°C to 65°C)
<b>Working Pressure</b>	Maximum 75% of full scale value
<b>Accuracy</b>	$\pm 3-2-3\%$ ANSI/ASME Grade B
<b>Enclosure Rating</b>	IP52

## Order Codes (products in bold are normally in stock)

Product	Water Test Gauge	Maximum Pointer Water Test Gauge
Dial Size	<b>2.5" (63mm)</b>	<b>2.5" (63mm)</b>
Connection	$\frac{3}{4}$ " Female Swivel Hose Connection	$\frac{3}{4}$ " Female Swivel Hose Connection
0/160 psi/kPa	<b>PETW213LF</b>	<b>PETM213LF</b>
0/300 psi/kPa	<b>PETW217LF</b>	<b>PETM217LF</b>

Other ranges available upon request.

## 2.5" Water Test Gauge

