



BEHR PREMIUM® Semi-Transparent Concrete Stain

No. 850 Tint Base

- Interior/Exterior Flat Finish
- Weather Resistant
- Chemical & Hot-Tire Resistant
- Siliconized 100% Acrylic



Spread Rate:
Rough 23-37 m²
Smooth 37-46 m²



Dry Time:
1 Hr. Dry to Touch
4 Hr. Recoat



Clean-Up:
Soap & Water



Protect
from Freezing

CAUTION: Stained surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.

WHERE TO USE

For uncoated and unsealed, properly prepared Interior or Exterior Patios, Pavers, Driveways*, Walkways, Garage Floors*, Pool Decks** and other concrete floors. *The composition of concrete varies; therefore, the lack of proper surface preparation and/or over application can lead to automobile tires lifting the product from the surface. **Light and pastel colored concrete stains should be used over pool deck surfaces. DARK COLOURS RETAIN HEAT.

PREPARATION†

(Proper surface preparation is required.) All surfaces must be clean, sound, dry and free of any dirt, oil and grease. New concrete must cure for a minimum of 30 days. Remove old coating or sealer, if present, using a product such as BEHR PREMIUM® No. 992 Concrete & Masonry Paint Stripper. Clean and etch surface using a product such as BEHR PREMIUM No. 991 Concrete & Masonry Cleaner & Etcher to achieve a textured profile similar to 150 grit sandpaper. Test: Sprinkle a few drops of water onto the surface. If water is quickly absorbed, the surface is ready. If not absorbed, re-etch. For areas subject to automotive traffic, apply a product such as BEHR PREMIUM No. 880 Concrete & Masonry Bonding Primer to increase adhesion of topcoat to the surface. Follow all label instructions.

APPLICATION

Do not thin. Internix cans of same products to ensure colour uniformity. STIR thoroughly before and during application. Use product when temperature is between 50 – 90° F (10 – 32° C). Do not apply in direct sunlight. Apply to dry concrete. Do not apply if rain or heavy dew is expected within 24 hours. Apply stain in small concrete sections approximately 4' by 4' (1.2 m x 1.2 m).

LIMITED WARRANTY If this product is found to be defective upon inspection by an expert, Behr Process Corporation will, at its option, and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. This warranty is not transferable. If you believe this product is defective, contact Behr Process Corporation at 2750 Centre Avenue N.E., Calgary, AB T2A2L3. The cost of transportation or shipping, if any, are to be assumed by the consumer. The clause of limitation of liability which follows is inapplicable in Quebec: **This warranty excludes (1) labour and costs of labour for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** The above provisions are not intended to operate where prohibited by law. This limited warranty is the only warranty provided by Behr Process Corporation unless extended by a provincial consumer statute.

To consult with a Behr Certified Coatings Professional, call 1-800-661-1591.

Work quickly and feather edges. Apply with a high quality pump sprayer at a fine spray setting using a circular motion. *Optional: If a more even, uniform appearance is desired, immediately back roll after spraying with a 10 mm nap roller or pad applicator.* Spread rate will vary depending on the porosity and texture of the surface. Allow first coat to dry before deciding if a second coat is necessary. An additional coat will provide a darker and more uniform colour. Horizontal surfaces may be subject to premature wear. Periodic touch-ups may be necessary.

OPTIONAL TOPCOAT

For added protection, use a product such as BEHR PREMIUM No. 985 Wet-Look Sealer for a high-gloss finish or a product such as BEHR PREMIUM No. 986 Low-Lustre Sealer for a low-gloss finish. Allow stain at least 4 hours to dry before topcoating. **NOTE:** Do not use Wet-Look Sealer or Low Lustre Sealer as a topcoat around pool decks or other areas subject to constant moisture. Follow all label instructions.

DRY TIME

Longer dry time required in cooler temperatures and in higher humidity. Surfaces may be subjected to light foot traffic after 24 hours. Allow 72 hours before subjecting surface to heavy foot traffic, repositioning furniture or automotive traffic. Park tires on corrugated cardboard for 7 days after applying stain. After 30 days, clean as needed with a mild, non-abrasive liquid detergent.

CLEAN UP

Use soap and water. Properly dispose of all soiled rags and protect unused product from freezing. To recycle or properly dispose of product in your community, contact your household refuse collection service.

† WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

CAUTION! IRRITANT! HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Avoid contact with eyes, skin and clothing. Do not breathe fumes. Wear eye protection and protective clothing. Use only with adequate ventilation. **FIRST AID TREATMENT:** Contains ETHYLENE GLYCOL. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes rinse with water for 20 minutes. If on skin rinse well with water. If inhaled, move person to fresh air.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.

BEHR
A Masco Company

©2016 Behr Process Corporation
Santa Ana, CA 92704 U.S.A. • behr.com
V.O.C. (C.O.V.) <100 g/L • REV. 08/16