TECHNICAL DATA

JMX-11



JOMAX[®] MOLD KILLER AND DEODORIZER

DESCRIPTION AND USES

Jomax[®] Mold Killer and Deodorizer effectively cleans, disinfects, controls and prevents mold and mildew and <u>kills</u> bacteria on hard, non-porous surfaces such as fiberglass, Formica[®], glass, ceramic, metal, plastic, painted surfaces and steel. No rinsing is necessary. Use this non-bleach formula on appliances, bathroom fixtures, bathtubs, cabinets, chairs, countertops, floors, sinks, tables, toilets, urinals, walls and other non-porous surfaces. Also eliminates pet urine odor.

IMPORTANT NOTE: Rinse all hard, non-porous surfaces that come in contact with foods such as countertops, appliances, tables and stovetops with potable water before reuse. Do not use on utensils, glassware and dishes.

Jomax Mold Killer and Deodorizer is a CRYOCIDE[®] disinfectant DuPont brand technology, a potent broad spectrum biocide less harmful than household bleach (lower in odor, less corrosive and will not discolor surfaces).

PERFORMANCE CHARACTERISTICS

- Kills mold, mildew, bacteria and odors on various hard, non-porous surfaces
- For interior use on walls, floors and other hard surfaces
- Eliminates tough household odors (including per urine)
- Controls and prevents mold and mildew growth
- Ready-to use, spray and wait 10 minutes to dry
- Provides excellent cleaning and deodorizing without damage and discoloration bleach can cause
- A single treatment works rapidly and thoroughly to clean and disinfect in 10 minutes
- A DuPont formulated technology

PRODUCTS

SKU	Description		
60191	1-Gallon		
60190	32 oz. spray		

PRODUCT APPLICATION

SURFACE PREPARATION

Remove all heavy build-up of dirt, grime and/or loose debris from the area to be treated.

PRODUCT APPLICATION (cont.)

DIRECTIONS FOR USE

Make sure bottle or container is tightly sealed to avoid leaking. Shake container well before use. For 32 ounce spray, apply to hard, non-porous surfaces thoroughly and evenly, 6-8 inches away from the surface. Use SPRAY nozzle position for large areas or STREAM for a concentrated jet on hard to reach areas. For 1-gallon, apply the product with a commercial low pressure sprayer, wet mop, sponge, or suitable application device to thoroughly wet the surface. Note: Where mist or vapors may be generated, ensure that proper ventilation is provided. In the absence of proper ventilation, a NIOSH approved respirator is advised. Treated surfaces must remain wet for 10 minutes. Wipe dry with a clean cloth, sponge or mop and allow to air dry. For heavily soiled areas, pre-cleaning is recommended. Rinse all surfaces that come in contact with foods such as countertops, appliances, tables and stovetops with potable water before reuse. Do not use on utensils, glassware and dishes. Repeat every 7 days or more frequently if growth occurs.

CAUTION! Avoid contact with eyes and skin. If eye contact occurs, flush with water for at least 15 minutes. If contact with skin occurs, wash thoroughly with soap and water. If irritation persists, seek medical attention. Do not take internally. **KEEP OUT OF REACH OF CHILDREN.**

STORAGE AND DISPOSAL

Store in the original container in a cool dry place at temperatures between 40-80°F (4-27°C). Dispose of container and unused contents in accordance with federal, state and local requirements.



JOMAX[®] MOLD KILLER AND DEODORIZER

PHYSICAL PROPERTIES

		MOLD KILLER AND DEODORIZER	
Composition		Oxychlorine Compounds, Quaternary Ammonia, Water	
Weight	Per Gallon	8.44 lbs.	
	Per Liter	1.01 kg	
рН		NA	
VOC		NA	
Practical Coverage		Varies with surface type and porosity	
Shelf Life		2 years	
Flash Point		>200°F (93°C)	
Caution!		May cause eye irritation. Avoid contact with skin, eyes and clothing. Wash thoroughly wit soap and water after handling. Remove contaminated clothing and wash before use. KEEP OUT OF REACH OF CHILDREN .	
Safety Information		For additional information, see MSDS.	

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, Illinois 60061 An RPM Company

Phone: 877•385•8155 www.rustoleum.com