

P2564 60" Outdoor Ceiling Fan

Project:

Fixture Type:

Contact:

Ceiling mounted • Wet location listed PROGRESS LED

Description:

This five-blade 60" Montague ceiling fan features an all weather wet location rating (ABS) to accommodate a variety of interior and exterior locations. The white opal glass shade contains a 17W dimmable, 3000K LED module, offering both form and function with energy- and cost-savings benefits. A remote with batteries is included. The Montague features a dual mount system to offer greater flexibility when installing. ABS blades are available in with three finish options: Antique Bronze, White and Forged Black.

Specifications:

- · Antique Bronze (-20) (Painted)
- Steel construction Bowl
- This five-blade 60" Montague ceiling fan features an all weather wet location rating to accommodate a variety of interior and exterior locations.
- Includes Progress Lightings dependable AirPro motor for a smooth, quiet performance
- Features a 17W dimmable, 1400 Lumen, 3000K, 90CRI LED replaceable light module, offering energy- and cost-savings benefits with a white opal shade
- The Montague features a dual mount system to offer greater flexibility when installing. The fan can be installed on a flat or sloped ceiling.
- Three speed reversible motor for year round comfort allows you to choose either a down draft (summer) or an up draft (winter)
- · Rated for wet locations
- A hand held remote control with fan speed control and full range light dimming is included and comes with a convenient wall bracket for storage
- Remote control may be replaced by a P2630-30 wall control
- ABS blades are included for maintenance free operation inside or out
- Limited Lifetime Warranty on the motor for peace of mind
- Canopy covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 80" of wire supplied
- •

Performance:

Number of Modules	1
Input Power	18w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	1386/77 (LM-79)
ССТ	3000 K
CRI	90 CRI
Life (hours)	46,000 (L70/TM-21)
EMI/RFI	Title 20
Min. Start Temp	-10 °C
Max. Operating Temp	40 °C
Warranty	Limited Lifetime warranty
Labels	UL Wet location listed

P2564-2030K

Images:



Dimensions:

Diameter: 60" Height: 17-5/8"