

TECHNOLOGY

SANIGRIND[®]Pro

A solution for any conventional toilet



View of installation behind the wall

Pump Type:
GRINDER

Discharge up to:
↑ 25 Ft. ↑ and/or ← 150 Ft. →

Power/Electrical Information:
115V – 60 Hz / 1 HP / 9.0 A

Dimensions:
H 10 1/2" (26.8cm) x W 20 3/8" (52cm) x D 8" (20.5cm)

Discharge pipe diameter:
3/4" rigid pipe

Discharge flow rate at 25':
19 gal per min (72 liters per min)

Discharge flow rate at 3':
38 gal per min (145 liters per min)

Max. Temperature:
104°F (40°C)

Possible Connections:



● 3/4" Discharge

● 1 1/2" Vent

● Connect to a conventional toilet

● Connect to shower, bathtub, sink or washing machine**

** Indirect Connection



EASY SERVICE
ACCESS PANEL



Part# 014

- Great for retrofitting applications. **Designed to work with conventional toilets** not supplied by Saniflo.
- **Mix and match** your fixtures (shower, bathtub and sink) from **different brands** and choose **any conventional toilet** to create your personalized one of a kind bathroom.
- Take advantage of the **different types of installations** Saniflo has to offer. The unit can either be installed on the floor while the rest of the fixtures are installed on a raised platform or you can lower the pump eliminating the need to create a subfloor.

Choose any conventional toilet, shower, bathtub or sink and enjoy your dream bathroom.