



BEHR® CHALK DECORATIVE PAINT

NO. 7100 WHITE



PRODUCT INFORMATION

BEHR® Chalk Decorative Paint is an easy way to create a unique and trendy look for your next paint project. This simple two-step paint and wax process allows your personal style and vision to come to life, whether you're looking for an aged antique look or prefer more of a vintage modern flair. The wide variety of BEHR colors, paired with BEHR Decorative Waxes, make every application completely tailored to achieve the one-of-a-kind look you desire. BEHR® Chalk Decorative Paint can be applied over most existing surfaces with very little surface preparation and delivers a smooth flat finish. Perfect for refreshing old and new wooden furniture, cast stone, concrete, and even metal surfaces to create one-of-a-kind accent pieces.

IDEAL FOR

BEHR Chalk Decorative Paint can be applied over most existing finishes with little surface preparation. Apply to old or new wood, cast stone, concrete, or even metal surfaces[†]. **Do not use on horizontal surfaces subject to foot traffic.**

PRODUCT SPECIFICATIONS

Tint Bases/Max Tint Load:

NO. 7100 31 oz / 1 oz
NO. 7130 29 oz / 3 oz

FINISH

Gloss: <5 @85°

Resin Type: MODIFIED ACRYLIC

*Weight per Gallon: 12.5 lbs.

*% Solids by Volume: 38%

*% Solids by Weight: 59%

VOC: < 50 g/L

FLASHPOINT

N/A

VISCOSITY

85-95 KU

RECOMMENDED FILM THICKNESS

At 60 sq. ft. per Quart:

Wet: 6.5 mils; **Dry:** 2.5 mils

At 100 sq. ft. per Quart:

Wet: 4.0 mils; **Dry:** 1.5 mils

COVERAGE RATE

Up to 150 Sq. Ft./Quart depending on application method, number of coats, and substrate porosity.

APPLICATION

- Shake the container thoroughly before opening for application.
- Use on properly prepared surfaces.
- Use product when the surface and air temperatures are between 50-90°F and will remain in that range for at least 4 hours after applying.

Brush: Nylon / Polyester Blend

Roller:

High Density Foam Roller
3/8" - 1/2" Synthetic Roller

Thinning:

This product is formulated to be rich and concentrated to provide excellent hide and coverage. If you find this product to be too thick, add up to 2 oz. of water per quart to thin it to the desired thickness for smooth and easy application.

DRY TIME:

@ 77°F and 50% RH:

Darker colors may require additional dry time between coats.

Cooler temperatures or higher humidity may prolong drying time.

To Touch: 1 hour

To Recoat: 2 hours

SURFACE PREPARATION

- All surfaces must be clean, free of dust, chalk, oil, grease, wax, polish, mold and mildew stains, loose and peeling paint, rust and all other foreign substances.
- Remove all dust with a damp cloth and allow to dry. Use BEHR Chalk Decorative Paint on properly prepared uncoated or painted interior surfaces.
- For wood that contains tannins, such as Redwood and Cedar, a coat of primer such as BEHR PREMIUM PLUS® Multi-Surface Primer & Sealer No. 436 is recommended.
- [†]For improved adhesion, prime all uncoated metal, cast stone and concrete surfaces before painting.

Glossy Surfaces:

For maximum adhesion, sand the surface thoroughly before coating.

New Wood:

Remove mill glaze with sandpaper. Set nails and fill holes, scratches, and gouges with the appropriate wood filler and let dry completely. Remove all dust with a wiping cloth. Fill all gaps with a 100% acrylic, silicized, paintable caulking, and allow to completely dry prior to coating.

Previously Painted Wood:

Remove all loose and peeling paint and all other foreign substances. Clean any dirt and grease by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water. Set nails and fill holes, scratches, and gouges with the appropriate wood filler and let dry completely. Remove all dust with a tack or wiping cloth. Fill all gaps with a 100% acrylic, silicized, paintable caulking, and allow to completely dry prior to coating.

Wood:

WARNING! Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

Ferrous and Non-Ferrous Metal:

The oil film on new non-ferrous metal must be removed before it is painted. Remove oil film with a detergent and water solution. For better paint adhesion, sand the surface with sandpaper, steel wool, or by using a product such as BEHR PREMIUM® Concrete & Masonry Cleaner & Etcher No. 991. Clean by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water.

Metal:

Remove all rust and mill scale using sandpaper, steel wool, abrasive blasting, or other abrading methods to create a profile on the metal's surface. New Surfaces: Clean the metal by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water. Bare metal must be primed the same day it is cleaned.



BEHR® CHALK DECORATIVE PAINT

NO. 7100 WHITE



WARNING: If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Center at 1-800-424-LEAD or visit www.epa.gov/lead.

CLEAN UP & DISPOSAL

Clean all tools and equipment with water. For disposal of empty containers and unused product, contact your household refuse collection service.

CAUTIONS/LIMITATIONS

- **IMPORTANT!** Do not open can without reading instructions.
- Shake can thoroughly before opening for application.
- Stir before and during application.
- For tint bases-do not use without addition of colorant.
- Do not use on floors.
- Do not use when air and surface temperature are below 50°F or above 90°F.
- Shelf life under normal conditions is 2 years unopened.
- Protect from freezing.

GENERAL INFORMATION:

WARNING: Causes eye and skin irritation. Wear protective clothing, gloves, eye, and face protection. Do not eat, drink, or smoke when using this product. Take off contaminated clothing and wash it before reuse. Wash hands thoroughly after handling. Dispose of unused, contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.

FIRST AID: If in eyes: Rinse cautiously with water for several minutes and remove contacts if present and easy to do. Continue rinsing and get medical attention if eye irritation persists. **If on skin:** Wash with plenty of soap and water. **If swallowed:** Rinse mouth and get medical attention if you feel unwell.