

1. Identification

Product identifier Behr Aerosol Paint + Primer - Black Gloss

Other means of identification

Product code B000144

Recommended use Architectural Coating

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Supplier Behr Process Corp.
1801 E. St. Andrew Place
Santa Ana, CA 92705

Telephone 714-545-7101

Emergency telephone number (800)-424-9300 CHEMTREC®

2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
	Gases under pressure	Compressed gas
Health hazards	Serious eye damage/eye irritation	Category 2A
	Carcinogenicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2 (central nervous system, lung)
OSHA defined hazards	Not classified.	

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer. May cause damage to organs (central nervous system, lung) through prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist/vapors. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Acetone	67-64-1	20 - 40
Propane	74-98-6	10 - 20
n-Butyl acetate	123-86-4	10 - 20
2-Methoxy-1-methylethyl acetate	108-65-6	2.5 - 10
Isobutane	75-28-5	2.5 - 10
Isobutyl acetate	110-19-0	2.5 - 10
Petroleum ether	8032-32-4	1 - 2.5
Xylene	1330-20-7	1 - 2.5
Carbon black	1333-86-4	0.1 - 1

Composition comments The manufacturer has claimed the exact percentage as trade secret under the OSHA Hazard Communication Standard.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

Skin contact

Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion

Not likely, due to the form of the product. In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.

Most important symptoms/effects, acute and delayed

May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing. Discomfort in the chest. Shortness of breath. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not breathe mist/vapors. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Acetone (CAS 67-64-1)	PEL	2400 mg/m ³ 1000 ppm
Carbon black (CAS 1333-86-4)	PEL	3.5 mg/m ³
Isobutyl acetate (CAS 110-19-0)	PEL	700 mg/m ³ 150 ppm
n-Butyl acetate (CAS 123-86-4)	PEL	710 mg/m ³ 150 ppm
Propane (CAS 74-98-6)	PEL	1800 mg/m ³ 1000 ppm
Xylene (CAS 1330-20-7)	PEL	435 mg/m ³ 100 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Acetone (CAS 67-64-1)	STEL	500 ppm	
	TWA	250 ppm	
Carbon black (CAS 1333-86-4)	TWA	3 mg/m ³	Inhalable fraction.
Isobutane (CAS 75-28-5)	STEL	1000 ppm	
Isobutyl acetate (CAS 110-19-0)	STEL	150 ppm	
	TWA	50 ppm	
n-Butyl acetate (CAS 123-86-4)	STEL	150 ppm	

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Xylene (CAS 1330-20-7)	TWA	50 ppm	
	STEL	150 ppm	
	TWA	100 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	590 mg/m3
		250 ppm
Carbon black (CAS 1333-86-4)	TWA	3.5 mg/m3
Isobutane (CAS 75-28-5)	TWA	1900 mg/m3
		800 ppm
Isobutyl acetate (CAS 110-19-0)	TWA	700 mg/m3
		150 ppm
n-Butyl acetate (CAS 123-86-4)	STEL	950 mg/m3
		200 ppm
	TWA	710 mg/m3
		150 ppm
Petroleum ether (CAS 8032-32-4)	Ceiling	1800 mg/m3
	TWA	350 mg/m3
Propane (CAS 74-98-6)	TWA	1800 mg/m3
		1000 ppm
Xylene (CAS 1330-20-7)	STEL	655 mg/m3
		150 ppm
	TWA	435 mg/m3
		100 ppm

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	TWA	50 ppm

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines**US - California OELs: Skin designation**

2-Methoxy-1-methylethyl acetate (CAS 108-65-6)

Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear safety glasses with side shields (or goggles).

Skin protection	
Hand protection	Wear appropriate chemical resistant gloves.
Skin protection	
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
Respiratory protection	If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection. Chemical respirator with organic vapor cartridge and full facepiece. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Aerosol.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	324.2 °F (162.3 °C) estimated
Flash point	-155.9 °F (-104.4 °C) Propellant estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	1.8 % estimated
Flammability limit - upper (%)	9.9 % estimated
Vapor pressure	60 - 70 psig (68 °F (20 °C)) estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	835.25 °F (446.25 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Flammability class	Flammable IB estimated
Heat of combustion	27.92 kJ/g estimated
Oxidizing properties	Not oxidizing.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.

Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Heat. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong acids. Strong oxidizing agents. Chlorine. Fluorine. Halogens. Nitrates.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing. Discomfort in the chest. Shortness of breath.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components	Species	Test Results
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)		
Acute		
Dermal		
LD50	Rabbit	> 5000 mg/kg
Oral		
LD50	Rat	> 8532 mg/kg
Acetone (CAS 67-64-1)		
Acute		
Dermal		
LD50	Rabbit	> 15700 mg/kg, 24 Hours
Inhalation		
<i>Vapor</i>		
LC50	Rat	76 mg/l, 4 Hours
Oral		
LD50	Rat	5800 mg/kg
Carbon black (CAS 1333-86-4)		
Acute		
Dermal		
LD50	Rabbit	> 3000 mg/kg
Oral		
LD50	Rat	> 8000 mg/kg
Isobutane (CAS 75-28-5)		
Acute		
Inhalation		
LC50	Mouse	52 mg/l, 1 Hours
Isobutyl acetate (CAS 110-19-0)		
Acute		
Dermal		
LD50	Rabbit	> 5000 mg/kg
Oral		
LD50	Rat	13400 mg/kg

Components	Species	Test Results
n-Butyl acetate (CAS 123-86-4)		
Acute		
Inhalation		
LC50	Rat	2000 ppm, 4 Hours
Oral		
LD50	Rat	10768 mg/kg
Propane (CAS 74-98-6)		
Acute		
Inhalation		
Gas		
LC50	Rat	> 80000 ppm, 15 Minutes
Xylene (CAS 1330-20-7)		
Acute		
Oral		
LD50	Rat	3523 mg/kg
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Suspected of causing cancer.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Carbon black (CAS 1333-86-4)	2B Possibly carcinogenic to humans.	
Xylene (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.	
NTP Report on Carcinogens		
Carbon black (CAS 1333-86-4)	Known To Be Human Carcinogen.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)		
Not listed.		
Reproductive toxicity	Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals.	
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.	
Specific target organ toxicity - repeated exposure	May cause damage to organs (central nervous system, lung) through prolonged or repeated exposure.	
Aspiration hazard	Not an aspiration hazard.	
Chronic effects	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.	
12. Ecological information		
Ecotoxicity	The product is not classified as environmentally hazardous.	
Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.	
Bioaccumulative potential		
Partition coefficient n-octanol / water (log Kow)		
Isobutane (CAS 75-28-5)	2.76	
Isobutyl acetate (CAS 110-19-0)	1.78	
Propane (CAS 74-98-6)	2.36	
n-Butyl acetate (CAS 123-86-4)	1.78	
Mobility in soil	No data available.	
Other adverse effects	The product contains volatile organic compounds which have a photochemical ozone creation potential.	

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	-
Environmental hazards	
Marine pollutant	No.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

IATA

UN number	UN1950
UN proper shipping name	Aerosols
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	-
Environmental hazards	No
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	-
Environmental hazards	
Marine pollutant	No
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1)	Listed.
Isobutane (CAS 75-28-5)	Listed.
Isobutyl acetate (CAS 110-19-0)	Listed.
n-Butyl acetate (CAS 123-86-4)	Listed.
Propane (CAS 74-98-6)	Listed.
Xylene (CAS 1330-20-7)	Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Toxic Substances Control Act (TSCA)

All components of the mixture on the TSCA 8(b) inventory are designated "active".

Superfund Amendments and Reauthorization Act of 1986 (SARA)**SARA 302 Extremely hazardous substance**

Not listed.

SARA 311/312 Hazardous chemical Yes

Classified hazard categories	Flammable (gases, aerosols, liquids, or solids) Gas under pressure Serious eye damage or eye irritation Carcinogenicity Specific target organ toxicity (single or repeated exposure)
-------------------------------------	--

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Xylene	1330-20-7	1 - 2.5

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Xylene (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Isobutane (CAS 75-28-5)

Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA) Contains component(s) regulated under the Safe Drinking Water Act.**Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number**

Acetone (CAS 67-64-1) 6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Acetone (CAS 67-64-1) Low priority

Isobutyl acetate (CAS 110-19-0) Low priority

n-Butyl acetate (CAS 123-86-4) Low priority

US state regulations**US. Massachusetts RTK - Substance List**

Acetone (CAS 67-64-1)

Carbon black (CAS 1333-86-4)

Isobutane (CAS 75-28-5)

Isobutyl acetate (CAS 110-19-0)

n-Butyl acetate (CAS 123-86-4)

Propane (CAS 74-98-6)

Xylene (CAS 1330-20-7)

US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)

Carbon black (CAS 1333-86-4)

Isobutane (CAS 75-28-5)

Isobutyl acetate (CAS 110-19-0)

n-Butyl acetate (CAS 123-86-4)
Petroleum ether (CAS 8032-32-4)
Propane (CAS 74-98-6)
Xylene (CAS 1330-20-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)
Carbon black (CAS 1333-86-4)
Isobutane (CAS 75-28-5)
Isobutyl acetate (CAS 110-19-0)
n-Butyl acetate (CAS 123-86-4)
Petroleum ether (CAS 8032-32-4)
Propane (CAS 74-98-6)
Xylene (CAS 1330-20-7)

US. Rhode Island RTK

Acetone (CAS 67-64-1)
Carbon black (CAS 1333-86-4)
Isobutyl acetate (CAS 110-19-0)
n-Butyl acetate (CAS 123-86-4)
Propane (CAS 74-98-6)
Xylene (CAS 1330-20-7)

16. Other information, including date of preparation or last revision

Issue date August 9, 2019
Revision date August 9, 2019
Version # 1.0
HMIS® ratings Health: 2*
Flammability: 4
Physical hazard: 3

Disclaimer Behr Process Corp cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.