

Vigoro® Heavy Duty, 50ft. Poly Landscape Edging



Product Configurations

Item 1009-50HD	Vigoro® 50' Edging Coil
Item 1900-4HD-36	Vigoro® 4 ct. Metal Stake
Item 1900-12HD-12	Vigoro® 12 ct. Metal Stake

Product Specifications

Material:	Medium density polyethylene with UV inhibitor
Weight:	15.00 lbs. per 50' coil (nominal)
Height:	5.0 in. (nominal)



Installation Instructions

PREPARATION :

- 1) Uncoil edging and add weight to both ends of coil. Edging becomes more flexible when warmed in sun before using.
- 2) Make a trench along the edge of the garden bed at least 4 inches deep.

INSTALLATION :

- 1) Place edging in trench with the V-lip facing the outside of the garden bed. The rounded top should be above ground.
- 2) Pound stakes through edging every 4-5 feet at a 45 degree angle just above the V-lip. Use additional stakes to make the desired garden shape (stakes sold separately).
- 3) Pack soil on the bed side of the edging and fill with bedding materials up to the top of the beaded edge.

Packaging Specifications

Edging is sold in 50ft coiled lengths with 2 connectors included. Vigoro Metal Landscape Stakes are sold separately in 4 and 12 ct. packs.

Physical Property Testing

Vigoro® Poly Landscape Edging products have passed the following:

Ultraviolet and Weathering Tests per Federal Std. 191 A Method 5804.

Low Temperature Flexibility & Cracking Test per Federal Std. 501 Method 6511 at -1° C.

Dimex Limited Lifetime Warranty

Vigoro® Poly Landscape Edging is guaranteed to be free of manufacturing defects. This product will not crack, rot, or deteriorate due to UV exposure or severe weather conditions.



28305 State Route 7
Marietta, OH 45750
www.dimexcorp.com

Phone: 740-374-3100
Toll Free: 800-334-3776
Fax: 740-374-5420