



**PORCH & PATIO FLOOR PAINT**  
**NO. 6050-N (LOW-LUSTRE) ULTRA PURE WHITE®**



**PRODUCT INFORMATION**

BEHR PREMIUM® Porch & Patio Floor Paint is available in two sheens, Low-Lustre and Gloss Enamels. This 100% acrylic latex product, has a mildew resistant finish, resists scuffing, fading, cracking and peeling while providing a durable, long-lasting finish that is ideal for both interior and exterior applications.

**RECOMMENDED USES:**

This product is ideal for porches, floors, decks, basements, patios, siding, trim, furniture and trellises. Not for use on garage floors or areas subject to automotive traffic. Use on previously painted or primed interior or exterior surfaces such as:

- Wood
- Concrete
- Composite

**PRODUCT SPECIFICATIONS:**

**Tint Bases/Max Tint Load:**

- No. 6050-N Ultra Pure White® 128 oz. / 2 oz.
- No. 6400 Medium Base 120 oz. / 10 oz.
- No. 6300 Deep Base 116 oz. / 14 oz.

**PRE-MIXED COLORS:**

- No. 6694 Low-Lustre Silver Gray
- No. 6695 Low-Lustre Slate Gray

**Gloss:** 5-15 @ 60°

**Sheen:** 5-15 @ 85°

**Resin Type:** 100% Acrylic Latex

**Weight per Gallon:** 10.7 lbs.

**% Solids by Volume:** 37%

**% Solids by Weight:** 49.9%

**VOC:** <50 g/L

**Flash Point:** N/A

**Viscosity:** 90-100 KU

**Recommended Film Thickness:**

- Wet: 8.0 Dry: 2.9 mils @ 200 Sq. Ft./Gal.
- Wet: 4.0 Dry: 1.4 mils @ 400 Sq. Ft./Gal.

**Coverage:** 200-400 Sq.Ft./Gal. depending on application method and substrate porosity. Does not include the loss of material from spraying.

**APPLICATION:**

**Brush:** Nylon/polyester

**Roller:** 3/8"-1/2" nap

**Airless Spray:** At packaged consistency

**Tip:** .015" - .019"

**Filter:** 60 mesh

**Thinning:** (If required) No more than 1/2 pint of water per gallon.

**Dry Time:** @ 77° & 50% RH

Longer dry time may be required in cooler temperatures and higher humidity.

**To Touch:** 1 hour

**To Recoat:** 4-6 hours

**Full Cure:** 2 weeks. Allow 72 hours before subjecting to normal use. After 30 days, cured paint film may be cleansed with a mild, non-abrasive liquid detergent.

**SURFACE PREPARATION:**

All surfaces must be clean, free of dust, chalk, oil, grease, wax, polish, mold and mildew stains, loose and peeling paint, rust and all other foreign substances.

**Non-Ferrous Metal:** The oil film on new non-ferrous metal must be removed before it is painted. Remove oil film with a detergent and water solution. For better paint adhesion, sand the surface with sandpaper, steel wool, or by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water.

**New Surfaces:** Wipe down clean metal surfaces prior to painting with a vinegar solution, one part vinegar to five parts water (1:5). Bare metal must be primed the same day it is cleaned. **Metal:** Remove all rust and mill scale using sandpaper, steel wool, abrasive blasting, or other abrading methods to create a profile on the metal's surface. Clean the metal by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water. Bare metal must be coated the same day it is cleaned.

**Vinyl Siding, Architectural Plastics: Previously**

**Painted Surface:** Remove loose paint and all other foreign substances. Clean any dirt by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water. For best results, apply a primer such as PREMIUM PLUS® Interior/Exterior Multi-Surface Primer & Sealer No. 436 prior to topcoat application. **CAUTION:** Vinyl siding is manufactured to withstand certain levels of heat intensity. Be sure when choosing a paint color, to select a color which is similar or lighter than the vinyl siding's original color. A darker color paint will absorb more heat, resulting in a warping of the siding.

COMPLIES WITH THE BELOW AS OF 1/1/2017			
SCAQMD	YES	OTC Phase II	YES
CARB	YES	LADCO	YES
CARB SCM 2007	YES	AIM	YES
OTC	YES	LEED v.3 (2009) <sup>†</sup>	YES

This coating conforms to USDA regulatory requirements for incidental food-contact materials intended for use on surfaces not in direct contact with food, such as walls, floors and ceilings.

<sup>†</sup>Please visit [www.usgbc.org/LEED](http://www.usgbc.org/LEED) for additional details.

**Wood: Shakes & Shingles, Composition Panels/**

**Siding, Fiber Board: New Wood:** Remove mill glaze with sandpaper or use a product such as BEHR PREMIUM® All-in-One Wood Cleaner No. 63 to open the pores of the wood and follow all label instructions. Remove mildew stains with a mildew stain removing product. Set nails and fill holes, scratches, and gouges with the appropriate wood filler and let dry completely. Remove all dust with a wiping cloth. Fill all gaps with a 100% acrylic, siliconized, paintable caulking and allow to dry completely. Patched and filled surfaces should be sanded smooth and dusted clean prior to coating. **Previously Painted Wood:** Remove all loose and peeling paint and all other foreign substances. Clean any dirt and grease by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water. Set nails and fill holes, scratches, and gouges with the appropriate wood filler and let dry completely prior to coating. Remove all dust with a wiping cloth. Fill all gaps with a 100% acrylic, siliconized, paintable caulking, and allow to completely dry prior to coating. **Glossy Surfaces:** For maximum adhesion, scuff sand the surface thoroughly before coating. **Weathered Wood Surfaces:** To remove loose wood fibers, latex, oil-based and 100% acrylic coatings on new or weathered wood decks, siding, fences, shakes and shingles, use a product such as BEHR PREMIUM® Wood Stain & Finish Stripper No. 64 and follow all label instructions. Use a product such as BEHR PREMIUM All-in-One Wood Cleaner No. 63 and follow all label instructions to clean and brighten the wood surface and to remove light to medium stains caused by mold, mildew, algae and fungus. Be sure to follow all label instructions.

**Wood: WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.





## PORCH & PATIO FLOOR PAINT

### NO. 6050-N (LOW-LUSTRE) ULTRA PURE WHITE®

**Tannin Bleed & Stainblocking:** After priming, test for stain bleed-through by applying the topcoat to a small section. If the stain bleeds through the topcoat, apply a second coat of primer and test again before top-coating the entire area. If bleeding continues, a longer dry time of the primer may be needed before top-coating or an additional coat of primer may be required to block the tannin bleed or stain.

**Masonry: Stucco, Concrete, Cut Masonry Unit's (CMUs), Split-Faced Block: New:** All masonry surfaces must be cured at least 30 days before painting. The pH must be 10.0 or lower prior to coating. Smooth masonry may require an adequate profile for adhesion. For all other smooth concrete, create a profile using a product with mechanical means.

**Masonry: Cement Composition Panels/Siding, Exterior Insulation and Finish Systems (EIFS) or Synthetic Stucco: New:** All masonry surfaces must be cured at least 30 days before painting. The pH must be 10.0 or lower prior to coating. All surfaces must be clean, free of dust, chalk, mold and mildew stains, loose and peeling paint and all other foreign substances. Clean surfaces with a detergent and water solution by scrubbing the surface vigorously and rinse with a garden hose or a power washer at a low setting (500-1200 PSI). DO NOT USE HIGH PRESSURE as this may harm the substrate. **Previously Painted Surface:** All surfaces must be clean, free of dust, chalk, mold and mildew stains, loose and peeling paint and all other foreign substances. Clean surfaces with a detergent and water solution by scrubbing the surface vigorously and rinse with a garden hose or a power washer and allow to dry.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Center at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### RECOMMENDED PRIMER/SYSTEMS:

#### PROPERLY PREPARED NEW SURFACES:

##### Wood:

- BEHR PREMIUM PLUS Interior/Exterior Multi-Surface Primer & Sealer No. 436
- BEHR PREMIUM PLUS Interior All-In-One Primer & Sealer No. 75

##### Tannin/Stainblocking:

- BEHR PREMIUM PLUS Interior/Exterior Multi-Surface Primer & Sealer No. 436
- For Interior Tannin/Stainblocking: BEHR PREMIUM PLUS Interior All-In-One Primer & Sealer No. 75

##### Masonry:

- BEHR PREMIUM Concrete & Masonry Bonding Primer No. 880
- BEHR PREMIUM PLUS Interior/Exterior Multi-Surface Primer & Sealer No. 436
- BEHR PREMIUM PLUS Interior Stain-Blocking Primer & Sealer No. 75

##### Masonry with pH Levels up to 13.0:

- BEHR PREMIUM Interior/Exterior Basement & Masonry Waterproofing No. 875
- BEHR PREMIUM PLUS Interior/Exterior Multi-Surface Primer & Sealer No. 436

##### Non-Ferrous Metal:

- BEHR PREMIUM PLUS Interior/Exterior Multi-Surface Primer & Sealer No. 436

##### Vinyl Siding, Architectural Plastics:

- BEHR PREMIUM PLUS Interior/Exterior Multi-Surface Primer & Sealer No. 436

### CLEAN UP:

Clean all tools and equipment with clean water. For disposal of empty containers and unused product, contact your household refuse collection service.

### CAUTIONS/LIMITATIONS:

- Protect from freezing.
- Do not use on garage floors and driveways.
- Do not use on roofs.
- For best results, apply at temperatures between 50°F - 90°F. Temperatures above 90°F may affect the application such as drying too fast. Avoid painting in direct sun. NOTE: If the surface is hot to the touch it should be considered too hot to apply this coating.
- Allow 72 hours before subjecting to normal use.
- After 30 days, cured paint film may be cleaned with a mild, non-abrasive liquid detergent.
- Shelf life under normal conditions is two years unopened.

### GENERAL INFORMATION:



**Warning!** Causes eye and skin irritation. Wear protective clothing, gloves, eye, and face protection. Do not eat, drink, or smoke when using this product. Take off contaminated clothing and wash it before reuse. Wash hands thoroughly after handling. Dispose of unused, contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.

**First aid: If in eyes:** Rinse cautiously with water for several minutes and remove contacts if present and easy to do. Continue rinsing and get medical attention if eye irritation persists. **If on skin:** Wash with plenty of soap and water. **If swallowed:** Rinse mouth and get medical attention if you feel unwell.