

# KILZ® COMPLETE® INTERIOR/EXTERIOR OIL-BASE PRIMER



- Oil based primer/sealer/stainblocker
- Interior and exterior use
- Seals porous surfaces for uniform finish
- Blocks heavy stains including tannin bleed (ex. Cedar and Redwood)
- Seals persistent smoke, pet and food odors
- Deeply penetrating oil provides excellent adhesion for wood
- Ideal for priming ferrous metals, cast iron, wrought iron and steel
- Mildew-resistant film
- Fast drying - recoat in 1 hour



Mineral Spirits  
Clean-Up



300 - 400 sq ft / gal.\*



Dry to Touch: 30 Min\*\*  
Dry to Recoat: 1 Hr\*\*



Protect from  
Freezing

## WHERE TO USE

KILZ COMPLETE® is a premium quality primer, sealer and severe stain blocker for interior & exterior surfaces. It is ideal for blocking severe fire & smoke damage, tannins from Cedar & Redwood and other bleeding stains. KILZ COMPLETE offers great adhesion, quick dry time and a dry film that is mold resistant. Use on wood, ferrous metals, cured plaster, masonry and CMU and under or over latex or oil-based paint. Not recommended for floors or galvanized metals.

## SURFACE PREPARATION (The following steps are recommended for product performance.)

- All surfaces must be clean, free of dust, chalk, oil, grease, wax, polish, mold and mildew, loose peeling paint, rust and all other foreign substances.
- If washing is necessary, use a non-soapy detergent or a TSP substitute, rinse well and allow to dry.
- Unpainted wood exposed to sun and/or moisture longer than 2-4 weeks must be cleaned and sanded before priming.
- Glossy Surfaces: For maximum adhesion, scuff sand the surface thoroughly before priming.
- Peeling or Checked Paint: Scrape off loose paint and sand to a smooth surface.
- Mold or Mildew Covered Surfaces: Wash the area with a mildew remover, rinse with water and allow to dry before priming.
- Masonry, Brick, Stucco and Plaster: KILZ COMPLETE primers may be used on clean, dry, aged masonry surfaces that have cured (dried) at least 90 days. If masonry has cured less than 90 days, use KILZ® PREMIUM, KILZ 2® or KILZ ODORLESS® primers.
- Fire Restoration: It is critical to remove charred wood and clean smoke damaged surfaces thoroughly before priming. If water-base is preferred, use KILZ MAX® to permanently seal severe stains and odors.

**WARNING** WARNING If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Center at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

## APPLICATION

- Eye protection is recommended. Do not thin. Stir thoroughly before and occasionally during use. Apply using a brush, roller or sprayer.
- Use product when painting surface and air temperatures are between 50°F (10°C) and 90°F (32°C).
- Use a high quality 3/8-1/2" nap roller cover, nylon/polyester brush or an airless sprayer (.015-.021" spray tip, 60 mesh filter).
- Prime entire surface to ensure a uniform appearance of the topcoat.
- Stainblocking: After priming, test for stain bleed-through by applying the topcoat to a small section. If the stain bleeds through the topcoat, apply a second coat of primer and test again before topcoating the entire area. If bleeding continues, a longer dry time is needed before topcoating.
- Tinting: Up to 2 ounces of universal colorant per gallon. Tinting to a lighter shade

than topcoat is recommended.

- Coverage: 300 - 400 sq. ft. (28 - 37 m<sup>2</sup>) per gallon depending on application method and surface porosity.
- Dry Time @ 77°F (25°C) / 50% RH: Touch 30 minutes, Recoat 1 hour.

## CLEAN-UP & DISPOSAL

- Clean equipment and paint splatters with mineral spirits or acetone. Immediately after use, dispose of soiled rags and waste in a closed, water-filled container.
- Do not dispose of this product down a drain. Please consider donating any unused product.
- If spilled, contain material and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused product in accordance with all current federal, state and local regulations. For recycling or disposal information contact your local household refuse collection service.



**WARNING** Cancer and Reproductive Harm  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**VENTILATION REQUIRED:** To avoid inhalation and combustion hazards (see below), **DO NOT** use this product unless you can achieve cross-ventilation by opening windows and doors during application and drying. **CONTAINS PETROLEUM DISTILLATES. VAPOR HARMFUL.** May affect the brain or nervous system causing dizziness, headache or nausea. Do not breathe vapors or spray mist. If you experience eye watering, headaches or dizziness, increase fresh air, wear respiratory protection (NIOSH/MSHA TC-23C or equivalent) or leave the area. Follow respirator manufacturer's directions for respirator use. Causes eye, skin, nose and throat irritation. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling and before smoking and eating. **NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. **VAPORS MAY CAUSE FLASH FIRE.** Keep away from sparks, heat and open flame. Do not smoke. Vapors are heavier than air, and can travel at floor level to distant ignition sources. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors, high intensity lights and other sources of ignition during use and until all vapors are gone. Close container after each use. To avoid spontaneous combustion, soak soiled rags and waste immediately after use in a closed, water-filled metal container. **FIRST AID:** If swallowed, do not induce vomiting. Call a physician immediately. If you have difficulty breathing, leave area to obtain fresh air. If difficulty continues, get medical attention immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water.

### KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY

**LIMITED WARRANTY:** For one year from the date of purchase, Masterchem Industries LLC warrants to the original residential consumer purchaser (1) that the product meets Masterchem Industries LLC's manufacturing specifications, and (2) the performance of this product when applied according to the label instructions and specifications. In the event that this product proves to be defective within one year from the date of purchase, Masterchem Industries LLC will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. This warranty is not transferable. **This warranty excludes (1) labor and costs of labor for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. To the extent permitted by applicable law, any implied warranties including the implied warranties of merchantability and of fitness for a particular purpose, are limited to the duration of this express warranty. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state. **Note to residents of the State of New Jersey:** The provisions of this warranty, including its limitations, are intended to apply to the fullest extent permitted by the laws of the State of New Jersey. For warranty service, call 1-866-774-6371, or email: [techservice@masterchem.com](mailto:techservice@masterchem.com). Masterchem Industries LLC reserves the right to inspect any and all application of the product prior to processing your claim made under this warranty.

\* Depending on the surface texture, porosity and application method

\*\* @ 77°F, 50% RH. Longer dry time required in cooler temperatures and in higher humidity



©2018 Masterchem Industries LLC  
1-866-774-6371 • [www.kilz.com](http://www.kilz.com)  
REV. 08/17 • L1013  
Max VOC: 450 grams/liter