SAFETY DATA SHEET

Issuing Date No data available

Revision Date 02-Feb-2015

Revision Number 2



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name	Positec 20V 1.5Ah Li batt.	
Other means of identification		
Synonyms	None	
Recommended use of the chemical	and restrictions on use	
Recommended Use	LITHIUM ION BATTERIES	
Uses advised against	No information available	
Details of the supplier of the safety data sheet		
Supplier Name Supplier Address	Positec(Macao Commercial Offshore) Limited 461,East Ganjiang Road,Suzhou,Jiangsu,China Suzhou Jiangsu 215006 CN	
Supplier Phone Number	Phone:(86) 512 65152835 Fax:(86) 512 65152885 Contact Phone(86) 512 65152290	
Supplier Email Emergency telephone number	email@positec.biz	


2. HAZARDS IDENTIFICATION

Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Carcinogenicity	Category 1A
Specific target organ toxicity (repeated exposure)	Category 1

GHS Label elements, including precautionary statements



Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Wash face, hands and any exposed skin thoroughly after handling Contaminated work clothing should not be allowed out of the workplace Wear protective gloves Do not breathe dust/fume/gas/mist/vapors/spray Do not eat, drink or smoke when using this product Wear eye/face protection

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Skin

IF ON SKIN: Wash with plenty of soap and water Take off contaminated clothing and wash before reuse If skin irritation or rash occurs: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable



Unknown Toxicity

55.99% of the mixture consists of ingredient(s) of unknown toxicity

Other information

May be harmful if swallowed Very toxic to aquatic life with long lasting effects Repeated or prolonged skin contact may cause allergic reactions with susceptible persons

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%	Trade Secret
Iron	7439-89-6	7 - 13	*
Copper	7440-50-8	5 - 10	*
Lithium nickel oxide (LiNiO2)	12031-65-1	1 - 5	*
Nickel	7440-02-0	1 - 5	*
Aluminum	7429-90-5	1 - 5	*
Lithium manganese oxide (LiMn2O4)	12057-17-9	1 - 5	*
Manganese	7439-96-5	1 - 5	*
Lithium Cobalt Oxide (CoLiO2)	12190-79-3	1 - 5	*
Supplier Trade Secret	Proprietary	1 - 5	*
Ethylene carbonate	96-49-1	1 - 5	*
Phosphate(1-), hexafluoro-, lithium	21324-40-3	1 - 5	*
Carbon black	1333-86-4	0.1 - 1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice	First aid is upon rupture of sealed battery.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. Do not rub affected area.
Skin Contact	Wash off immediately with soap and plenty of water for at least 15 minutes. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.
Inhalation	Remove to fresh air. Get medical attention immediately if symptoms occur.
Ingestion	Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician.
Self-protection of the first aider	Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Wear personal protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Itching. Coughing and/ or wheezing. **Effects**

Indication of any immediate medical attention and special treatment needed

Notes to Physician May cause sensitization of susceptible persons. Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

Product is or contains a sensitizer. May cause sensitization by skin contact.

Hazardous Combustion Products

Carbon oxides.

Explosion Data Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge No.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions	Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas.	
Other Information	Refer to protective measures listed in Sections 7 and 8.	
Environmental Precautions		
Environmental Precautions	Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so.	
Methods and material for containment and cleaning up		
Methods for Containment	Prevent further leakage or spillage if safe to do so.	
Methods for cleaning up	Pick up and transfer to properly labeled containers.	



7. HANDLING AND STORAGE

Precautions for safe handling

HandlingIn case of rupture: Handle in accordance with good industrial hygiene and safety practice.
Avoid contact with skin, eyes or clothing. Use personal protection equipment.Conditions for safe storage, including any incompatibilitiesKeep containers tightly closed in a dry, cool and well-ventilated place.StorageKeep containers tightly closed in a dry, cool and well-ventilated place.Incompatible ProductsStrong acids. Strong oxidizing agents. Strong bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Copper	TWA: 0.2 mg/m ³ fume TWA: 1	TWA: 0.1 mg/m ³ fume	IDLH: 100 mg/m ³ dust, fume and
7440-50-8	mg/m ³ Cu dust and mist	TWA: 1 mg/m ³ dust and mist	mist
		(vacated) TWA: 0.1 mg/m ³ Cu	TWA: 1 mg/m ³ dust and mist
		dust, fume, mist	TWA: 0.1 mg/m ³ fume
Lithium nickel oxide (LiNiO2)	TWA: 0.2 mg/m ³ Ni inhalable	TWA: 1 mg/m ³ Ni	IDLH: 10 mg/m ³ Ni
12031-65-1	fraction	(vacated) TWA: 1 mg/m ³ Ni	TWA: 0.015 mg/m ³ except Nickel
			carbonyl Ni
Nickel	TWA: 1.5 mg/m ³	TWA: 1 mg/m ³	IDLH: 10 mg/m ³
7440-02-0		(vacated) TWA: 1 mg/m ³	TWA: 0.015 mg/m ³
Aluminum	TWA: 1 mg/m ³ respirable fraction		TWA: 10 mg/m ³ total dust
7429-90-5		TWA: 5 mg/m ³ respirable fraction	TWA: 5 mg/m ³ respirable dust
		(vacated) TWA: 15 mg/m ³ total	
		dust	
		(vacated) TWA: 5 mg/m ³ respirable fraction (vacated)	
		TWA: 5 mg/m ³ Al Aluminum	
Lithium manganese oxide (LiMn2O4)	TWA: 0.2 mg/m ³ Mn	(vacated) Ceiling: 5 mg/m ³	IDLH: 500 mg/m ³ Mn
12057-17-9	TWA. 0.2 mg/mº Mm	Ceiling: 5 mg/m ³ Mn	TWA: 1 mg/m ³ Mn
12037-17-9		Cennig: 5 mg/m² Mm	STEL: 3 mg/m ³ Mn
Manganese	TWA: 0.02 mg/m ³ respirable	(vacated) TWA: 1 mg/m ³ fume	IDLH: 500 mg/m ³
7439-96-5	fraction	(vacated) STEL: 3 mg/m ³ fume	TWA: 1 mg/m ³ fume
	TWA: 0.1 mg/m ³ inhalable	(vacated) Ceiling: 5 mg/m ³	STEL: 3 mg/m ³
	fraction TWA: 0.02 mg/m ³ Mn	Ceiling: 5 mg/m ³ fume Ceiling: 5	g
	TWA: 0.1 mg/m ³ Mn	mg/m³ Mn	
Lithium Cobalt Oxide (CoLiO2)	TWA: 0.02 mg/m ³	-	
12190-79-3			
Supplier Trade Secret	TWA: 1 mg/m ³ respirable fraction	-	
Phosphate(1-), hexafluoro-, lithium	TWA: 2.5 mg/m ³ F	TWA: 2.5 mg/m ³ F	
21324-40-3		TWA: 2.5 mg/m ³ dust	
		(vacated) TWA: 2.5 mg/m ³	
Carbon black	TWA: 3 mg/m ³ inhalable fraction	TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³
1333-86-4		(vacated) TWA: 3.5 mg/m ³	TWA: 3.5 mg/m ³
			TWA: 0.1 mg/m ³ Carbon black in
			presence of Polycyclic aromatic
			hydrocarbons PAH

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health



Other Exposure Guidelines	Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters	
Appropriate engineering controls		
Engineering Measures	Showers Eyewash stations Ventilation systems	
Individual protection measures, suc	h as personal protective equipment	
Eye/Face Protection	None required for consumer use. If splashes are likely to occur:. Wear safety glasses with side shields (or goggles).	
Skin and Body Protection	None required for consumer use. Repeated or prolonged contact:. Wear protective gloves and protective clothing.	
Respiratory Protection	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.	
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Wash hands before breaks and immediately after handling the product.	

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical State Appearance Color	Solid containing liquid, Solid Black No information available	Odor Odor Threshold	None No information available
00101			
Property_	Values	Remarks Method	
pH	No data available	None known	
Melting / freezing point	No data available	None known	
Boiling point / boiling range	No data available	None known	
Flash Point	No data available	None known	
Evaporation Rate	No data available	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limit in Air			
Upper flammability limit	No data available		
Lower flammability limit	No data available		
Vapor pressure	No data available	None known	
Vapor density	No data available	None known	
Specific Gravity	No data available	None known	
Water Solubility	Virtually insoluble	None known	
Solubility in other solvents	No data available	None known	
Partition coefficient: n-octanol/wa	terNo data available	None known	
Autoignition temperature	No data available	None known	
Decomposition temperature	No data available	None known	
Kinematic viscosity	No data available	None known	
Dynamic viscosity	No data available	None known	
Explosive properties	No data available		
Oxidizing Properties	No data available		

Other Information

Softening Point VOC Content (%) Particle Size Particle Size Distribution

No data available No data available No data available

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

None known based on information supplied.

Incompatible materials

Strong acids. Strong oxidizing agents. Strong bases.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	
Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.
Eye Contact	Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to eyes. May cause redness, itching, and pain. May cause temporary eye irritation.
Skin Contact	Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to skin. Prolonged contact may cause redness and irritation.
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Iron	= 984 mg/kg (Rat)	-	-
7439-89-6			
Nickel	> 9000 mg/kg (Rat)	-	-
7440-02-0			



Carbon black	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-
1333-86-4			

Information on toxicological effects

Symptoms

5	Erythema (skin redness). May cause redness and tearing of the eyes. Itching. Rashes.
	Hives.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization	May cause sensitization of susceptible persons. May cause sensitization by skin contact. May cause sensitization by inhalation.
Mutagenic Effects	No information available.
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen. This product contains carbon black which is classified as a possible carcinogen when present as respirable dust. This is not relevant for this product since it is not in a respirable form.

Chemical Name	ACGIH	IARC	NTP	OSHA
Lithium nickel oxide (LiNiO2) 12031-65-1	A1	Group 1	Known	Х
Nickel 7440-02-0		Group 1 Group 2B	Reasonably Anticipated	Х
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	A3	Group 2B		Х
Supplier Trade Secret		Group 3		
Carbon black 1333-86-4	A3	Group 2B		Х

ACGIH (American Conference of Governmental Industrial Hygienists) A1 - Known Human Carcinogen A3 - Animal Carcinogen IARC (International Agency for Research on Cancer) Group 1 - Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans Group 3 - Not Classifiable as to Carcinogenicity in Humans NTP (National Toxicology Program) Known - Known Carcinogen Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen OSHA (Occupational Safety and Health Administration of the US Department of Labor) X - Present **Reproductive Toxicity** No information available. STOT - single exposure No information available. STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE).

Chronic ToxicityNo known effect based on information supplied. Contains a known or suspected
carcinogen. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May
cause adverse effects on the bone marrow and blood-forming system. May cause adverse
liver effects. Carbon black has been classified by the International Agency for Research on
Cancer (IARC) as possibly carcinogenic to humans (Group 2B) by inhalation.

Target C	Drgan	Effects
----------	-------	---------

Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Blood. Central Nervous System (CNS). Central Vascular System (CVS). Kidney. Liver. Lungs. Nasal cavities.

Aspiration Hazard

No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 2,906.00 mg/kg ATEmix (dermal) 12,456.00 mg/kg (ATE) ATEmix (inhalation-dust/mist) 2,265.00 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Very toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Iron 7439-89-6		96h LC50: = 13.6 mg/L (Morone saxatilis)		
Copper 7440-50-8	96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50: = 0.112 mg/L (Poecilia reticulata) 96h LC50: = 0.3 mg/L (Cyprinus carpio) 96h LC50: = 0.8 mg/L (Cyprinus carpio) 96h LC50: = 1.25 mg/L (Lepomis macrochirus) 96h LC50: = 0.052 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.2 mg/L (Pimephales promelas) 96h LC50: < 0.3 mg/L (Pimephales promelas)		48h EC50: = 0.03 mg/L
Nickel 7440-02-0	72h EC50: = 0.18 mg/L (Pseudokirchneriella subcapitata) 96h EC50: 0.174 - 0.311 mg/L (Pseudokirchneriella subcapitata)	96h LC50: > 100 mg/L (Brachydanio rerio) 96h LC50: = 1.3 mg/L (Cyprinus carpio) 96h LC50: = 10.4 mg/L (Cyprinus carpio)		48h EC50: > 100 mg/L 48h EC50: = 1 mg/L
Carbon black 1333-86-4				24h EC50: > 5600 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

No information available

Other adverse effects

No information available.



13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated Packaging Dispose of contents/containers in accordance with local regulations.

D011

US EPA Waste Number

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Nickel	(hazardous constituent - no	Included in waste streams:		
7440-02-0	waste number)	F006, F039		

California Hazardous Waste Codes 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Copper 7440-50-8	Toxic
Nickel 7440-02-0	Toxic powder Ignitable powder
Aluminum 7429-90-5	Ignitable powder
Manganese 7439-96-5	Ignitable powder
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	Toxic

14. TRANSPORT INFORMATION

Note:	The transportation of primary lithium cells and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code and the US Department of Transportation. The batteries must meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation Iisted in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard Passenger Aircraft; Final Rule) Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision 188 of IMO-IMDG Code"
DOT Proper Shipping Name Hazard Class	NOT REGULATED NON REGULATED N/A
TDG	Not regulated
MEX	Not regulated
ICAO	Not regulated

IATA Proper Shipping Name Hazard Class	Not regulated NON REGULATED N/A
IMDG/IMO Hazard Class EmS-No.	Not regulated N/A F-A, S-I
RID	Not regulated
ADR	Not regulated
ADN	Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL	All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Copper - 7440-50-8	7440-50-8	5 - 10	1.0
Lithium nickel oxide (LiNiO2) - 12031-65-1	12031-65-1	1 - 5	0.1
Nickel - 7440-02-0	7440-02-0	1 - 5	0.1
Aluminum - 7429-90-5	7429-90-5	1 - 5	1.0
Lithium manganese oxide (LiMn2O4) - 12057-17-9	12057-17-9	1 - 5	1.0
Manganese - 7439-96-5	7439-96-5	1 - 5	1.0
Lithium Cobalt Oxide (CoLiO2) - 12190-79-3	12190-79-3	1 - 5	0.1
SARA 311/312 Hazard Categories			
Acute Health Hazard	No		
Chronic Health Hazard	No		
Fire Hazard	No		
Sudden release of pressure hazard	No		
Reactive Hazard	No		

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Copper 7440-50-8		Х	Х	
Lithium nickel oxide (LiNiO2) 12031-65-1		Х		
Nickel 7440-02-0		Х	Х	

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Copper 7440-50-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Nickel 7440-02-0	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

US State Regulations

<u>California Proposition 65</u> This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65	
Lithium nickel oxide (LiNiO2) - 12031-65-1	Carcinogen	
Nickel - 7440-02-0	Carcinogen	
Carbon black - 1333-86-4	Carcinogen	
Lithium carbonate - 554-13-2	Developmental	
Titanium dioxide - 13463-67-7	Carcinogen	

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Carbon 7440-44-0			Х		
Copper 7440-50-8	Х	X	Х	Х	Х
Lithium nickel oxide (LiNiO2) 12031-65-1			Х	Х	Х
Nickel 7440-02-0	Х	Х	Х	Х	Х
Aluminum 7429-90-5	X	Х	Х	Х	
Dimethyl carbonate 616-38-6	X	Х	Х		
Manganese 7439-96-5	X	Х	Х	Х	Х
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	X		Х	Х	Х
Oxygen 7782-44-7	X	Х	Х		
Supplier Trade Secret	Х				
Carbon black 1333-86-4	Х	Х	Х		Х
Lithium carbonate 554-13-2	Х	Х		Х	
Tin 7440-31-5	Х	Х	Х		
Silver 7440-22-4	Х	Х	Х	Х	

International Regulations

Mexico

National	occupational	exposure	limits	

Component	Carcinogen Status	Exposure Limits



Copper 7440-50-8(5 - 10)	Mexico: TWA= 1 mg/m ³ Mexico: TWA= 0.2 mg/m ³ Mexico: STEL= 2 mg/m ³
Nickel 7440-02-0(1 - 5)	Mexico: TWA 1 mg/m ³
Aluminum 7429-90-5 (1-5)	Mexico: TWA= 10 mg/m ³
Lithium manganese oxide (LiMn2O4) 12057-17-9(1-5)	Mexico: TWA 0.2 mg/m ³
Manganese 7439-96-5(1 - 5)	Mexico: TWA 0.2 mg/m ³ Mexico: TWA 1 mg/m ³ Mexico: STEL 3 mg/m ³
Carbon black 1333-86-4 (0.1 - 1)	Mexico: TWA 3.5 mg/m ³ Mexico: STEL 7 mg/m ³

Mexico - Occupational Exposure Limits - Carcinogens

Canada WHMIS Hazard Class Non-controlled

16. OTHER INFORMATION				
NFPA	Health Hazards 1	Flammability 0	Instability 0	Physical and Chemical Hazards -
HMIS	Health Hazards 0	Flammability 0	Physical Hazard 0	Personal Protection
Prepared By	23 British	Stewardship American Blvd. NY 12110 2-6501		
Revision Date Revision Note	02-Feb-2015 No information available			

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

