

Installation Instructions

THOROUGHLY READ THIS INSTRUCTION SHEET BEFORE STARTING.



Required tools: felt tip marker, tape measure or ruler, scissors or utility knife.

IMPORTANT WARNINGS:

1. Never Restrict Airflow into the Burner Area on a gas water heater, (located at the tank bottom).

2. Do not cover or restrict the top venting hood, the pressure relief valve, (located on top or side of the tank), or the burner access cover.

3. Do not put material over access cover or the wiring connection box on electric tanks.

4. DO NOT BLOCK any vent holes.

5. BEGIN Installation BY WRAPPING THE WATER HEATER, STARTING AT THE TOP OF THE TANK.

Extend the material above the top of the tank and “slice” the material like a pizza, folding down the flaps to cover the top of the tank. Cut as many strips as needed to cover the tank. Tape these strips together to make a “jacket” for the tank. Face the foil side of material away from the tank. Do not tape to the tank at this time.

FINISH: CUT OPENING IN THE JACKET TO ALLOW EXPOSURE OF THE POP OFF VALVE AND PIPE. Cut out holes for burner cover, controls, drain, etc. Make a hole about (2) inches larger than access opening to allow plenty of airflow around burner area.

Optional: You may want to tape the jacket to the tank around the access hold. This will keep the edges secure.