



MODEL	FG7750PBE
ITEM#	F2E625E891
UPC	814726022402
PERFORMANCE	
FREQUENCY	60Hz
PEAK WATTS	GAS/LPG: 7750W/7500W
RUNNING WATTS	GAS/LPG: 6250W/6000W
ENGINE	
Engine Type	Single Cylinder, 4 Stroke, OHV, Air Cooled
Displacement	420cc
Noise Level (@7m)	≤ 76dBA
Low Oil Sensor	YES
Starter Type	Recoil,Eletric Push
CONTROL PANEL	
Outlets	Two 120V 20A Duplex GFCI Outlets One 120V AC 30A Twist-lock Outlet (NEMA L5-30) One 120/240V AC 30A Twist-Lock (NEMA L14-30) Outlet
AVR	YES NO
Voltage Selector	NO N/A
DC Voltage Regulator Hours Meter	YES
Rubber Outlet Dust Covers	YES
OVERALL DESIGN	
OVERALL DESIGN	
Frame Style	Heavy Duty, Premium Design, Easy to Move, & Compact to Store
Frame Structure	Heavy Duty Ø1-1/4" (32mm) Steel Tubing
Frame Finish	Powder Coated
Frame Color	Black

Color Scheme	Ford Blue on Matted Black
Handle Type	Fold Down / Cushion Grip
Wheel Type	Ford 150 Chrome Look 10"x 3" (25.4 x 7.6 cm) No Flat Foam Tires with Heavy Duty Hub
Axles	Consumer Installed Zinc Plated Short Axles with Hitch-Pin
OTHER FEATURES	
High Capacity Fuel Tank	6.6 gal. (25L)
Typical Run time @ 50% Load	10.5hrs.
1	
Fuel Gauge	YES
Battery Type	9AH
ACCESSORIES	
Quick Start Guide	YES
Manuals	User Instruction & Engine Manual
	Includes Spark Plug T Wrench, 10mm Combination Wrench & Phillips Screw Driver funnel
Tool Pouch	
Engine Oil	Included 10W30 38oz. (1.1L) with Oil Spout Cap
CERTIFICATIONS	
	YES
CSA EPA3	YES
CARB	NO
PACKAGING	
Create Weight	OEka
Gross Weight	95kg Color Box
Carton Type Outside Dimensions (L x W x H)	800x555x575mm
ISTA3A	YES
SHIPPING	
4010.05	208
40HQ Qty. WARRANTY	200
Labor	1 Year Limited
Parts	2 Years Limited