

MATERIAL SAFETY DATA SHEET

MSDS Number: 1601E

Section 1 Trade Name:	PRODUCT AND COMPANY IDENTIFICATION OATEY SILVER LEAD FREE PLUMBING WIRE SOLDER OATEY SAFE-FLO LEAD FREE PLUMBING WIRE SOLDER
Product Nos.:	23000, 23001, 23002, 29030, 29024, 29025, 53061, 53180, 53062, 53188, 53064, 53195, 50683, 50684, 50691, 50692, 53013, 53186, 48311, 48312, 48313, 48313
Product Use:	Solder for copper water lines
Formula:	See Section 3
Synonyms:	Solder
Firm Name &	Oatey Company 4700 West 160th Street, Cleveland, Ohio 44135
Address:	www.oatey.com
Firm Phone No:	(216) 267-7100
Emergency Phone	For Emergency First Aid call 1-877-740-5015. For chemical transportation
Nos.:	emergencies ONLY, call Chemtrec at 1-800-424-9300. Outside the U.S. 1-703-527-3887.
Prepared by:	Technical Department
Preparation Date:	04/07/10

Section 2 HAZARDS IDENTIFICATION

Emergency Overview:

Silver-gray wire metal. The fumes may be hazardous during soldering operations. Fumes can cause eye irritation and may cause headache and respiratory system irritation. Ingestion of metal alloys may be harmful.

OSHA Hazard Classification: Not hazardous as is. In use, irritant and organ effects.

Section 3 COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENTS:	<u>%wt/wt :</u>	CAS NUMBER:	ACGIH TLV TWA:	OSHA PEL TWA
Tin	60 - 100%	7440-31-5	2 mg/m3	2 mg/m3
Copper	1 - 5%	7440-50-8	0.2 mg/m3(fume) 1 mg/m3(dust)	0.1 mg/m3(fume) 1 mg/m3(dust)
Bismuth	1 - 5%	7440-69-9	None	None
Silver	1 - 5%	7440-22-4	0.1 mg/m3	0.1 mg/m3

Section 4 Skin:	FIRST AID MEASURES If irritation arises, wash thoroughly with soap and water. Seek medical attention if irritation persists.
Eyes:	If material gets into eyes, immediately flush eyes with water while holding eyelids open until material is removed. If irritation persists, seek medical attention.
Inhalation:	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Keep victim quiet and warm. Call a poison control center or physician immediately.
Ingestion:	DO NOT INDUCE VOMITING. Ingestion is not a likely route of entry. Never give anything by mouth to a person who is unconscious or drowsy. Get medical attention by calling a Poison Control Center, or hospital emergency room.

Section 5 FIRE FIGHTING MEASURES

Flashpoint / Not applicable

Method:		
Flammability:	LEL = Not applicable, UEL = Not applicable	
Extinguishing Media:	Use appropriate means of extinguishing surrounding fire.	
Special Fire	Not applicable	
Fighting		
Procedure: Unusual Fire	None known	
And Explosion		
Hazards:		
Hazardous	Material will not decompose under normal conditions. If overheated, oxides of	
Decomposition	tin, bismuth, copper and silver may result.	
Products:		
Section 6	ACCIDENTAL RELEASE MEASURES	
Spill or Leak	Collect solid and place in properly labeled containers for recycle or disposal.	
Procedures:		
Section 7	HANDLING AND STORAGE	
Handling:	Avoid inhalation of fumes, vapors or dust. Keep away from children. Wash	
	thoroughly after handling before eating, drinking, or smoking.	
Storage:	Store in a cool, dry place away from heat or open flame.	
Other:	None	
Section 8 Ventilation:	EXPOSURE CONTROLS/PERSONAL PROTECTION Good general ventilation (equivalent to outdoors) should be adequate for normal	
Venerration	use. For operations where the TLV may be exceeded, mechanical ventilation such	
	as local exhaust may be needed to maintain exposure levels below applicable	
	limits.	
Respiratory	For operations where the TLV may be exceeded, a NIOSH approved organic vapor	
Protection:	respirator or supplied air respirator is recommended. Equipment selection	
	depends on contaminant type and concentration, select in accordance with 29 CFR	
	1910.134 and good industrial hygiene practice.	
Skin Protection:	Wear gloves and long sleeves to avoid direct contact with skin.	
Еуе	Safety glasses with side shields or safety goggles.	
Protection:		
Other:	Eye wash and safety shower should be available.	
Section 9	PHYSICAL AND CHEMICAL PROPERTIES	
Boiling Point	: Not determined	
Melting Point	: 415 to 455 Degrees F (213 to 235 Degrees C)	
Vapor Pressur		
Vapor Density	: (Air = 1) Greater than 1	

Vapor Pressure:	Not determined
Vapor Density:	(Air = 1) Greater than 1
Volatile Components:	None
Solubility In Water:	Negligible
pH:	Not applicable
Specific Gravity:	9 to 11
Evaporation Rate:	Not applicable
Appearance:	Silver-gray wire metal
Odor:	None
Will Dissolve In:	Not applicable
Material Is:	Solid

Section 10STABILITY AND REACTIVITYStability:Stable.Conditions ToDo not heat over 480 degrees F (250 degrees C).

Avoid: Hazardous If overheated, oxides of tin, bismuth, copper and silver. Decomposition Products: Incompatibility/ None. Materials To Avoid: Hazardous Will not occur. Polymerization:

Section 11	TOXICOLOGICAL INFORMATION
Inhalation:	Fumes from soldering operations may be irritating to the respiratory system. Prolonged exposure to fumes may cause stannosis, a mild benign
	pneumoconiosis. Repeated inhalation of fumes may cause occupational asthma.
	Symptoms may be delayed.
Skin:	Fumes may cause irritation.
Eye:	Fumes may cause irritation.
Ingestion:	Ingestion may cause abdominal pain, nausea, vomiting, diarrhea, gastrointestinitis, or internal cuts. Long term chronic ingestion may damage the liver, kidneys, nervous system and gastrointestinal system.
Toxicity Data:	No data available.
Sensitization:	None of the components are known to cause sensitization.
Carcinogenicity	7: None of the components are listed as a carcinogen or suspect carcinogen by NTP, IARC or OSHA.
Mutagenicity:	None of the components have been found to be mutagenic.
Reproductive Toxicity:	None of the components are known to cause adverse reproductive effects.
Medical	Persons with pre-existing skin, lung, kidney or liver disorders may be at
Conditions	increased risk from exposure to the fumes of this product.
Aggravated By	
Exposure:	

Section 12 ECOLOGICAL INFORMATION No data available. Keep out of waterways.

Section 13 DISPOSAL CONSIDERATIONS

Waste Disposal: Dispose of in accordance with federal, state, and local regulations. It is the responsibility of the end-user to determine at the time of disposal of the product. RCRA Hazardous Waste None Number: EPA Hazardous Waste None ID Number: EPA Hazard Waste None. Number:

Section 14 TRANSPORT INFORMATION

DOT	
UN/NA Number:	None
Proper Shipping Name:	Not regulated
Hazard Class:	None
Packing Group:	None
Hazard Labels:	None
IMDG	
UN Number: None	
Proper Shipping Name:	Not regulated
Hazard Class:	None
Packing Group:	None
Label:	None

Section 15 REGULATORY INFORMATION

Hazard Category for Acute and chronic health hazards. Section 311/312:

Section 302 This product does not contain chemicals regulated under SARA Section 302. Extremely Hazardous Substances (TPQ): Section 313 Toxic This product contains the following chemicals subject to SARA Title III Chemicals: Section 313 Reporting requirements:

Chemical	CAS #	% wt
Copper	7440-50-8	1 - 5%
Silver	7440-22-4	1 - 5%

CERCLA 103 Reportable Quantity:	This product contains no chemicals subject to CERCLA reporting.
California Proposition 65:	This product does not contain any chemicals subject to California Proposition 65 regulations.
TSCA Inventory Canadian WHIMS Classification:	All of the components of this product are listed on the TSCA inventory. Not a controlled product. This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

Section 16 OTHER INFORMATION

NFPA and HMIS: NFPA Hazard Signal: Health: 1 Flammability: 0 Reactivity: 0 Special: None HMIS Hazard Signal: Health: 1 Flammability: 0 Reactivity: 0 PPE: B

Disclaimer:

The information herein has been compiled from sources believed to be reliable, up-to-date, and is accurate to the best of our knowledge. However, we cannot give any guarantees regarding information from other sources, and expressly do not make warranties, nor assume any liability for its use.

Template: tmpl-so-e1