


Installation

Novostrip aluminium is a very easy to install profile.

1. Mark the place to install the Novostrip. This profile is intended to be inserted in its full length, so it will be necessary to identify the beginning and the end of the position to draw a cutting line.
2. Cut the floor using a 3 mm width blade along the line with a depth not less than 7 mm.
3. Clean the groove and fill it with adhesive (polyurethane mastic or similar)
4. Insert the profile into the groove and be sure it fits perfectly in width and it makes contact with the flooring.
5. Let dry.

You can repeat the installation to install as many profiles as you need, creating your own pattern.

This profile has been developed for high thickness floorings (marble, terrazzo, granite...) Nevertheless, you can install it with thinner floorings, like ceramics, by joining the tiles below the visible side as it is shown in the drawing.



Cleaning and maintenance

Novostrip Aluminium resists water and detergents. The cleaning must be done periodically with a soft cloth. If you use a neutral liquid cleaner, you must rinse the profile with cold water and dry to remove excess moisture. If dirtiness persists, clean the profile with a solution with clean water and detergent or neutral soap 5%, brushing with a cloth with no particles that could scratch the finish. Outdoors, rainfall will clean the profile.

Steel wool, abrasive cleaners, souring products as well as strong acids (hydrochloric and perchloric), strong bases (caustic soda or ammonia) or carbonated solutions are not recommended. Citric acid is neither recommended because it dissolves the protective layer of the surface of aluminium. Waxes, petrolatum, lanolin or similar substances are not appropriate. Solvents containing haloalkanes (hydrofluoroether and chlorinated solvents) and curing accelerators containing chlorides should not be used (use special accelerators free of chlorides).

Technical information

You can find out more information about the technical features of the Emac®'s products by downloading its Technical Files in www.emac.es.

If you have any query, please contact our Technical Department in tecnico@emac.es



Outdoors



Indoors



Flooring

Emac Complementos S.L. (Spain) info@emac.es // Emac America L.L.C. (FL,USA) info@emac-america.com // Emac Italia S.R.L. (Italy) info@emac-italia.it

www.emac.es

*The data provided are for information only and have been obtained by our supplier or Emac®.
Does not constitute legal guarantee in terms of properties and / or functionality of the application of material*