



BEHR PREMIUM® Concrete & Masonry Bonding Primer

No. 880 Clear

- Interior/Exterior
- Helps Prevent Peeling of Topcoats
- Easy to Apply
- Promotes A Uniform Topcoat Finish



Coverage:
33-47 m²



Dry Time:
2 Hr. Dry to Touch
4 Hr. Ready for Topcoat



Clean-Up:
Use Commercial
Brush Cleaner



Protect
from Freezing

PRODUCT DRIES CLEAR- IT WILL LOOK MILKY IN CAN AND AT INTIAL APPLICATION.

CAUTION: Surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.

WHERE TO USE

Uncoated Interior or Exterior surfaces such as Concrete, Masonry, and any Porous Stone or Brick. Not designed for use on wood, metal or silicone treated surfaces. Do not use on coated surfaces. Use only on porous surfaces. Not for use on vertical surfaces. **NOTE: SOME SURFACES MAY APPEAR SLIGHTLY DARKER AFTER PRODUCT DRIES.**

PREPARATION†

(Proper surface preparation is required.) New concrete must cure for a minimum of 30 days prior to priming. Patch all holes and cracks and allow to dry. For touch-ups where surface coatings have failed, completely remove any loose or peeling paint. Do not apply over previously coated surfaces. To completely strip previous coatings, use a product such as BEHR PREMIUM® No. 992 Concrete & Masonry Paint Stripper. For proper penetration and adhesion of primer, use a product such as BEHR PREMIUM No. 991 Concrete & Masonry Cleaner & Etcher to clean and etch the surface. Test: Sprinkle a few drops of water onto the surface. If water is quickly absorbed, the surface is ready. If not absorbed strip or re-etch. Follow all label instructions.

APPLICATION

DO NOT THIN. Stir primer thoroughly before and occasionally during application. Use product when air and surface temperatures are between 50 - 90° F (10 - 32° C). Apply using a high quality pump sprayer, 10-13 mm nap roller, nylon/polyester brush or a pad applicator.

DRY TIME

Longer dry time required in cooler temperatures and in higher humidity. **Must apply a topcoat after at least 4 hours, but before 30 days.**

DISPOSAL

Do not use soap and water to clean brushes or other applicators as they will become gummy. Properly dispose of all soiled rags. To recycle or properly dispose of product in your community, contact your household refuse collection service.

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead

LIMITED WARRANTY If this product is found to be defective upon inspection by an expert, Behr Process Corporation will, at its option, and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. This warranty is not transferable. If you believe this product is defective, contact Behr Process Corporation at 2750 Centre Avenue N.E., Calgary, AB T2A2L3. The cost of transportation or shipping, if any, are to be assumed by the consumer. The clause of limitation of liability which follows is inapplicable in Quebec: **This warranty excludes (1) labour and costs of labour for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** The above provisions are not intended to operate where prohibited by law. This limited warranty is the only warranty provided by Behr Process Corporation unless extended by a provincial consumer statute.

To consult with a Behr Certified Coatings Professional, call 1-800-661-1591.

CAUTION! IRRITANT! HARMFUL IF SWALLOWED. MAY IRRITATE EYES. Avoid contact with eyes and clothing. Do not breathe fumes. Wear eye protection and protective clothing. Use only with adequate ventilation. **FIRST AID TREATMENT:** Contains acrylic polymers. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 20 minutes. If on skin, rinse well with water. If inhaled, move person to fresh air.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.

BEHR
A Masco Company

©2016 Behr Process Corporation
Santa Ana, CA 92704 U.S.A. • behr.com
V.O.C. (C.O.V.) <100 g/L • REV. 8/16