



The FS100 series of stepladders feature HolsterTops with the Lock-In System that allows you to customize your ladder top. The system secures tools from falling while keeping them handy while working all the while increasing productivity on the job. The tops also hold tools and have a sturdy paint can hanger on the back side. The external spreaders are pinch proof and the TRACTION-TRED® steps are slip resistant. These stepladders have a duty rating of 250 pounds and offer the EDGE® bracing for enhanced strength and increased protection against damage. Fiberglass rails are non-conductive for working near electricity.

## Features

- Back-up plates to reinforce top connectors
- Designed for one person jobs
- Every rivet backed up by metal plate or washer to protect fiberglass
- External Spreaders
- Molded braces
- Slip-resistant foot pad
- Slip-resistant Traction-Tred steps

## Dimensions

Feature	Size
Top Dimension	5-3/4 in x 13 in
Front Rails Dimension	3-1/8 in
Front Flange Dimension	1-1/8 in
Rear Rails Dimension	1-3/4 in
Rear Flange Dimension	1-3/16 in Back, 5/8 in Front
Steps Dimension	3 in

# Specifications

Feature	Size / Details
Size	8 ft
Reach Height	12 ft
Max. Standing Height	5 ft 9 in
Description of Top Features	Paint tray slot, can hook, Lock in accessory sockets, 4 tool holes, drill hole, p int, quart & gallon paint can, parts tray
Edge Bracing	Medium
Load Capacity	250 lbs
Type	Type I Duty Rating
Performance Rating	★★★
Material	Fiberglass
Approx. Width	25 in
Approx. Spread	53-1/2 in
With Pail Shelf	No
Spreader Material	Steel
Certifications	ANSI A14.5 (2007); OSHA
Approx. Cu. Ft. Per Unit	6.8
Approx. Shipping Wt. Lbs.	25.5