

# **Material Safety Data Sheet**

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: 160Z REVITALIZING LEMON OIL

 Product code:
 461700

 Print Date:
 22/May/2012

 Revision Date:
 15/May/2012

**Recommended use:** For coating metal containers and similar products.

**Company Identification:** The Valspar Corporation

PO Box 1461

Minneapolis, MN 55440

**Manufacturer's Phone:** 1-612-851-7000

**Australia Poisons Information** 

131-126

Centre 24 hours:

### 2. HAZARDS IDENTIFICATION

Classified as hazardous according to criteria of NOHSC.

Classified as NON-DANGEROUS according to Australian Dangerous Goods Code.

R52/53 - Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### S-phrase(s)

S23 - Do not breathe gas/fumes/vapour/spray.

S51 - Use only in well-ventilated areas.

# 3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient Name	Approx.	Chemical Name
CAS-No.	Weight %	
2-(2-	5-10	Diethylene glycol monobutyl ether
<b>BUTOXYETHOXY)ETHANOL</b>		
112-34-5		

3. COMPOSITION / INFORMATION ON INGREDIENTS			
REACTION PRODUCT OF METHYL BENZOTRIAZOL AND PEG 300 104810-48-2	0.2-0.5	Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]omegahydroxy-	
REACTION PRODUCT OF BENZOTRIAZOL PROPIONATE AND PEG 300 104810-47-1	0.1-0.2	Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]omega[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxoprop	

If this section is blank, there are no hazardous components per NOHSC guidelines.

# 4. FIRST AID MEASURES

#### General

If symptoms persist, call a physician. Never give anything by mouth to an unconscious person.

#### Skin:

Take off all contaminated clothing immediately. Wash off immediately with soap and plenty of water. Do NOT use solvents or thinners.

### Eyes:

Remove contact lenses. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Keep eye wide open while rinsing.

#### Inhalation:

Move to fresh air. If victim is unconscious but breathing: Victim to lie down in the recovery position, cover and keep him warm. If not breathing, give artificial respiration. Obtain medical attention.

### Ingestion:

Keep at rest. If swallowed, seek medical advice immediately and show this container or label. Do NOT induce vomiting.

### 5. FIRE FIGHTING MEASURES

Hazchem Code: None Allocated

Flash point: 106
Lower explosive limit: 1
Upper explosive limit: 6

Autoignition temperature: not determined

### The following actions are recommended

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Fire will produce dense black smoke containing hazardous combustion products (see heading 10).

Wear self contained breathing apparatus for fire fighting if necessary.

Cool containers / tanks with water spray.

### Suitable extinguishing media

Suitable extinguishing media

Alcohol-resistant foam

Carbon dioxide (CO2)

Dry powder

Extinguishing media which must not be used for safety reasons

High volume water jet

# 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions:

Exclude non essential personnel. Remove all sources of ignition. Ensure adequate ventilation. Do not breathe vapours/dust.

# **6. ACCIDENTAL RELEASE MEASURES**

#### **Environmental precautions:**

Local authorities should be advised if significant spillages cannot be contained.

### Methods for cleaning up:

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Clean with detergents. Avoid solvents.

### 7. HANDLING AND STORAGE

#### Handling:

Operators should wear anti-static footwear and clothing. Use only non-sparking tools. Good housekeeping standards and regular safe removal of waste materials will minimise the risks of spontaneous combustion and other fire hazards. Vapours are heavier than air and may spread along floors. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Provide adequate ventilation. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Keep container tightly closed. Keep away from open flames, hot surfaces and sources of ignition. Avoid contact with skin and eyes. Do not breathe vapours or spray mist. When using, do not eat, drink or smoke. Do not use pressure to empty drums. Store in original container.

### Storage:

Containers which are opened must be carefully resealed and kept upright to prevent leakage. Take notice of the directions of use on the label. Keep in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition. Keep away from direct sunlight. Store in a place accessible by authorized persons only. Do not smoke.

### Storage temperature:

10 - 30 C

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### **Exposure limits:**

# Australia:

### **Engineering measures:**

During curing, decomposition products may be formed, which should be extracted safely from the work area. Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

#### **Basic Personal Protection**

### Respiration

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

# Hand protection:

Wear suitable gloves and eye/face protection. Use protective skin cream before handling the product.

### Skin:

Wear as appropriate: Flame retardant antistatic protective clothing Wear shoes with conductive soles.

#### Eves:

Wear as appropriate: Safety glasses with side-shields Goggles

#### Hygiene measures:

Do not use solvents or thinners to clean skin. When using, do not eat, drink or smoke. Wash hands before breaks and at the end of workday. It is good practice in industrial hygiene to avoid contact with solvents by using appropriate protective measures whenever possible.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: liquid

**Vapor pressure:** .0203008 mmHg @68° F (20° C)

**Vapor density (air = 1.0):** 5.6

Solubility in water: not determined

Flash point: 106°C Boiling point/range 150°C

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Specific Gravity

.87

### 10. STABILITY AND REACTIVITY

**Stability:** Stable under normal conditions.

**Conditions to avoid:** Stable under recommended storage conditions.

Materials to avoid: Keep away from oxidising agents, strongly alkaline and strongly acid materials in

order to avoid exothermic reactions.

Hazardous Polymerization:

**Hazardous decomposition** 

products:

Hazardous decomposition products may be produced when the recommended

processing temperatures or times are exceeded.

Carbon monoxide Carbon dioxide (CO2)

None anticipated.

Smoke

nitrogen oxides (NOx)

# 11. TOXICOLOGICAL INFORMATION

#### **Potential Acute Health Effects:**

Eve contact:

May cause eye irritation.

Skin contact:

May cause skin irritation.

Ingestion:

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Inhalation:

May cause irritation of respiratory tract.

### **Target Organ and Other Health Effects:**

Contains glycol ether which has been shown to cause blood effects damage in laboratory animals.

Liver injury may occur.

Causes headache, drowsiness or other effects to the central nervous system.

Kidney injury may occur.

If this section is blank, no information is available.

# 12. ECOLOGICAL INFORMATION

#### **Air Pollutant**

Local pollution requirements may apply to the use of this product. Do not let product enter drains. Do not contaminate surface water.

### 13. DISPOSAL CONSIDERATIONS

# Waste disposal methods:

Do not let product enter drains. Do not contaminate ponds, waterways or ditches with chemical or used container. Where possible recycling is preferred to disposal or incineration. Dispose of as special waste in compliance with local and national regulations.

### 14. TRANSPORTATION INFORMATION

Australia ADG:

Proper shipping name: NOT REGULATED Hazchem Code: None Allocated

IMDG:

Proper shipping name: NOT REGULATED

# 14. TRANSPORTATION INFORMATION

IATA:

Proper shipping name: NOT REGULATED

# 15. REGULATORY INFORMATION

#### **AICS Australian Inventory:**

This product/preparation is in compliance with the Australian Inventory of Chemical Substances (AICS) list.

#### **Label Information:**

#### contains

D-LIMONENE, REACTION PRODUCT OF METHYL BENZOTRIAZOL AND PEG 300, REACTION PRODUCT OF BENZOTRIAZOL PROPIONATE AND PEG 300

#### Indication of danger:

none.

R52/53 - Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### S-phrase(s)

S23 - Do not breathe gas/fumes/vapour/spray.

S51 - Use only in well-ventilated areas.

Contains sensitising components

REACTION PRODUCT OF BENZOTRIAZOL PROPIONATE AND PEG 300, REACTION PRODUCT OF METHYL BENZOTRIAZOL AND PEG 300, D-LIMONENE

### 16. OTHER INFORMATION

 Print Date:
 22/May/2012

 Revision Date:
 15/May/2012

Abbreviations:

NOHSC - National Occupational Health and Safety Commission, AICS - Australia Inventory of Chemical Substances, EC - European Community, ADR - Australia Code for the Transportation of Dangerous Goods by Road and Rail, IATA - International Air Transport Association, IMDG - International Maritime Dangerous Goods, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, WT - Weight, mg/m³ - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit

#### Disclaimer:

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.